

# FMA4X, FMA4P

## APARTMENT FAN COILS

### ALL MODELS

- 1-1/2, 2, 2-1/2, and 3 Tons
- Upflow application only
- Accessory field-installed electric heat kits available in 5, 7.5, or 10 kW
- 208/230-1-60 supply voltage
- Cabinet exterior is galvanized sheet metal
- Cabinet air leakage rate below 1.4% when tested to ASHRAE Standard 193
- Insulated for conditioned space (not to be installed in unconditioned spaces)
- All Aluminum coils

### FMA4P

- For use with R-410A refrigerant utilizing standard piston

### FMA4X

- R-410A refrigerant TXV standard

### PERFORMANCE

- PSC motor on all FMA4P
- ECM motor on all FMA4X
- Motor suspended on rubber grommets for quieter operation
- Fresh air intake knockouts in cabinet

### EASY TO INSTALL AND SERVICE

- Units fits between standard stud spacings
- All service access is located in the front
- Primary and secondary drain connections exit from the bottom, access panel in bottom of cabinet
- No return-air ductwork required in specific applications
- Wall hanging brackets included with the unit



Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to [www.ahridirectory.org](http://www.ahridirectory.org).

| UNIT PERFORMANCE DATA |             |             |                  |                |                                                     |                        |                       |       |
|-----------------------|-------------|-------------|------------------|----------------|-----------------------------------------------------|------------------------|-----------------------|-------|
| Model                 | Nominal BTU | Size (tons) | Nominal CFM(L/s) |                | Operating Dimensions height x width x depth in (mm) | Filter Size in(mm)     | Ship Weight lbs. (kg) | Notes |
|                       |             |             |                  |                |                                                     |                        |                       |       |
| FMA4P1800AL           | 18,000      | 1-1/2       | 450(212)         | 675(319)       | 36-1/2 x 20-1/2 x 15<br>(928 x 521 x 381)           | 16 x 20<br>(406 x 508) | 101 (46)              |       |
| FMA4P2400AL           | 24,000      | 2           | 600(283)         | 900(425)       |                                                     | 101 (46)               |                       |       |
| FMA4P3000AL           | 30,000      | 2-1/2       | 750(354)         | 1125(531)      | 39-1/2 x 22 x 19<br>(1004 x 559 x 483)              | 20 x 20<br>(508 x 508) | 123 (56)              |       |
| FMA4P3600AL           | 36,000      | 3           | 900(425)         | 1350(637)<br>) |                                                     |                        | 123 (56)              |       |
|                       |             |             |                  |                |                                                     |                        |                       |       |
| FMA4X1800AL           | 18,000      | 1-1/2       | 450(212)         | 675(319)       | 36-1/2 x 20-1/2 x 15<br>(928 x 521 x 381)           | 16 x 20<br>(406 x 508) | 101 (46)              |       |
| FMA4X2400AL           | 24,000      | 2           | 600(283)         | 900(425)       |                                                     |                        | 101 (46)              |       |
| FMA4X3000AL           | 30,000      | 2-1/2       | 750(354)         | 1125(531)<br>) | 39-1/2 x 22 x 19<br>(1004 x 559 x 483)              | 20 x 20<br>(508 x 508) | 123 (56)              |       |
| FMA4X3600AL           | 36,000      | 3           | 900(425)         | 1350(637)<br>) |                                                     |                        | 123 (56)              |       |