FUJITSU

SALES FACT SHEET

FO*13C SERIES

Efficiencies 13-15.5 SEER/11.5-13 EER
Nominal Sizes 1.5 to 5 Ton [5.28 to 17.6 kW]
Cooling Capacities 17.3 to 60.5 kBTU [5.7 to 17.7 kW]

Fujitsu Air Conditioners

Features:

- New composite base pan – dampens sound, captures louver panels, eliminates corrosion and reduces number of fasteners needed
- Powder coat paint system – for a long lasting professional finish
- Scroll compressor – uses 70% fewer moving parts for higher efficiency and increased reliability
- Modern cabinet aesthetics – increased curb appeal with visually appealing design
- Curved louver panels – provide ultimate coil protection, enhance cabinet strength, and increased cabinet rigidity
- Optimized fan orifice – optimizes airflow and reduces unit sound
- Rust resistant screws – confirmed through 1500-hour salt spray testing
- 3"-4"-5" service valve space – provides a minimum working area of 27-square inches for easier access
- 15" wide, industry leading corner service access – makes repairs easier and faster.
- External gauge port access – allows easy connection of "low-loss" gauge ports
- Single-row condenser coil – makes unit lighter and allows thorough coil cleaning to maintain "out of the box" performance
- Fewer cabinet fasteners – allow for faster access to internal components and hassle-free panel removal
- Service trays – hold fasteners or caps during service calls
- QR code – provides technical information on demand for faster service calls
- Fan motor harness with extra long wires allows unit top to be removed without disconnecting fan wire.

GENERAL TERMS OF LIMITED WARRANTY*

Fujitsu will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.
Conditional Parts
(Registration Required).....Ten (10) Years

***For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.**

Model FO*13C	Nominal Cooling Capacity	Voltage	Phase	Operating			Service Valve - Liquid	Service Valve - Suction	Shipping Lbs. [kg]	Price
				Width "W" Inches [mm]	Length "L" Inches [mm]	Height "H" Inches [mm]				
18	18,000	208/230	1	29.75 [755]	29.75 [755]	27 [685]	3/8"	3/4"	127 [57.6]	
24	24,000	208/230	1	29.75 [755]	29.75 [755]	25 [635]	3/8"	3/4"	142 [64.4]	
30	30,000	208/230	1	29.75 [755]	29.75 [755]	25 [635]	3/8"	3/4"	163 [73.9]	
36	36,000	208/230 208/230 460	1 3 3	29.75 [755]	29.75 [755]	27 [685]	3/8"	3/4"	164 [74.8]	
42	42,000	208/230 208/230 460	1 3 3	29.75 [755]	29.75 [755]	31 [787]	3/8"	7/8"	195 [88.4]	
48	48,000	208/230 208/230 460 & 575	1 3 3	33.75 [857]	33.75 [857]	27 [685]	3/8"	7/8"	202 [91.6]	
60	60,000	208/230 208/230 460 & 575	1 3 3	35.75 [908]	35.75 [908]	31 [787]	3/8"	7/8"	235 [106.6]	

[ ] Designates Metric Conversions

Accredited by the RvA
ISO 9001:2008
Certificate Number: 30064

ENERGUIDE
Seasonal Energy Efficiency Ratio (SEER)
THIS MODEL 15.5
13.0 — Uses least energy → 21.0

AHRI CERTIFIED
www.ahridirectory.org
Unitary Small AC
AHRI Standard 210/240
Certification applies only when the complete system is listed with AHRI

c UL us LISTED

Fujitsu General America, Inc.
353 Route 46 West, Fairfield, NJ 07004

FUJITSU

SALES FACT SHEET

ACCESSORIES

Description	Part No.	Price
Low Ambient Control (RXAD-A08)	RXAD-A08	
Crankcase Heater for 1.5 - 3 ton Models	44-17402-44	
Crankcase Heater for 3.5 - 5 ton Models	44-17402-45	
Low Pressure Control	RXAC-A07	
High Pressure Control	RXAB-A07	
Compressor Sound Cover 1.5 - 3 ton Models	68-23427-26	
Compressor Sound Cover 3.5 - 5 ton Models	68-23427-25	
Compressor Hard Start Kit	SK-A1	
Top Cap w/Label	91-101123-30	

Total Price $