

GAS CONNECTORS | YELLOW EPOX COATED



Stainless Steel Gas Appliance Connector

- 1/4" ID | 3/8" OD
- Male x Male

Spec Sheet: XXXXXXXX

Part No.	Sizing & Connection	Length	MC
G014YE101018	1/2" MIP (Tap 3/8" FIP) X 1/2" MIP (Tap 3/8" FIP)	18"	25
G014YE101024	1/2" MIP (Tap 3/8" FIP) X 1/2" MIP (Tap 3/8" FIP)	24"	25
G014YE101036	1/2" MIP (Tap 3/8" FIP) X 1/2" MIP (Tap 3/8" FIP)	36"	25

Features:

- -40°F to 150°F operating temperature
- Zinc-plated steel S45C fittings
- Yellow epoxy coated for extra safe-guard protection from common wear & tear



Stainless Steel Gas Appliance Connector

- 3/8" ID | 1/2" OD
- Male x Male

Spec Sheet: XXXXXXXX

Part No.	Sizing & Connection	Length	MC
G038YE101018	1/2" MIP (Tap 3/8" FIP) X 1/2" MIP (Tap 3/8" FIP)	18"	25
G038YE101024	1/2" MIP (Tap 3/8" FIP) X 1/2" MIP (Tap 3/8" FIP)	24"	25
G038YE101036	1/2" MIP (Tap 3/8" FIP) X 1/2" MIP (Tap 3/8" FIP)	36"	25
G012YE101036RP	1/2" MIP (Tap 3/8" FIP) X 1/2" MIP (3/8" FIP)	36"	
G038YE101048	1/2" MIP (Tap 3/8" FIP) X 1/2" MIP (Tap 3/8" FIP)	48"	25
G012YE101048RP	1/2" MIP (Tap 3/8" FIP) X 1/2" MIP (3/8" FIP)	48"	

Features:

- -40°F to 150°F operating temperature
- Zinc-plated steel S45C fittings
- Yellow epoxy coated for extra safe-guard protection from common wear & tear



Stainless Steel Gas Appliance Connector

- 1/4" ID | 3/8" OD
- Male x Female

Spec Sheet: XXXXXXXX

Part No.	Sizing & Connection	Length	MC
G014YE101118	1/2" MIP (Tap 3/8" FIP) X 1/2" FIP	18"	25
G014YE101124	1/2" MIP (Tap 3/8" FIP) X 1/2" FIP	24"	25
G014YE101124RP	1/2" MIP (Tap 3/8" FIP) X 1/2" FIP	24"	10
G014YE101136	1/2" MIP (Tap 3/8" FIP) X 1/2" FIP	36"	25
G014YE101136RP	1/2" MIP (Tap 3/8" FIP) X 1/2" FIP	36"	10
G014YE101148RP	1/2" MIP (Tap 3/8" FIP) X 1/2" FIP	48"	10

Features:

- -40°F to 150°F operating temperature
- Zinc-plated steel S45C fittings
- Yellow epoxy coated for extra safe-guard protection from common wear & tear



Stainless Steel Gas Appliance Connector


- 3/8" ID | 1/2" OD
- Male x Female

Spec Sheet: XXXXXXXX

Part No.	Sizing & Connection	Length	MC
G038YE101118	1/2" MIP (Tap 3/8" FIP) X 1/2" FIP	18"	25
G038YE101124	1/2" MIP (Tap 3/8" FIP) X 1/2" FIP	24"	25
G038YE101124RP	1/2" MIP (Tap 3/8" FIP) X 1/2" FIP	24"	10
G038YE101136	1/2" MIP (Tap 3/8" FIP) X 1/2" FIP	36"	25
G038YE101136RP	1/2" MIP (Tap 3/8" FIP) X 1/2" FIP	36"	10
G038YE111048	1/2" MIP (Tap 3/8" FIP) X 1/2" FIP	48"	25
G038YE101148RP	1/2" MIP (Tap 3/8" FIP) X 1/2" FIP	48"	10

Features:

- -40°F to 150°F operating temperature
- Zinc-plated steel S45C fittings
- Yellow epoxy coated for extra safe-guard protection from common wear & tear



Stainless Steel Gas Appliance Connector

- 1/4" ID | 3/8" OD
- Male x Female

Spec Sheet: XXXXXXXX

Part No.	Sizing & Connection	Length	MC
G014YE121372	3/8" MIP (Tap 1/4" FIP) X 3/8" FIP	72"	12

Features:

- -40°F to 150°F operating temperature
- Zinc-plated steel S45C fittings
- Yellow epoxy coated for extra safe-guard protection from common wear & tear



Stainless Steel Gas Appliance Connector w/Valve

- 3/8" ID | 1/2" OD
- Male x Female

Spec Sheet: XXXXXXXX

Part No.	Sizing & Connection	Length	MC
G038YE103130	1/2" MIP (Tap 3/8" FIP) X 1/2" FIP Ball Valve	30"	25

Features:

- -40°F to 150°F operating temperature
- Zinc-plated steel S45C fittings
- Yellow epoxy coated for extra safe-guard protection from common wear & tear