

Husky[™] K16WT Series Thermocouples

Description

K16WT Series thermocouples are heavy duty larger gauge copper tubing for lower load currents to operate. This thermocouple includes an adapter that attaches to a male terminal connector. This style of thermocouple can also be used with other manufacturers' standing pilots.

Agency Listing

 CSA (AGA/CGA) Certificate number 229521-1656071



Selection Chart

Part Number	Length	Replaces	Open Circuit mV Range
K16WT-48H	48 in. (1219 mm)	N/A	25 – 35 mV
K16WT-60H	60 in. (1524 mm)	N/A	25 – 35 mV
K16WT-72H	72 in. (1829 mm)	N/A	25 – 35 mV

Notes: Connects to valves with 11/32-32 female nut connector

Open Circuit: 17 mV minimum Closed Circuit: 8 mV minimum

Maximum Hot Junction Temperature: 1500°F (816°C)

The K16WT works better for situations where millivolt line loss needs to be kept to a minimum.

63499-WT Series "WT" Extension Kits

Description

63499-WT Series are used where additional length is needed. These kits adapt directly to the K16WT series only.

Agency Listing

None

Selection Chart

Part Number	Length	
63499-WT48H	48 in. (1219 mm)	
63499-WT60H	60 in. (1524 mm)	
63499-WT72H	72 in. (1829 mm)	

