

[Print](#)

H6062A1000/U

HumidiPRO Digital Humidity Control

Overview

Easy to use, digital control of your home's humidification or dehumidification. HumidiPRO™ will automatically adjust settings for changes in outdoor temperature to ensure no condensation will appear in your home (window protection).

Features

- Automatic humidification (window protection) with included outdoor sensor
- Manual humidification control
- Manual dehumidification control
- Dehumidifier compressor protection
- Large, digital backlit display
- Simple, intuitive programming
- RH% and outdoor temperature calibration
- Adjustable high and low range stops (10-90%)
- Automatically detects presence of outdoor sensor to set control to Automatic or Manual Mode

Product Specifications

Dimensions (in.)	3 7/16 in. high x 4 1/2 in. wide x 1 5/16 in. deep
Dimensions (mm)	86 mm x 114 mm x 33 mm
Temperature Range (F)	-20 F to +120 F
Includes	HumidiPRO Control, Outdoor Sensor, Mounting Hardware
Used With	Whole Home Humidifiers or Dehumidifiers
Item Type	Product
Mounting	Return Duct (Recommended) or Wall Mount
Frequency	50 Hz; 60 Hz
Operating Humidity Range (% RH)	Manual Mode: 10% to 90% RH% (Adjustable) Auto Mode: 10% to 60% RH% (35% Default)
Voltage	24 Vac
Type	Humidistat/Dehumidistat
Color	Premier White®
Differential	4% to 6% RH