

Aluminum Levels

Patent Pending

MAGNET TRACK

ULTRA
POWERFUL
Rare-Earth Magnets



Top V-Groove
fits contour of pipe

Tapered nose easily slides into pockets and fits in tighter spaces

High-visibility orange levels won't get lost on conduit

Large, high visibility vials are easy to read

Billet Aluminum Torpedo Levels

Includes core aluminum levels features plus:

- Professional grade billet aluminum body is precision machined for high-accuracy leveling
- Cat. No. 935RBLT features large, easy to read bright LED high-definition vials for any lighting condition, a 3-minute auto-shut-off to save batter life, and is water and impact resistant



Super Bright High-Definition LED Vials (Cat No. 935RBLT)



935RBLT



935RB

Cat. No.	Number of Vials	Type of Vials	Overall Length	Weight
935RBLT	4	0°, 90°, 45°, 30°	9" (228.6 mm)	0.70 lb (0.32 kg)
935RB	4	0°, 90°, 45°, 30°	8" (203.2 mm)	0.46 lb (0.21 kg)

Accu-Bend™ Levels

Includes core aluminum levels features plus:

- Professional grade billet aluminum body is precision machines for high-accuracy leveling
- Thumb screw attaches level to conduit to measure angle while bending
- Cat. No. 935AB1V is non-magnetic



935AB4V




935AB1V

Cat. No.	Number of Vials	Type of Vials	Overall Length	Weight
935AB4V	4	0°, 90°, 45°, 30°	6-1/4" (158.8 mm)	0.37 lb (0.17 kg)
935AB1V	1	0°	2-1/2" (63.5 mm)	0.15 lb (0.07 kg)

⚠ WARNING: Brass bolt contains lead, a chemical known to the State of California to cause cancer, and birth defects or other reproductive harm. Wash hands after handling.





Levels

Aluminum Torpedo Levels

- Aluminum frame with orange body for added visibility and durability
- Locking track prevents powerful rare-earth magnets from falling out
- Top V-groove fits contour of pipe
- Large high-visibility vials are easy to read
- Cat. No. 931-9RETT has tether ring for working at height



935R



9319RETT
SPLIT TETHER RING

Cat. No.	Number of Vials	Type of Vials	Overall Length	Weight
935R	3	0°, 90°, 45°	9" (228.6 mm)	0.53 lb (0.24 kg)
9319RETT	3	0°, 90°, 45°	9" (228.6 mm)	0.10 lb (0.05 kg)

Torpedo Level

- Strip magnet bottom holds securely to conduit and metal surfaces
- High-visibility orange level won't get lost on conduit
- Large high-visibility vials are easy to read
- Top V-groove fits contour of pipe



935

Cat. No.	Number of Vials	Type of Vials	Overall Length	Weight
935	3	0°, 90°, 45°	9" (228.6 mm)	0.27 lb (0.12 kg)

Cross-Line Laser Levels

Self-leveling,
easy-to-read
**horizontal
& vertical**
laser lines

IP54: water and dust resistant

Integrated magnetic 360° mounting bracket with 1/4" and 5/8" tripod mounting threads



Projects horizontal and vertical lines independently or together for various alignments

Plumb spot lasers to pinpoint overhead locations (model 93LCLS only)

Laser Line Levels

NEW!

Includes core laser level features plus:

- Additional mounting clamp attachment for use on ceiling grid applications
- Molded hard carrying case included



CAUTION
LASER RADIATION:
DO NOT STARE INTO BEAM
Max. Output <1mW
Wavelength: 630-670nm
CLASS 2 LASER PRODUCT

Cat. No.	Plumb Laser	Accuracy	Overall Length	Overall Height	Overall Width	Weight
93LCL NEW!	No	±3/32" per 33 ft (±2 mm per 10 m)	2-5/8" (66.7 mm)	5" (127.0 mm)	5-1/4" (133.4 mm)	1.6 lb (0.7 kg) without Batteries
93LCLS NEW!	Yes	±3/32" per 33 ft (±2 mm per 10 m)	2-5/8" (66.7 mm)	5" (127.0 mm)	5-1/4" (133. mm)	1.6 lb (0.7 kg) without Batteries

See page 295 for additional information on warnings.



Tape Measures

Patent Pending
UNCLUTTERED,
EASY-TO-READ
**BOLD LINES
EVERY 1/8"**

**EXTRA-LARGE
BOLD NUMBERS
FOR IMPROVED
READABILITY**



Up to
9-1/2 ft. (3 m)
STAND-OUT

▲WARNING:

- Protect hands when cleaning magnetic tip end. Use gloves or cloth.
- Avoid magnetic contact with sensitive electronic or computer equipment.
- To avoid personal injury and damage to this tool, do not allow the tape blade to retract into case.
- Do NOT open case. Spring motor is under tension, and opening case may cause injury.

Magnetic end hooks with dual angle polarity
attaches to conduit and steel studs to easily
read from above or below



Retraction Speed Brake
controls blade speed and
protects fingers from having
to touch blade



Blade-printed conduit multiplier bending table
helps calculate offsets and saddles



Tape Measures - Magnetic

Includes core tape measure features plus:

- Heavy duty nylon coating protects blade printing
- Super-sized back clip holds securely to wide belts and extends into pockets
- Cat. Nos. 86315 and 86375 feature double sided printing with centimeters and inches
- U.S. Patent Pending

Cat. No.	Tape Length	Hook	Overall Length	Overall Width	Weight
86216	16 ft (4.9 m)	Double	3-1/4" (82.6 mm)	2" (50.8 mm)	0.81 lb (0.37 kg)
86225	25 ft (7.6 m)	Double	6-1/2" (165.1 mm)	4-1/4" (108.0 mm)	1.1 lb (0.5 kg)
86230	30 ft (9.1 m)	Double	3-3/4" (95.3 mm)	2" (50.8 mm)	1.3 lb (0.6 kg)
Metric					
86315	5 m	Double	3-1/4" (82.6 mm)	2" (50.8 mm)	0.81 lb (0.37 kg)
86375	7.5 m	Double	3-1/2" (88.9 mm)	2" (50.8 mm)	1.1 lb (0.5 kg)



86225

Tape Measure - Non-Magnetic

Includes core tape measure features plus:

- Heavy duty nylon coating protects blade printing
- Super-sized back clip holds securely to wide belts and extends into pockets
- U.S. Patent Pending

Cat. No.	Tape Length	Hook	Overall Length	Overall Width	Weight
86125	25 ft (7.6 m)	Single	3-1/2" (88.9 mm)	2" (50.8 mm)	1.1 lb (0.5 kg)



86125



Tape Measures

Tape Measures-Steel with High-Visibility Case

- High-visibility, high-impact orange case makes it easy to find in a tool box, pouch and on the jobsite
- 16" stud markings and 19.2" truss markings

Cat. No.	Tape Length	Hook	Overall Length	Overall Width	Weight
928-25HV	25 ft (7.6 m)	Single	3-1/2" (88.9 mm)	1" (25.4 mm)	1.0 lb (0.5 kg)



928-25HV

Tape Measure Holders

- Klein offers a complete selection of leather or nylon Tape Holders and Pouches



5707



5195



5196



5712



5195TT

Tape Measure	Holder Cat. No.	Description	Overall Size	Weight
86216, 86315	5195	Medium Leather Pouch	4-1/2" x 7" (114 mm x 178 mm)	2.9 oz. (82 g)
	5707	Nylon Tape Measure Clip/Holder	4-1/8" x 3-3/4" (104 mm x 95 mm)	1.6 oz. (45 g)
86215, 86225, 86375	5196	Large Leather Pouch	5" x 7" (127 mm x 178 mm)	3.4 oz. (95 g)
	5707	Nylon Tape Measure Clip/Holder	4-1/8" x 3-3/4" (104 mm x 95 mm)	1.6 oz. (45 g)
	5195TT	Tape Measure Holder with Ring	3" x 3-1/2" (76 mm x 89 mm)	1.6 oz. (45 g)
	5712	Tape Measure Holder with Ring	3" x 3-1/2" (76 mm x 89 mm)	3.8 oz. (109 g)
86230	5196	Large Leather Pouch	5" x 7" (127 mm x 178 mm)	3.4 oz. (95 g)
	5707	Nylon Tape Measure Clip/Holder	4-1/8" x 3-3/4" (104 mm x 95 mm)	1.6 oz. (45 g)
	5712	Tape Measure Holder with Ring	3" x 3-1/2" (76 mm x 89 mm)	3.8 oz. (109 g)

Laser Measuring

Laser Distance Measurer

- Meter provides measurements up to 65 ft. (19.8 m) in distance, at an accuracy of + or - 1/16" (1.6 mm)
- Quickly calculates length, area, volume, and indirect measurements with large, easy-to-read buttons
- Offers the option of one-touch, single-distance measurement and continuous measurement
- Depth gauge stick flips out to measure from inside corners or channels
- Highly visible backlit display
- Provides both fractional (imperial) and metric readings
- Memory stores last 20 measurements
- Includes handy carrying pouch to keep until safe when not in use

Cat. No.	Batteries	Overall Length	Overall Height	Overall Width	Weight
93LDM65	2 x AAA	1-3/8" (34.9 mm)	4-1/2" (114.3 mm)	2" (50.8 mm)	0.32 lb (0.15 kg)



93LDM65



Folding Rulers

Wood Folding Rules

- Strong, 6' (183 cm) long hardwood rules with clear abrasion-resistant coating
- Black markings on yellow, with red stud center markings every 16 inches
- Measurements are marked on both sides and both edges, graduated to 1/16th inch
- Riveted lock joints are designed for long wear and maintained accuracy
- Extension slide moves under friction in a T-slot with stops at each end. (Cat. No. 905-6)

Cat. No.	Reading	Overall Length	Weight
900-6	Inside	6 ft (1.8 m)	0.33 lb (0.15 kg)
901-6	Outside	6 ft (1.8 m)	0.33 lb (0.15 kg)
905-6	Outside	6 ft (1.8 m)	0.33 lb (0.15 kg)



901-6

Non-Conductive Fiberglass Folding Rules

- Constructed of tough nylon, reinforced with glass fibers for added durability, and resistance to weather, abrasion and most chemicals
- Positive locking joints and stainless steel spring hinges for added strength
- Measurements are marked on both sides and both edges, graduated to 1/16th inch
- Black markings on yellow, with red stud center markings every 16 inches
- Engraved graduations on both sides

Cat. No.	Reading	Overall Length	Weight
910-6	Inside	6 ft (1.8 m)	0.33 lb (0.15 kg)
911-6	Outside	6 ft (1.8 m)	0.33 lb (0.15 kg)



910-6

Fiberglass Tapes

Woven Fiberglass Tapes

- Woven fiberglass tape with moisture-proof coating of polyvinyl chloride assures durability and protects against oil or chemicals
- Can be immersed in water without adverse effects
- All metal parts are nickel-plated for protection against rust
- End-hooks are permanently attached to a reinforced strip
- Case and reel are ruggedly built, yet lightweight and comfortable to use
- Tape line is graduated in feet and inches to 8ths
- Black graduating numbers and red foot markings on yellow background
- Protective carrying case on Cat. Nos. 946-50 and 946-100 encloses tape completely
- Tape rings tuck neatly into case opening for storage
- Cat. No. 946-150 is contained in an open reel and is easy to handle and rewind



946-100

946-150

Cat. No.	Tape Length	Hook	Overall Length	Overall Width	Weight
946-50	50 ft (15.2 m)	Single	7-3/4" (196.9 mm)	1" (25.4 mm)	0.80 lb (0.36 kg)
946-100	100 ft (30 m)	Single	9" (228.6 mm)	1" (25.4 mm)	1.2 lb (0.5 kg)
946-150	150 ft (45.7 m)	Single	13" (330.2 mm)	2" (50.8 mm)	1.7 lb (0.8 kg)