



1/2-6 HP

Air-cooled Condensing Units

Technical Guide
Models LZ | LH | LS



Table of Contents

Nomenclature.....	2
Features & Benefits	3
Options	4
Hermetic Compressor Models.....	5-10
Performance Data.....	5-8
High Temperature (R-404A/507).....	5
Extended Temperature (R-404A/507).....	6
Low Temperature (R-404A/507)	7
Extended Temperature (R-407C).....	8
Unit Specifications.....	9
Electrical Data	10
Scroll Compressor Models	11-18
Performance Data.....	11-16
Medium Temperature (R-404A/507)	11
Medium Temperature (R-407A)	12
Medium Temperature (R-407C)	13
Low Temperature (R-404A/507)	14
Low Temperature (R-407A)	15
Low Temperature (R-407C)	16
Unit Specifications.....	17
Electrical Data	18
Semi-Hermetic Compressor Models.....	19-22
Performance Data	19-20
Medium Temperature (R-404A/507)	19
Low Temperature (R-404A/507)	20
Unit Specifications.....	21
Electrical Data	22
Replacement Parts by InterLink	23
Dimensional Drawings	24-25



Nomenclature

L	H	T	030	L	6	C	F
Model	Compressor	Application	Equiv. HP	Temperature	Refrigerant*	Voltage	Identifier
L = Larkin	H = Hermetic	T = Outdoor	005 = 1/2 HP	H - High Temp.	6 - R-404A, R-507	B = 208-230/1/60	F = Stock
S = Semi-Herm	N = Indoor		008, 009 = 3/4 HP	M - Med. Temp.		C = 208-230/3/60	
Z = Scroll	S = Beacon II		010, 011 = 1 HP	L - Low Temp.		D = 460/3/60	
			01* = 1 1/2 HP	E - Extra Low Temp.		G = 230/1/60	
			02* = 2 HP	X = Extended Temp.		K = 230/3/60	
			03* = 3 HP				
			04* = 4 HP				
			05* = 5 HP				
			060 = 6 HP				

* = Compressors also compatible with R-407A and R-407C

Features & Benefits

Cabinet & Construction

- Microchannel coil technology standard on most units
- Painted steel cabinets for superior strength and corrosion protection
- Heavy duty steel raised base with 1-1/2" legs
- Fan guards and wiring conduit on indoor models



Typical Outdoor Hermetic Unit

Serviceability

- Suction service valves for hermetic and scroll compressors located outside the cabinet for quick installations. Semi-hermetic compressor models have a suction valve on the compressor and an access fitting on the suction line entering the cabinet.
- Receiver with fusible plug, liquid shutoff valve and charging port is standard
- Large electrical panel for ease of access
- Prefabricated wiring harnesses for tight crimp connections and consistent labeling
- Unit stays on if the hood is removed for servicing
- Sight glass is easily viewable



Typical Outdoor Unit with throwaway liquid-line filter and sight glass

Quality

- All units are completely leak tested in a helium environment, bump tested and allowed to cycle off on the high and low pressure control. Each unit has a copy of the run data shipped inside the electrical panel
- Electrical circuits are completely checked for continuity
- Piping is laid out to minimize stress and vibration and is pre-bent to eliminate leaks
- Encapsulated, auto-reset, high and low pressure controls to eliminate leaks (standard on all high and medium temperature models, adjustable low pressure control standard on low temperature models)



Typical Outdoor Hermetic Unit with liquid filter drier and sight glass

Components

Fan

- Specifically matched with motor and coil to attain maximum air movement and cooling

Motor

- Rated for 50 and 60 cycle application
- Standard PSC or optional Variable Speed EC (VSEC) motors with Orbus Controller

Compressor

- Wide variety of compressors including: hermetic, semi-hermetic and scroll. R-404A/507 available for both medium and low temperature applications (R-407A/407C available on select Scroll & Hermetic Models)
- Spring-mounted compressors with vibration eliminators on all 1-1/2 to 6 HP semi-hermetic compressors; 1/2 to 1 HP semi-hermetic compressors are rigid mounted and have a discharge loop
- Discharge service valves come standard on all units including hermetics

1/2 - 6 HP Condensing Unit: Options

Electrical Options

Option	Outdoor	Indoor	Stock
Adjustable low pressure control for medium temp. comp.	Option	Option	N/A
Air or electric defrost timer only	Option	Option	1/2-3 HP low temp.
Beacon II™	Option	N/A	N/A
Crankcase heater	Standard	N/A	Standard
Dual pressure control (not available on Beacon II™)	Option	Option	N/A
Electric defrost with timer & contactors (040-060 models only)	Option	Option	4-6 HP low temp.
Fixed fan cycling — pressure or temperature (2 fan units) (Pressure standard on Beacon II™)	Option	Option	N/A
Fused disconnect / Non-fused disconnect	Option	Shipped loose	N/A
Phase loss / low voltage monitor	Option	Option	N/A
Smart Defrost Kit™ (Factory-Installed)	Option	Option	N/A
Variable speed EC (VSEC) motors with Orbus controller	Option	N/A	N/A

Mechanical Options

Option	Outdoor	Indoor	Stock
12" Extended legs for snowbelt operation	Shipped loose	Shipped loose	Shipped loose
Head pressure control flooding valve	Standard	Option	Standard
Liquid line drier, sight glass	Option	Option	Standard
Liquid line solenoid valve and pumpdown switch	Option	Option	N/A
Low ambient kit with heated and insulated receiver, TD relay	Option	N/A	N/A
Oil separator with discharge line check valve (D cabinet)	Option	Option	N/A
Oversize receiver (D cabinet)	Option	Option	N/A
Precharged refrigerant with quick connect fittings	Option	Option	N/A
Replaceable core liquid line filter (D cabinet)	Option	Option	N/A
Replaceable core suction line filter (D cabinet)	Option	Option	N/A
Suction accumulator	Option	Option	N/A
Suction line filter	Option	Option	N/A



The Beacon II™ Refrigeration System is a preassembled, factory installed refrigeration system featuring an integrated microcomputer based electronic control board.

The Beacon II™ Refrigeration System replaces the expansion valve, solenoid valve, room thermostat, defrost control and timer. It comes factory preset, thereby eliminating all of the expensive and time consuming fine tuning and adjustments necessary for a good system installation. For additional information, contact your Sales Representative.

PERFORMANCE DATA: HERMETIC COMPRESSOR MODELS

High Temperature R-404A/507

Model	Compressor	Capacity BTUH @ 90°F Ambient by SST	
		40°F	35°F
LH*005H6†	RST45C1E	8,910	8,150
LH*009H6†	RST64C1E	12,520	11,570
LH*010H6†	RST70C1E	13,720	12,610
LH*015H6	CS10K6E	21,400	19,460
LH*025H6	CS14K6E	26,320	24,270
LH*032H6	CS20K6E	42,890	39,110
LH*040H6	CS27K6E	52,240	48,170
LH*050H6	CS33K6E	57,030	52,650

Model	Compressor	Capacity BTUH @ 95°F Ambient by SST	
		40°F	35°F
LH*005H6†	RST45C1E	8,510	7,790
LH*009H6†	RST64C1E	11,980	11,080
LH*010H6†	RST70C1E	13,010	11,960
LH*015H6	CS10K6E	20,260	18,400
LH*025H6	CS14K6E	25,000	23,030
LH*032H6	CS20K6E	40,730	37,110
LH*040H6	CS27K6E	49,580	45,670
LH*050H6	CS33K6E	54,240	50,060

Model	Compressor	Capacity BTUH @ 100°F Ambient by SST	
		40°F	35°F
LH*005H6†	RST45C1E	8,120	7,430
LH*009H6†	RST64C1E	11,440	10,580
LH*010H6†	RST70C1E	12,310	11,320
LH*015H6	CS10K6E	19,120	17,350
LH*025H6	CS14K6E	23,690	21,810
LH*032H6	CS20K6E	38,560	35,100
LH*040H6	CS27K6E	46,920	43,180
LH*050H6	CS33K6E	51,440	47,460

Model	Compressor	Capacity BTUH @ 110°F Ambient by SST	
		40°F	35°F
LH*005H6†	RST45C1E	7,340	6,710
LH*009H6†	RST64C1E	10,350	9,580
LH*010H6†	RST70C1E	10,920	10,040
LH*015H6	CS10K6E	16,880	15,280
LH*025H6	CS14K6E	21,100	19,410
LH*032H6	CS20K6E	34,210	31,070
LH*040H6	CS27K6E	41,630	38,220
LH*050H6	CS33K6E	45,860	42,260

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II

†= RST compressor not suitable for R-507

PERFORMANCE DATA: HERMETIC COMPRESSOR MODELS

Extended Temperature R-404A/R-507

Model	Compressor	Capacity BTUH @ 90°F Ambient by SST						
		30°F	25°F	20°F	0°F	-10°F	-20°F	-25°F
LH*005X6†	RST45C1E	6,850	6,270	5,710	3,690	2,810	1,980	1,550
LH*008X6†	RST55C1E	8,130	7,450	6,790	4,430	3,490	2,710	2,400
LH*009X6†	RST64C1E	9,590	8,820	8,080	5,350	4,240	3,270	2,850
LH*010X6†	RST70C1E	10,060	9,300	8,660	5,540	4,080	2,750	2,050
LH*015X6	CS10K6E	16,430	15,090	13,550	7,910	5,280	3,610	2,970
LH*020X6	CS12K6E	18,590	17,000	15,420	9,110	6,330	4,030	3,270
LH*025X6	CS14K6E	20,150	18,630	17,270	10,900	8,050	5,740	4,760
LH*030X6	CS18K6E	29,490	27,030	24,550	14,390	10,600	7,380	6,180
LH*032X6	CS20K6E	32,420	29,620	26,840	15,930	12,200	8,780	7,000
LH*040X6	CS27K6E	43,970	39,510	35,150	20,560	14,980	11,830	8,690
LH*050X6	CS33K6E	44,600	43,160	39,300	24,160	17,610	13,500	11,700
Model	Compressor	Capacity BTUH @ 95°F Ambient by SST						
		30°F	25°F	20°F	0°F	-10°F	-20°F	-25°F
LH*005X6†	RST45C1E	6,530	5,970	5,440	3510	2,660	1,850	1,430
LH*008X6†	RST55C1E	7,730	7,070	6,440	4,180	3,280	2,550	2,250
LH*009X6†	RST64C1E	9,150	8,420	7,710	5,090	4,020	3,100	2,690
LH*010X6†	RST70C1E	9,400	8,850	8,170	5,120	3,770	2,610	1,820
LH*015X6	CS10K6E	15,400	13,960	12,800	7,220	5,060	3,330	2,630
LH*020X6	CS12K6E	17,490	16,000	14,470	8,370	5,830	3,860	2,830
LH*025X6	CS14K6E	18,920	17,490	16,250	10,090	7,530	5,230	4,330
LH*030X6	CS18K6E	27,840	25,490	23,130	13,480	9,710	6,750	5,620
LH*032X6	CS20K6E	30,530	27,890	25,240	14,800	11,200	7,930	6,220
LH*040X6	CS27K6E	41,480	37,270	33,160	19,400	14,130	11,160	8,200
LH*050X6	CS33K6E	42,300	41,000	37,180	22,370	17,300	12,700	10,900
Model	Compressor	Capacity BTUH @ 100°F Ambient by SST						
		30°F	25°F	20°F	0°F	-10°F	-20°F	-25°F
LH*005X6†	RST45C1E	6,200	5,670	5,170	3,330	2,510	1,720	1,310
LH*008X6†	RST55C1E	7,320	6,700	6,090	3,930	3,070	2,390	2,100
LH*009X6†	RST64C1E	8,720	8,010	7,340	4,830	3,810	2,920	2,540
LH*010X6†	RST70C1E	8,790	8,290	7,680	4,760	3,430	2,230	1,570
LH*015X6	CS10K6E	14,210	13,150	11,780	6,660	4,580	2,930	2,270
LH*020X6	CS12K6E	16,410	14,990	13,380	7,700	5,280	3,420	2,420
LH*025X6	CS14K6E	17,730	16,390	15,220	9,390	6,950	4,770	3,930
LH*030X6	CS18K6E	26,190	23,970	21,800	12,570	8,880	6,120	5,110
LH*032X6	CS20K6E	28,600	26,160	23,750	13,740	10,300	7,050	5,370
LH*040X6	CS27K6E	38,980	35,030	31,180	18,240	13,290	10,500	7,700
LH*050X6	CS33K6E	39,800	38,760	34,810	20,760	16,200	11,800	10,000
Model	Compressor	Capacity BTUH @ 110°F Ambient by SST						
		30°F	25°F	20°F	0°F	-10°F	-20°F	-25°F
LH*005X6†	RST45C1E	5,540	5,060	4,610	2,950	2,210	1,470	1,080
LH*008X6†	RST55C1E	6,530	5,970	5,410	3,450	2,670	2,070	1,820
LH*009X6†	RST64C1E	7,830	7,200	6,580	4,310	3,390	2,580	2,250
LH*010X6†	RST70C1E	7,700	7,140	6,590	4,080	3,010	1,680	—
LH*015X6	CS10K6E	12,150	11,110	10,030	5,410	3,650	2,140	1,540
LH*020X6	CS12K6E	14,270	12,980	11,550	6,460	4,410	2,580	1,660
LH*025X6	CS14K6E	15,430	14,450	13,230	8,100	5,760	3,860	2,990
LH*030X6	CS18K6E	23,000	21,020	18,970	10,810	7,100	4,940	4,140
LH*032X6	CS20K6E	24,840	22,790	20,580	11,490	8,260	5,270	3,630
LH*040X6	CS27K6E	35,150	31,240	27,520	15,210	11,290	8,920	6,550
LH*050X6	CS33K6E	35,200	34,060	30,530	19,000	14,100	10,400	9,010

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II

†= RST compressor not suitable for R-507

PERFORMANCE DATA: HERMETIC COMPRESSOR MODELS

Low Temperature R-404A/R-507

Model	Compressor	Capacity BTUH @ 90°F Ambient by SST					
		0°F	-5°F	-10°F	-20°F	-25°F	-30°F
LH*011L6	CF04K6E	7,030	6,240	5,370	3,850	3,330	2,630
LH*014L6	CF06K6E	10,500	9,380	7,830	6,090	4,890	4,080
LH*019L6	CF06K6E	12,100	10,180	8,910	6,580	5,530	4,570
LH*025L6	CF09K6E	15,550	14,500	12,700	9,000	7,560	6,230
LH*031L6	CF12K6E	18,840	17,800	15,140	11,540	9,790	8,070

Model	Compressor	Capacity BTUH @ 95°F Ambient by SST					
		0°F	-5°F	-10°F	-20°F	-25°F	-30°F
LH*011L6	CF04K6E	6,840	5,750	4,920	3,650	3,020	2,360
LH*014L6	CF06K6E	9,900	8,840	7,750	5,670	4,710	3,680
LH*019L6	CF06K6E	11,400	10,100	8,750	6,040	5,030	4,150
LH*025L6	CF09K6E	15,400	13,700	12,000	8,300	6,950	5,750
LH*031L6	CF12K6E	17,690	16,800	14,360	10,910	9,170	7,470

Model	Compressor	Capacity BTUH @ 100°F Ambient by SST					
		0°F	-5°F	-10°F	-20°F	-25°F	-30°F
LH*011L6	CF04K6E	6,310	5,170	4,460	3,300	2,660	2,070
LH*014L6	CF06K6E	9,310	8,280	7,280	5,280	4,350	3,510
LH*019L6	CF06K6E	10,700	9,430	8,170	5,810	4,570	3,700
LH*025L6	CF09K6E	14,500	12,800	11,200	8,130	6,410	5,220
LH*031L6	CF12K6E	17,600	15,090	13,410	10,700	9,040	7,320

Model	Compressor	Capacity BTUH @ 110°F Ambient by SST					
		0°F	-5°F	-10°F	-20°F	-25°F	-30°F
LH*011L6	CF04K6E	5,240	4,450	3,620	2,630	2,100	—
LH*014L6	CF06K6E	8,310	7,340	6,420	4,580	3,730	2,990
LH*019L6	CF06K6E	9,330	8,170	7,040	4,920	3,980	3,090
LH*025L6	CF09K6E	12,700	11,400	9,900	7,030	5,760	4,590
LH*031L6	CF12K6E	15,700	14,000	12,400	9,250	7,690	6,100

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II™

PERFORMANCE DATA: HERMETIC COMPRESSOR MODELS

Extended Temperature Models R-407C

Model	Compressor	Capacity BTUH @ 90°F Ambient by SST					
		40°F	30°F	25°F	20°F	10°F	0°F
LH*005X6	RST45C1E	7,310	5,970	7,310	4,760	3,730	2,880
LH*008X6	RST55C1E	8,420	6,960	6,260	5,610	4,440	3,420
LH*009X6	RST64C1E	10,310	8,560	7,760	7,000	5,590	4,330
LH*010X6	RST70C1E	10,450	8,710	7,920	7,160	5,770	4,470

Model	Compressor	Capacity BTUH @ 95°F Ambient by SST					
		40°F	30°F	25°F	20°F	10°F	0°F
LH*005X6	RST45C1E	7,050	5,730	5,140	4,570	3,570	2,750
LH*008X6	RST55C1E	8,090	6,680	6,010	5,400	4,260	3,280
LH*009X6	RST64C1E	9,890	8,210	7,440	6,710	5,370	—
LH*010X6	RST70C1E	10,040	8,360	7,600	6,880	5,530	—

Model	Compressor	Capacity BTUH @ 100°F Ambient by SST					
		40°F	30°F	25°F	20°F	10°F	0°F
LH*005X6	RST45C1E	6,770	5,520	4,930	4,380	3,420	—
LH*008X6	RST55C1E	7,750	6,400	5,750	5,160	4,090	—
LH*009X6	RST64C1E	9,460	7,850	7,120	6,420	5,140	—
LH*010X6	RST70C1E	9,620	8,010	7,290	6,590	5,300	—

Model	Compressor	Capacity BTUH @ 110°F Ambient by SST					
		40°F	30°F	25°F	20°F	10°F	0°F
LH*005X6	RST45C1E	6,220	5,050	4,510	4,010	3,110	—
LH*008X6	RST55C1E	7,080	5,840	5,260	4,710	3,730	—
LH*009X6	RST64C1E	—	7,140	6,480	5,850	4,670	—
LH*010X6	RST70C1E	—	7,300	6,640	6,030	—	—

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II™

UNIT SPECIFICATIONS: HERMETIC COMPRESSOR MODELS

Model	Fig. ++	Compressor	Connections (ID)		Receiver 90% Full Lbs.	Fan(s)	Dimensions			Net. Wt. Lbs.	Sound Data dBA [†]
			Liquid	Suction			D (In.)	W (In.)	H (In.)		
LH*005X6	A	RST45C1E	3/8	1/2	5.5	1	28-1/4	23-3/4	17-1/2	135	68
LH*008X6	A	RST55C1E	3/8	1/2	5.5	1	28-1/4	23-3/4	17-1/2	135	68
LH*009X6	A	RST64C1E	3/8	1/2	5.5	1	28-1/4	23-3/4	17-1/2	144	68
LH*010X6	A	RST70C1E	3/8	5/8	5.5	1	28-1/4	23-3/4	17-1/4	138	68
LH*015X6	B	CS10K6E	3/8	5/8	9.0	2	28-1/4	37-3/4	17-1/4	193	71
LH*020X6	B	CS12K6E	3/8	7/8	9.0	2	28-1/4	37-3/4	17-1/4	203	73
LH*025X6	B	CS14K6E	3/8	7/8	9.0	2	28-1/4	37-3/4	17-1/4	208	74
LH*030X6	D	CS18K6E	1/2	7/8	20.0	1	30-1/4	42-1/2	29-3/4	290	73
LH*032X6	D	CS20K6E	1/2	7/8	20.0	1	30-1/4	42-1/2	29-3/4	275	76
LH*040X6	D	CS27K6E	1/2	1-1/8	20.0	1	30-1/4	42-1/2	29-3/4	281	73
LH*050X6	D	CS33K6E	1/2	1-1/8	20.0	1	30-1/4	42-1/2	29-3/4	313	73
LH*011L6	A	CF04K6E	3/8	5/8	5.5	1	28-1/4	23-3/4	17-1/4	139	73
LH*014L6	A	CF06K6E	3/8	5/8	5.5	1	28-1/4	23-3/4	17-1/4	170	73
LH*019L6	B	CF06K6E	3/8	5/8	9.0	2	28-1/4	37-3/4	17-1/4	200	69
LH*025L6	B	CF09K6E	3/8	7/8	9.0	2	28-1/4	37-3/4	17-1/4	222	76
LH*031L6	C	CF12K6E	1/2	7/8	14.0	2	28-1/4	37-3/4	19-3/4	223	77
LH*005H6	A	RST45C1E	3/8	1/2	5.5	1	28-1/4	23-3/4	17-1/4	135	68
LH*009H6	A	RST64C1E	3/8	5/8	5.5	1	28-1/4	23-3/4	17-1/4	144	68
LH*010H6	A	RST70C1E	3/8	5/8	5.5	1	28-1/4	23-3/4	17-1/4	138	68
LH*015H6	B	CS10K6E	3/8	5/8	9.0	2	28-1/4	37-3/4	17-1/4	193	71
LH*025H6	B	CS14K6E	3/8	7/8	9.0	2	28-1/4	37-3/4	17-1/4	208	74
LH*032H6	D	CS20K6E	1/2	7/8	20.0	1	30-1/4	42-1/2	29-3/4	275	76
LH*040H6	D	CS27K6E	1/2	1-1/8	20.0	1	30-1/4	42-1/2	29-3/4	281	73
LH*050H6	D	CS33K6E	1/2	1-1/8	20.0	1	30-1/4	42-1/2	29-3/4	313	73

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II™

++ = See Dimensional Drawings for details

† = Estimated sound pressure values are 10 feet from the unit. For estimating sound pressure from the unit at different distances, deduct the following from the unit values: 20 feet, deduct 6 dBA; for 40 feet, deduct 12 dBA; for 80 feet, deduct 18 dBA. This data is typical of "free field" conditions for horizontal air cooled condensing units at the outlet of the discharge air. The actual sound measurements may vary depending on the condensing unit installation. Factors such as reflecting walls, background noise and mounting conditions may have a significant influence on this data.

PERFORMANCE DATA: SCROLL COMPRESSOR MODELS

Medium Temperature Models R-404A/507

Model	Compressor	Capacity BTUH @ 90°F Ambient by SST								
		40°F	30°F	25°F	20°F	10°F	0°F	-10°F	-20°F	-25°F
LZ*010M6	ZS09KAE	17,730	14,770	13,420	12,160	9,920	8,040	6,460	5,130	4,540
LZ*015M6	ZS13KAE	22,840	19,190	17,490	15,880	16,060	10,640	8,610	6,880	6,110
LZ*020M6	ZS15KAE	26,550	22,440	20,560	18,730	15,470	12,660	10,280	8,250	7,340
LZ*025M6	ZS19KAE	28,990	24,460	22,410	20,520	16,980	13,970	11,380	9,160	8,140
LZ*030M6	ZS21KAE	42,030	35,340	32,260	29,300	24,050	19,540	15,750	12,570	11,160
LZ*035M6	ZS26KAE	45,290	38,280	34,960	31,830	26,200	21,350	17,230	13,770	12,250
LZ*045M6	ZS29KAE	49,890	42,320	38,830	35,420	29,280	23,920	19,370	15,520	13,810
LZ*050M6	ZS33KAE	53,930	45,740	41,980	38,450	31,790	26,110	21,210	17,030	15,180
LZ*055M6	ZS38K4E	57,230	50,410	46,970	43,530	36,770	30,380	24,200	18,140	15,190
LZ*060M6	ZS45K4E	65,560	58,120	54,430	50,680	43,160	35,890	28,800	21,690	18,180
Model	Compressor	Capacity BTUH @ 95°F Ambient by SST								
		40°F	30°F	25°F	20°F	10°F	0°F	-10°F	-20°F	-25°F
LZ*010M6	ZS09KAE	17,060	14,220	12,930	11,720	9,570	7,760	6,250	4,980	4,410
LZ*015M6	ZS13KAE	21,950	18,450	16,780	15,300	12,570	10,250	8,310	6,660	5,920
LZ*020M6	ZS15KAE	25,490	21,550	19,750	18,000	14,870	12,180	9,920	7,990	7,120
LZ*025M6	ZS19KAE	27,810	23,460	21,500	19,690	16,310	13,430	10,960	8,850	7,880
LZ*030M6	ZS21KAE	40,480	33,960	30,990	28,170	23,140	18,830	15,210	12,160	10,820
LZ*035M6	ZS26KAE	43,480	36,760	33,580	30,610	25,210	20,560	16,630	13,330	11,870
LZ*045M6	ZS29KAE	47,860	40,620	37,280	34,020	28,160	23,020	18,680	15,010	13,380
LZ*050M6	ZS33KAE	51,700	43,860	40,260	36,900	30,550	25,110	20,440	16,460	14,700
LZ*055M6	ZS38K4E	54,940	48,470	45,160	41,860	35,360	29,210	23,240	17,370	14,500
LZ*060M6	ZS45K4E	62,910	55,880	52,340	48,730	41,500	34,510	27,650	20,750	17,320
Model	Compressor	Capacity BTUH @ 100°F Ambient by SST								
		40°F	30°F	25°F	20°F	10°F	0°F	-10°F	-20°F	-25°F
LZ*010M6	ZS09KAE	16,430	13,670	13,420	11,260	9,200	7,470	6,030	4,820	4,280
LZ*015M6	ZS13KAE	21,050	17,690	16,110	14,690	12,070	9,850	8,000	6,430	5,730
LZ*020M6	ZS15KAE	24,420	20,640	18,920	17,250	14,260	11,690	9,530	7,700	6,880
LZ*025M6	ZS19KAE	26,620	22,440	20,570	18,850	15,610	12,860	10,520	8,520	7,610
LZ*030M6	ZS21KAE	38,780	32,510	29,740	27,020	22,210	18,100	14,640	11,750	10,470
LZ*035M6	ZS26KAE	41,640	35,210	32,120	29,360	24,180	19,750	16,010	12,860	11,480
LZ*045M6	ZS29KAE	45,800	38,880	35,690	32,580	27,010	22,100	17,970	14,470	12,930
LZ*050M6	ZS33KAE	49,440	41,940	38,510	35,300	29,270	24,080	19,640	15,870	14,190
LZ*055M6	ZS38K4E	52,630	46,530	43,350	40,190	33,950	28,040	22,280	16,580	13,780
LZ*060M6	ZS45K4E	60,260	53,640	50,250	46,780	39,840	33,130	26,500	19,800	16,470
Model	Compressor	Capacity BTUH @ 110°F Ambient by SST								
		40°F	30°F	25°F	20°F	10°F	0°F	-10°F	-20°F	-25°F
LZ*010M6	ZS09KAE	15,010	12,510	11,370	10,330	8,450	6,870	5,560	4,470	3,990
LZ*015M6	ZS13KAE	19,200	16,130	14,720	13,380	11,010	9,010	7,340	5,940	5,320
LZ*020M6	ZS15KAE	22,300	18,780	17,210	15,680	12,960	10,650	8,720	7,090	6,360
LZ*025M6	ZS19KAE	24,200	20,370	18,670	17,110	14,150	11,690	9,590	7,810	7,000
LZ*030M6	ZS21KAE	35,310	29,700	27,060	24,630	20,270	16,560	13,440	10,840	9,710
LZ*035M6	ZS26KAE	37,880	32,030	29,300	26,690	22,040	18,040	14,680	11,860	10,620
LZ*045M6	ZS29KAE	41,600	35,430	32,420	29,560	24,530	20,140	16,440	13,310	11,930
LZ*050M6	ZS33KAE	44,850	38,020	34,910	32,010	26,610	21,910	17,940	14,570	—
LZ*055M6	ZS38K4E	47,970	42,650	39,740	36,840	31,120	25,700	20,340	14,960	12,300
LZ*060M6	ZS45K4E	—	49,170	46,060	42,880	36,520	30,370	24,460	18,630	15,760

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II™

PERFORMANCE DATA: SCROLL COMPRESSOR MODELS

Medium Temperature Models R-407A

Model	Compressor	Capacity BTUH @ 90°F Ambient by SST								
		40°F	30°F	25°F	20°F	10°F	0°F	-10°F	-20°F	-25°F
LZ*010M6	ZS09KAE	15,350	12,820	11,710	10,690	8,870	7,290	5,850	4,430	3,690
LZ*015M6	ZS13KAE	19,540	16,560	15,170	13,890	11,580	9,600	7,760	5,970	5,040
LZ*020M6	ZS15KAE	22,390	19,080	17,590	16,150	13,550	11,250	9,170	7,060	5,960
LZ*025M6	ZS19KAE	24,230	20,780	19,180	17,700	14,910	12,430	10,130	7,820	-
LZ*030M6	ZS21KAE	35,850	30,360	27,740	25,240	20,660	16,570	12,990	9,810	8,370
LZ*035M6	ZS26KAE	39,030	33,210	30,410	27,730	22,760	18,340	14,270	10,490	8,680
LZ*045M6	ZS29KAE	-	-	30,800	28,160	23,260	18,790	14,670	10,770	8,860
LZ*050M6	ZS33KAE	46,450	39,990	36,780	33,690	27,860	22,470	17,590	12,960	10,730
LZ*055M6	ZS38K4E	-	43,820	40,600	37,520	31,280	25,510	20,360	16,040	-
LZ*060M6	ZS45K4E	-	-	46,630	43,090	36,400	30,070	24,390	-	-

Model	Compressor	Capacity BTUH @ 95°F Ambient by SST								
		40°F	30°F	25°F	20°F	10°F	0°F	-10°F	-20°F	-25°F
LZ*010M6	ZS09KAE	14,820	12,380	11,320	10,330	8,570	7,040	5,660	4,290	3,570
LZ*015M6	ZS13KAE	18,820	15,950	14,620	13,390	11,170	9,260	7,500	5,770	-
LZ*020M6	ZS15KAE	21,530	18,360	16,930	15,550	13,050	10,840	8,850	-	-
LZ*025M6	ZS19KAE	-	19,980	18,500	17,020	14,350	11,980	9,780	-	-
LZ*030M6	ZS21KAE	34,670	29,320	26,800	24,390	19,950	15,970	12,430	9,250	-
LZ*035M6	ZS26KAE	37,660	32,080	29,400	26,830	22,030	17,710	13,700	9,940	-
LZ*045M6	ZS29KAE	-	-	29,690	27,170	22,410	18,110	14,060	10,180	-
LZ*050M6	ZS33KAE	44,830	38,640	35,570	32,600	26,980	21,740	16,900	-	-
LZ*055M6	ZS38K4E	-	42,170	39,080	36,110	30,110	24,560	19,620	-	-
LZ*060M6	ZS45K4E	-	-	-	41,490	35,030	28,930	-	-	-

Model	Compressor	Capacity BTUH @ 100°F Ambient by SST								
		40°F	30°F	25°F	20°F	10°F	0°F	-10°F	-20°F	-25°F
LZ*010M6	ZS09KAE	14,280	11,940	10,920	9,950	8,260	6,790	5,460	4,140	-
LZ*015M6	ZS13KAE	18,090	15,340	14,060	12,880	10,750	8,920	7,230	-	-
LZ*020M6	ZS15KAE	-	17,690	16,270	14,940	12,550	10,440	8,530	-	-
LZ*025M6	ZS19KAE	-	19,160	17,750	16,340	13,790	11,520	-	-	-
LZ*030M6	ZS21KAE	33,430	28,310	25,890	23,580	19,290	15,400	11,900	-	-
LZ*035M6	ZS26KAE	36,410	30,980	28,410	25,950	21,330	17,120	13,180	-	-
LZ*045M6	ZS29KAE	-	-	28,600	26,200	21,650	17,470	13,510	-	-
LZ*050M6	ZS33KAE	-	37,340	34,430	31,590	26,180	21,080	-	-	-
LZ*055M6	ZS38K4E	-	-	-	34,660	28,910	23,600	-	-	-
LZ*060M6	ZS45K4E	-	-	-	-	33,630	-	-	-	-

Model	Compressor	Capacity BTUH @ 110°F Ambient by SST								
		40°F	30°F	25°F	20°F	10°F	0°F	-10°F	-20°F	-25°F
LZ*010M6	ZS09KAE	13,180	11,030	10,100	9,200	7,640	6,300	-	-	-
LZ*015M6	ZS13KAE	-	14,100	12,940	11,860	9,920	8,240	-	-	-
LZ*020M6	ZS15KAE	-	-	-	-	11,550	-	-	-	-
LZ*025M6	ZS19KAE	-	-	-	-	12,670	-	-	-	-
LZ*030M6	ZS21KAE	-	26,490	24,290	22,150	18,180	14,500	-	-	-
LZ*035M6	ZS26KAE	-	-	26,600	24,320	20,110	16,130	-	-	-
LZ*045M6	ZS29KAE	-	-	-	24,430	20,310	-	-	-	-
LZ*050M6	ZS33KAE	-	-	-	-	24,900	-	-	-	-
LZ*055M6	ZS38K4E	-	-	-	-	-	-	-	-	-
LZ*060M6	ZS45K4E	-	-	-	-	-	-	-	-	-

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II™

20°F Maximum Superheat

PERFORMANCE DATA: SCROLL COMPRESSOR MODELS

Medium Temperature Models R-407C

Model	Compressor	Capacity BTUH @ 90°F Ambient by SST								
		40°F	30°F	25°F	20°F	10°F	0°F	-10°F	-20°F	-25°F
LZ*010M6	ZS09KAE	13,910	11,640	10,590	9,550	7,610	5,780	4,010	2,210	—
LZ*015M6	ZS13KAE	18,110	15,260	13,910	12,600	10,090	7,630	5,170	2,590	—
LZ*020M6	ZS15KAE	21,050	17,870	16,310	14,800	11,890	9,090	6,310	3,480	—
LZ*025M6	ZS19KAE	23,100	19,700	18,010	16,370	13,220	10,230	7,370	4,560	—
LZ*030M6	ZS21KAE	33,600	28,210	25,650	23,170	18,560	14,250	10,210	6,330	—
LZ*035M6	ZS26KAE	36,670	30,890	28,150	25,490	20,420	15,510	10,610	5,530	—
LZ*045M6	ZS29KAE	40,190	34,030	31,040	28,140	22,590	17,380	12,360	7,410	—
LZ*050M6	ZS33KAE	43,590	37,040	33,810	30,660	24,610	18,820	13,150	7,500	—
LZ*055M6	ZS38K4E	—	44,900	41,370	37,900	31,360	25,330	20,090	15,790	—
LZ*060M6	ZS45K4E	—	—	47,950	44,020	36,630	30,020	24,160	19,080	—

Model	Compressor	Capacity BTUH @ 95°F Ambient by SST								
		40°F	30°F	25°F	20°F	10°F	0°F	-10°F	-20°F	-25°F
LZ*010M6	ZS09KAE	13,540	11,350	10,320	9,310	7,420	5,620	3,870	2,080	—
LZ*015M6	ZS13KAE	17,610	14,860	13,540	12,260	9,810	7,400	4,980	2,430	—
LZ*020M6	ZS15KAE	20,470	17,390	15,880	14,400	11,560	8,800	6,070	3,280	—
LZ*025M6	ZS19KAE	22,450	19,160	17,510	15,910	12,840	9,910	7,090	4,320	—
LZ*030M6	ZS21KAE	32,700	27,470	24,980	22,570	18,050	13,810	9,800	5,940	—
LZ*035M6	ZS26KAE	35,680	30,080	27,410	24,820	19,870	15,040	10,210	5,180	—
LZ*045M6	ZS29KAE	39,100	33,140	30,230	27,400	21,980	16,870	11,920	7,020	—
LZ*050M6	ZS33KAE	42,380	36,020	32,870	29,800	23,870	18,160	12,520	6,900	—
LZ*055M6	ZS38K4E	—	43,500	40,070	36,700	30,340	24,500	19,440	—	—
LZ*060M6	ZS45K4E	—	—	—	42,670	35,570	29,040	23,370	18,520	—

Model	Compressor	Capacity BTUH @ 100°F Ambient by SST								
		40°F	30°F	25°F	20°F	10°F	0°F	-10°F	-20°F	-25°F
LZ*010M6	ZS09KAE	13,180	11,050	10,030	9,060	7,210	5,450	3,720	1,940	—
LZ*015M6	ZS13KAE	17,120	14,450	13,170	11,920	9,520	7,150	4,770	2,240	—
LZ*020M6	ZS15KAE	19,890	16,900	15,430	14,000	11,220	8,510	5,810	3,050	—
LZ*025M6	ZS19KAE	—	18,610	17,010	15,460	12,460	9,570	6,800	—	—
LZ*030M6	ZS21KAE	31,800	26,730	24,310	21,950	17,520	13,350	9,390	5,530	—
LZ*035M6	ZS26KAE	34,690	29,260	26,660	24,140	19,300	14,540	9,780	4,790	—
LZ*045M6	ZS29KAE	38,020	32,240	29,410	26,660	21,370	16,350	11,460	—	—
LZ*050M6	ZS33KAE	41,160	34,990	31,920	28,920	23,100	17,460	11,850	—	—
LZ*055M6	ZS38K4E	—	—	—	35,580	29,310	23,670	—	—	—
LZ*060M6	ZS45K4E	—	—	—	—	34,380	28,050	—	—	—

Model	Compressor	Capacity BTUH @ 110°F Ambient by SST								
		40°F	30°F	25°F	20°F	10°F	0°F	-10°F	-20°F	-25°F
LZ*010M6	ZS09KAE	12,440	10,450	9,490	8,560	6,790	5,080	3,380	—	—
LZ*015M6	ZS13KAE	—	13,620	12,410	11,230	8,920	6,630	—	—	—
LZ*020M6	ZS15KAE	—	—	—	13,170	10,510	7,890	—	—	—
LZ*025M6	ZS19KAE	—	—	—	—	11,650	—	—	—	—
LZ*030M6	ZS21KAE	30,000	25,220	22,920	20,690	16,420	12,350	—	—	—
LZ*035M6	ZS26KAE	—	27,590	25,140	22,740	18,080	13,480	—	—	—
LZ*045M6	ZS29KAE	—	—	27,780	25,170	20,110	15,250	—	—	—
LZ*050M6	ZS33KAE	—	—	—	27,080	21,460	15,920	—	—	—
LZ*055M6	ZS38K4E	—	—	—	—	—	—	—	—	—
LZ*060M6	ZS45K4E	—	—	—	—	—	—	—	—	—

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II™

20°F Maximum Superheat

PERFORMANCE DATA: SCROLL COMPRESSOR MODELS

Low Temperature Models R-404A/507

Model	Compressor	Capacity BTUH @ 90°F Ambient by SST								
		0°F	-5°F	-10°F	-15°F	-20°F	-25°F	-30°F	-35°F	-40°F
LZ*020L6	ZF06K4E	11,670	10,620	9,640	8,710	7,840	7,020	6,240	5,500	4,790
LZ*025L6	ZF08K4E	14,330	13,090	11,880	10,750	9,690	8,690	7,770	6,900	6,080
LZ*030L6	ZF09K4E	15,860	14,480	13,220	11,990	10,840	9,760	8,730	7,760	6,830
LZ*035L6	ZF11K4E	18,860	17,300	15,810	14,390	13,030	11,760	10,550	9,410	8,330
LZ*045L6	ZF13K4E	23,620	21,430	19,380	17,440	15,620	13,930	12,350	10,880	9,510
LZ*055L6	ZF15K4E	28,370	25,910	23,520	21,280	19,190	17,230	15,400	13,690	12,090
LZ*060L6	ZF18K4E	32,630	29,860	27,230	24,790	22,400	20,170	18,060	16,040	14,110

Model	Compressor	Capacity BTUH @ 95°F Ambient by SST								
		0°F	-5°F	-10°F	-15°F	-20°F	-25°F	-30°F	-35°F	-40°F
LZ*020L6	ZF06K4E	11,220	10,220	9,280	8,390	7,560	6,760	6,010	5,290	4,600
LZ*025L6	ZF08K4E	13,760	12,570	11,410	10,330	9,320	8,360	7,470	6,640	5,850
LZ*030L6	ZF09K4E	15,200	13,890	12,690	11,520	10,420	9,380	8,410	7,470	6,580
LZ*035L6	ZF11K4E	18,010	16,530	15,120	13,780	12,490	11,290	10,130	9,040	8,010
LZ*045L6	ZF13K4E	22,630	20,540	18,570	16,720	14,990	13,370	11,880	10,480	9,200
LZ*055L6	ZF15K4E	27,170	24,820	22,540	20,410	18,420	16,550	14,810	13,170	11,640
LZ*060L6	ZF18K4E	31,270	28,650	26,180	23,830	21,560	19,430	17,420	15,490	13,640

Model	Compressor	Capacity BTUH @ 100°F Ambient by SST								
		0°F	-5°F	-10°F	-15°F	-20°F	-25°F	-30°F	-35°F	-40°F
LZ*020L6	ZF06K4E	10,770	9,820	8,930	8,080	7,270	6,510	5,790	5,090	4,420
LZ*025L6	ZF08K4E	13,150	12,000	10,920	9,900	8,930	8,020	7,170	6,370	5,610
LZ*030L6	ZF09K4E	14,530	13,290	12,160	11,040	9,990	9,000	8,070	7,170	6,310
LZ*035L6	ZF11K4E	17,140	15,750	14,420	13,110	11,950	10,790	9,690	8,660	7,680
LZ*045L6	ZF13K4E	21,620	19,620	17,750	15,990	14,350	12,820	11,400	10,100	8,890
LZ*055L6	ZF15K4E	25,970	23,710	21,540	19,520	17,630	15,850	14,200	12,640	11,170
LZ*060L6	ZF18K4E	29,890	27,360	25,070	22,860	20,700	18,680	16,770	14,930	13,170

Model	Compressor	Capacity BTUH @ 110°F Ambient by SST								
		0°F	-5°F	-10°F	-15°F	-20°F	-25°F	-30°F	-35°F	-40°F
LZ*020L6	ZF06K4E	9,890	9,040	8,230	7,470	6,730	6,040	5,370	4,720	4,090
LZ*025L6	ZF08K4E	11,910	10,870	9,900	8,980	8,120	7,300	6,530	5,790	5,100
LZ*030L6	ZF09K4E	13,120	12,060	11,040	10,030	9,100	8,210	7,360	6,550	5,760
LZ*035L6	ZF11K4E	15,340	14,120	12,940	11,800	10,730	9,740	8,760	7,840	6,970
LZ*045L6	ZF13K4E	19,540	17,740	16,070	14,500	13,040	11,690	10,460	9,330	8,300
LZ*055L6	ZF15K4E	23,380	21,350	19,450	17,660	15,970	14,390	12,910	11,510	10,190
LZ*060L6	ZF18K4E	27,080	24,860	22,830	20,820	18,940	17,140	15,430	13,790	12,200

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II™

The ZF compressor comes with liquid injection.

PERFORMANCE DATA: SCROLL COMPRESSOR MODELS

Low Temperature Models R-407A

Model	Compressor	Capacity BTUH @ 90°F Ambient by SST								
		0°F	-5°F	-10°F	-15°F	-20°F	-25°F	-30°F	-35°F	-40°F
LZ*020L6	ZF06K4E	10,710	9,700	8,730	7,800	6,910	6,100	5,340	4,640	4,000
LZ*025L6	ZF08K4E	12,760	11,590	10,450	9,380	8,350	7,380	6,480	5,640	4,870
LZ*030L6	ZF09K4E	13,850	12,740	11,570	10,390	9,230	8,110	7,100	6,230	5,540
LZ*035L6	ZF11K4E	16,260	15,040	13,730	12,410	11,060	9,760	8,560	7,520	6,700
LZ*045L6	ZF13K4E	21,360	19,200	17,140	15,180	13,350	11,710	10,280	9,070	8,120
LZ*055L6	ZF15K4E	25,310	22,740	20,370	18,130	16,070	14,210	12,600	11,230	10,160
LZ*060L6	ZF18K4E	29,350	26,560	23,840	21,310	18,950	16,790	14,880	13,240	11,940

Model	Compressor	Capacity BTUH @ 95°F Ambient by SST								
		0°F	-5°F	-10°F	-15°F	-20°F	-25°F	-30°F	-35°F	-40°F
LZ*020L6	ZF06K4E	10,330	9,350	8,420	7,530	6,690	5,900	5,160	4,490	3,870
LZ*025L6	ZF08K4E	12,260	11,120	10,060	9,030	8,050	7,120	6,250	5,440	4,700
LZ*030L6	ZF09K4E	13,350	12,280	11,190	10,060	8,940	7,860	6,870	6,020	5,340
LZ*035L6	ZF11K4E	15,570	14,420	13,230	11,970	10,680	9,430	8,270	7,260	6,460
LZ*045L6	ZF13K4E	20,610	18,480	16,500	14,600	12,850	11,280	9,910	8,760	7,890
LZ*055L6	ZF15K4E	24,320	21,890	19,590	17,430	15,430	13,650	12,090	10,800	9,780
LZ*060L6	ZF18K4E	28,290	25,590	22,960	20,530	18,240	16,160	14,320	12,760	11,520

Model	Compressor	Capacity BTUH @ 100°F Ambient by SST								
		0°F	-5°F	-10°F	-15°F	-20°F	-25°F	-30°F	-35°F	-40°F
LZ*020L6	ZF06K4E	9,920	9,000	8,110	7,250	6,450	5,690	4,980	4,330	3,730
LZ*025L6	ZF08K4E	11,730	10,660	9,650	8,670	7,730	6,840	6,010	5,230	4,520
LZ*030L6	ZF09K4E	12,820	11,840	10,800	9,720	8,650	7,610	6,650	5,810	5,140
LZ*035L6	ZF11K4E	—	—	—	—	10,270	9,100	7,990	7,000	6,220
LZ*045L6	ZF13K4E	19,840	17,760	15,840	14,000	12,320	10,810	9,510	8,440	7,650
LZ*055L6	ZF15K4E	23,350	21,000	18,780	16,680	14,760	13,040	11,560	10,320	9,370
LZ*060L6	ZF18K4E	27,200	24,590	22,060	19,710	17,510	15,500	13,740	12,240	11,060

Model	Compressor	Capacity BTUH @ 110°F Ambient by SST								
		0°F	-5°F	-10°F	-15°F	-20°F	-25°F	-30°F	-35°F	-40°F
LZ*020L6	ZF06K4E	9,070	8,240	7,430	6,660	5,920	5,230	4,580	3,980	3,430
LZ*025L6	ZF08K4E	—	—	—	—	—	6,250	5,500	4,790	4,140
LZ*030L6	ZF09K4E	—	—	—	—	—	—	6,210	5,420	4,770
LZ*035L6	ZF11K4E	—	—	—	—	—	—	—	—	—
LZ*045L6	ZF13K4E	18,170	16,250	14,420	12,720	11,170	9,800	8,640	7,740	7,100
LZ*055L6	ZF15K4E	—	—	—	—	—	11,720	10,370	9,260	8,420
LZ*060L6	ZF18K4E	—	—	—	—	—	—	—	11,110	10,050

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II™

Liquid Injection is required for all operating conditions

PERFORMANCE DATA: SCROLL COMPRESSOR MODELS

Low Temperature Models R-407C

Model	Compressor	Capacity BTUH @ 90°F Ambient by SST								
		0°F	-5°F	-10°F	-15°F	-20°F	-25°F	-30°F	-35°F	-40°F
LZ*020L6	ZF06K4E	9,510	8,510	7,590	6,740	5,970	5,260	4,620	4,020	3,470
LZ*030L6	ZF09K4E	12,420	11,340	10,260	9,170	8,120	7,130	6,240	5,490	4,920
LZ*035L6	ZF11K4E	14,840	13,620	12,360	11,060	9,800	8,610	7,550	6,660	6,010
LZ*045L6	ZF13K4E	18,720	16,750	14,870	13,120	11,510	10,070	8,840	7,810	7,040
LZ*055L6	ZF15K4E	22,320	20,030	17,870	15,840	13,980	12,310	10,890	9,720	8,840
LZ*060L6	ZF18K4E	26,110	23,500	21,000	18,690	16,560	14,640	12,970	11,580	10,520

Model	Compressor	Capacity BTUH @ 95°F Ambient by SST								
		0°F	-5°F	-10°F	-15°F	-20°F	-25°F	-30°F	-35°F	-40°F
LZ*020L6	ZF06K4E	9,230	8,270	7,380	6,570	5,820	5,130	4,510	3,920	3,380
LZ*030L6	ZF09K4E	12,050	11,010	9,970	8,910	7,900	6,940	6,070	5,330	4,760
LZ*035L6	ZF11K4E	14,330	13,170	11,950	10,720	9,510	8,360	7,330	6,460	5,820
LZ*045L6	ZF13K4E	18,160	16,230	14,380	12,670	11,110	9,730	8,540	7,570	6,850
LZ*055L6	ZF15K4E	21,630	19,400	17,270	15,310	13,510	11,900	10,520	9,400	8,570
LZ*060L6	ZF18K4E	25,330	22,790	20,350	18,100	16,030	14,170	12,560	11,230	10,220

Model	Compressor	Capacity BTUH @ 100°F Ambient by SST								
		0°F	-5°F	-10°F	-15°F	-20°F	-25°F	-30°F	-35°F	-40°F
LZ*020L6	ZF06K4E	8,930	8,020	7,160	6,380	5,660	4,990	4,380	3,820	3,290
LZ*030L6	ZF09K4E	11,670	10,680	9,680	8,670	7,680	6,750	5,910	5,180	4,610
LZ*035L6	ZF11K4E	13,810	12,690	11,550	10,380	9,220	8,110	7,110	6,260	5,630
LZ*045L6	ZF13K4E	17,570	15,680	13,880	12,220	10,710	9,370	8,240	7,330	6,670
LZ*055L6	ZF15K4E	20,910	18,730	16,670	14,760	13,020	11,470	10,130	9,060	8,280
LZ*060L6	ZF18K4E	24,530	22,050	19,680	17,490	15,480	13,680	12,130	10,860	9,900

Model	Compressor	Capacity BTUH @ 110°F Ambient by SST								
		0°F	-5°F	-10°F	-15°F	-20°F	-25°F	-30°F	-35°F	-40°F
LZ*020L6	ZF06K4E	8,300	7,460	6,690	5,960	5,300	4,680	4,110	3,580	3,070
LZ*030L6	ZF09K4E	—	—	—	—	—	6,380	5,580	4,890	4,330
LZ*035L6	ZF11K4E	—	—	—	—	—	—	—	5,880	5,270
LZ*045L6	ZF13K4E	16,330	14,530	12,840	11,260	9,860	8,630	7,620	6,820	6,270
LZ*055L6	ZF15K4E	19,340	17,280	15,380	13,560	11,930	10,490	9,260	8,280	7,580
LZ*060L6	ZF18K4E	—	—	—	—	—	12,620	11,190	10,020	9,160

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II™
Liquid Injection is required for all operating conditions

UNIT SPECIFICATIONS: SCROLL COMPRESSOR MODELS

Model	Fig. ++	Compressor	Connections (ID)		Receiver 90% Full Lbs.	Fan(s)	Dimensions			Net. Wt. Lbs.	Sound Data dBA [†]
			Liquid	Suction			D (In.)	W (In.)	H (In.)		
LZ*010M6	C	ZS09KAE	1/2	7/8	14	2	28-1/4	37-3/4	19-3/4	209	71
LZ*015M6	C	ZS13KAE	1/2	7/8	14	2	28-1/4	37-3/4	19-3/4	209	71
LZ*020M6	C	ZS15KAE	1/2	7/8	14	2	28-1/4	37-3/4	19-3/4	209	71
LZ*025M6	C	ZS19KAE	1/2	7/8	14	2	28-1/4	37-3/4	19-3/4	218	73
LZ*030M6	D	ZS21KAE	1/2	7/8	20	1	30-1/4	42-1/2	29-3/4	287	72
LZ*035M6	D	ZS26KAE	1/2	7/8	20	1	30-1/4	42-1/2	29-3/4	290	74
LZ*045M6	D	ZS29KAE	1/2	1-1/8	20	1	30-1/4	42-1/2	29-3/4	317	73
LZ*050M6	D	ZS33KAE	1/2	1-1/8	20	1	30-1/4	42-1/2	29-3/4	317	73
LZ*055M6	D	ZS38K4E	1/2	1-1/8	20	1	30-1/4	42-1/2	29-3/4	317	74
LZ*060M6	D	ZS45K43	1/2	1-1/8	20	1	30-1/4	42-1/2	29-3/4	317	76
LZ*020L6	C	ZF06K4E	1/2	7/8	14	2	28-1/4	37-3/4	19-3/4	209	71
LZ*025L6	C	ZF08K4E	1/2	7/8	14	2	28-1/4	37-3/4	19-3/4	218	73
LZ*030L6	C	ZF09K4E	1/2	7/8	14	2	28-1/4	37-3/4	19-3/4	218	71
LZ*035L6	C	ZF11K4E	1/2	7/8	14	2	28-1/4	37-3/4	19-3/4	217	73
LZ*045L6	D	ZF13K4E	1/2	1-1/8	20	1	30-1/4	42-1/2	29-3/4	307	73
LZ*055L6	D	ZF15K4E	1/2	1-1/8	20	1	30-1/4	42-1/2	29-3/4	313	74
LZ*060L6	D	ZF18K4E	1/2	1-1/8	20	1	30-1/4	42-1/2	29-3/4	317	76

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II™

++ = See Dimensional Drawings for details

† = Estimated sound pressure values are 10 feet from the unit. For estimating sound pressure from the unit at different distances, deduct the following from the unit values: 20 feet, deduct 6 dBA; for 40 feet, deduct 12 dBA; for 80 feet, deduct 18 dBA. This data is typical of "free field" conditions for horizontal air cooled condensing units at the outlet of the discharge air. The actual sound measurements may vary depending on the condensing unit installation. Factors such as reflecting walls, background noise and mounting conditions may have a significant influence on this data.

PERFORMANCE DATA: SEMI-HERMETIC COMPRESSOR MODELS

Medium Temperature Models R-404A/507

Model	Compressor	Capacity BTUH @ 90°F Ambient by SST						
		25°F	20°F	15°F	10°F	5°F	0°F	-5°F
LS*010M6	KAR-010E	9,680	8,730	7,930	7,260	6,500	5,890	5,000
LS*020M6	KAK-020E	16,890	15,110	13,590	12,260	11,070	9,940	8,690
LS*021M6	ERC-021E	19,930	17,400	15,800	14,300	12,800	11,840	10,220
LS*030M6	ERF-031E	30,880	28,310	25,730	23,180	20,690	18,260	15,950

Model	Compressor	Capacity BTUH @ 95°F Ambient by SST						
		25°F	20°F	15°F	10°F	5°F	0°F	-5°F
LS*010M6	KAR-010E	9,140	8,300	7,600	6,870	6,150	5,550	4,730
LS*020M6	KAK-020E	16,240	14,530	13,070	11,790	10,640	9,560	8,360
LS*021M6	ERC-021E	18,850	16,500	14,900	13,500	12,700	11,140	9,580
LS*030M6	ERF-031E	29,690	27,220	24,740	22,290	19,890	17,560	15,340

Model	Compressor	Capacity BTUH @ 100°F Ambient by SST						
		25°F	20°F	15°F	10°F	5°F	0°F	-5°F
LS*010M6	KAR-010E	8,680	7,950	7,110	6,410	5,780	5,220	4,450
LS*020M6	KAK-020E	15,590	13,950	12,550	11,320	10,210	9,180	8,030
LS*021M6	ERC-021E	17,840	16,280	14,870	13,440	11,970	10,450	8,940
LS*030M6	ERF-031E	28,500	26,130	23,750	21,400	19,090	16,860	14,730

Model	Compressor	Capacity BTUH @ 110°F Ambient by SST						
		25°F	20°F	15°F	10°F	5°F	0°F	-5°F
LS*010M6	KAR-010E	7,740	7,000	6,350	5,720	5,120	4,600	3,900
LS*020M6	KAK-020E	14,290	12,790	11,500	10,380	9,360	8,410	7,360
LS*021M6	ERC-021E	15,840	14,610	12,600	11,850	10,470	9,180	7,770
LS*030M6	ERF-031E	26,130	23,950	21,770	19,620	17,500	15,450	13,500

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II™

PERFORMANCE DATA: SEMI-HERMETIC COMPRESSOR MODELS

Low Temperature Models R-404A/507

Model	Compressor	Capacity BTUH @ 90°F Ambient by SST						
		0°F	-5°F	-10°F	-20°F	-25°F	-30°F	-40°F
LS*005L6	KAN-005E	3,530	3,150	2,760	2,050	1,720	1,420	930
LS*008L6	KAM-007E	6,010	5,360	4,730	3,570	3,050	2,580	1,820
LS*010L6	KAJ-010E	7,770	6,990	6,240	4,830	4,190	3,610	2,640
LS*015L6	KAL-015E	11,780	10,600	9,470	7,340	6,370	5,500	4,020
LS*020L6	EAD-020E	13,780	12,290	10,860	8,260	7,120	6,100	4,470
LS*021L6	EAV-021E	15,120	13,660	12,200	9,420	8,140	6,980	5,160
LS*030L6	LAH-032E	22,600	20,320	18,090	13,810	11,830	9,970	6,780
LS*030E6	LAC-032E	—	—	—	16,780	14,570	12,540	9,010

Model	Compressor	Capacity BTUH @ 95°F Ambient by SST						
		0°F	-5°F	-10°F	-20°F	-25°F	-30°F	-40°F
LS*005L6	KAN-005E	3,310	2,940	2,580	1,900	1,580	1,300	830
LS*008L6	KAM-007E	5,520	4,900	4,320	3,280	2,810	2,390	1,620
LS*010L6	KAJ-010E	7,220	6,480	5,790	4,520	3,940	3,390	2,440
LS*015L6	KAL-015E	10,960	9,930	8,920	6,990	6,110	5,300	3,930
LS*020L6	EAD-020E	12,530	11,160	9,870	7,520	6,490	5,560	3,980
LS*021L6	EAV-021E	13,920	12,600	11,280	8,780	7,610	6,520	4,590
LS*030L6	LAH-032E	21,310	19,100	16,930	12,800	10,880	9,100	6,040
LS*030E6	LAC-032E	—	—	—	15,700	13,550	11,580	8,270

Model	Compressor	Capacity BTUH @ 100°F Ambient by SST						
		0°F	-5°F	-10°F	-20°F	-25°F	-30°F	-40°F
LS*005L6	KAN-005E	3,100	2,760	2,400	1,750	1,450	1,170	750
LS*008L6	KAM-007E	5,290	4,680	4,100	3,020	2,540	2,100	1,400
LS*010L6	KAJ-010E	6,900	6,180	5,470	4,160	3,570	3,030	2,150
LS*015L6	KAL-015E	10,520	9,460	8,410	6,440	5,540	4,700	3,300
LS*020L6	EAD-020E	12,140	10,730	9,400	6,970	5,920	4,980	3,530
LS*021L6	EAV-021E	13,390	12,110	10,810	8,260	7,060	5,940	4,050
LS*030L6	LAH-032E	20,020	17,890	15,790	11,790	9,940	8,230	5,300
LS*030E6	LAC-032E	—	—	—	14,630	12,530	10,640	7,540

Model	Compressor	Capacity BTUH @ 110°F Ambient by SST						
		0°F	-5°F	-10°F	-20°F	-25°F	-30°F	-40°F
LS*005L6	KAN-005E	2,680	2,360	2,030	1,440	1,160	900	520
LS*008L6	KAM-007E	4,560	4,010	3,470	2,480	2,030	1,620	970
LS*010L6	KAJ-010E	6,040	5,370	4,720	3,510	2,960	2,470	1,660
LS*015L6	KAL-015E	9,290	8,320	7,370	5,560	4,710	3,930	2,580
LS*020L6	EAD-020E	10,510	9,210	7,950	6,000	4,720	3,880	2,610
LS*021L6	EAV-021E	11,670	10,570	9,450	7,130	5,990	4,900	2,950
LS*030L6	LAH-032E	17,480	15,490	13,530	9,800	8,080	6,490	3,750
LS*030E6	LAC-032E	—	—	—	12,510	10,510	8,760	6,090

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II™

UNIT SPECIFICATIONS: SEMI-HERMETIC COMPRESSOR MODELS

Model	Fig. ++	Compressor	Connections (ID)		Receiver 90% Full Lbs.	Fan(s)	Dimensions			Net. Wt. Lbs.	Sound Data dBA [†]
			Liquid	Suction			D (In.)	W (In.)	H (In.)		
LS*010M6	A	KAR-010E	3/8	5/8	5.5	1	28-1/4	23-3/4	17-1/4	178	67
LS*020M6	B	KAK-020E	3/8	7/8	9.0	2	28-1/4	37-3/4	17-1/4	189	69
LS*021M6	B	ERC-021E	3/8	7/8	9.0	2	28-1/4	37-3/4	17-1/4	301	70
LS*030M6	D	ERF-031E	1/2	7/8	20.0	1	30-1/4	42-1/2	29-3/4	397	71
LS*005L6	A	KAN-005E	3/8	1/2	5.5	1	28-1/4	23-3/4	17-1/4	172	67
LS*008L6	A	KAM-007E	3/8	5/8	5.5	1	28-1/4	23-3/4	17-1/4	172	67
LS*010L6	A	KAJ-010E	3/8	5/8	5.5	1	28-1/4	23-3/4	17-1/4	178	67
LS*015L6	B	KAL-015E	3/8	7/8	9.0	2	28-1/4	37-3/4	17-1/4	225	69
LS*020L6	B	EAD-020E	3/8	7/8	9.0	2	28-1/4	37-3/4	17-1/4	291	70
LS*021L6	B	EAV-021E	3/8	7/8	9.0	2	28-1/4	37-3/4	17-1/4	301	70
LS*030L6	C	LAH-032E	1/2	7/8	14.0	2	28-1/4	37-3/4	19-3/4	357	71
LS*030E6	C	LAC-032E	1/2	7/8	14.0	2	28-1/4	37-3/4	19-3/4	391	71

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II™

++ = See Dimensional Drawings for details

[†] = Estimated sound pressure values are 10 feet from the unit. For estimating sound pressure from the unit at different distances, deduct the following from the unit values: 20 feet, deduct 6 dBA; for 40 feet, deduct 12 dBA; for 80 feet, deduct 18 dBA. This data is typical of "free field" conditions for horizontal air cooled condensing units at the outlet of the discharge air. The actual sound measurements may vary depending on the condensing unit installation. Factors such as reflecting walls, background noise and mounting conditions may have a significant influence on this data.

ELECTRICAL DATA: SEMI-HERMETIC COMPRESSOR MODELS

Model Number	Part Number	Power Supply			Compressor		Fan Motor			MCA		MOPD		Evap. Fan Amps	Defrost Heater Amps
		Volts	Ph	Hz [†]	RLA	LRA	Qty.	HP	FLA	Air	Elec.	Air	Elec.		
LS*010M6B	KARB-010E-CAV	208-230	1	60	6.4	40.0	1	1/15	0.5	15	20	15	20	7.0	15
LS*010M6C	KARA-010E-TAC	208-230	3	60	3.8	27.0	1	1/15	0.5	15	20	15	20	9.0	15
LS*020M6B	KAKB-021E-CAV	208-230	1	60	9.1	55.0	2	1/15	1.0	15	24	20	25	6.0	19
LS*020M6C	KAKA-020E-TAC	208-230	3	60	5.8	50.0	2	1/15	1.0	15	24	15	25	9.0	19
LS*021M6C	ERCA-021E-TAC	208-230	3	60	7.9	46.0	2	1/15	1.0	15	24	15	25	9.0	19
LS*021M6D	ERCA-020E-TAD	460	3	60	3.1	23.0	2	1/15	1.0	15	15	15	15	^	^
LS*030M6C	ERFA-031E-TAC	208-230	3	60	11.2	82.0	1	1/3	3.5	20	38	25	40	12.0	30
LS*030M6D	ERFA-031E-TAD	460	3	60	5.2	41.0	1	1/3	1.9	15	15	15	15	^	^
LS*005L6B	KANB-005E-CAV	208-230	1	60	3.1	24.0	1	1/15	0.5	15	20	15	20	9.0	15
LS*005L6C	KANA-006E-TAC	208-230	3	60	2.0	13.2	1	1/15	0.5	15	20	15	20	9.6	15
LS*008L6B	KAMB-007E-CAV	208-230	1	60	5.1	36.0	1	1/15	0.5	15	20	15	20	8.0	15
LS*008L6C	KAMA-007E-TAC	208-230	3	60	2.9	19.9	1	1/15	0.5	15	20	15	20	9.0	15
LS*010L6B	KAJB-010E-CAV	208-230	1	60	6.2	40.0	1	1/15	0.5	15	20	15	20	8.0	15
LS*010L6C	KAJA-011E-TAC	208-230	3	60	4.1	27.0	1	1/15	0.5	15	20	15	20	9.0	15
LS*015L6B	KALB-015E-CAV	208-230	1	60	8.9	55.0	2	1/15	1.0	15	24	20	25	8.0	19
LS*015L6C	KALA-016E-TAC	208-230	3	60	6.0	50.0	2	1/15	1.0	15	20	15	20	7.6	15
LS*015L6D	KALA-016E-TAD	460	3	60	3.1	25.0	2	1/15	1.0	15	20	15	20	9.0	15
LS*020L6C	EADA-020E-TAC	208-230	3	60	6.1	46.0	2	1/15	1.0	15	20	15	20	7.0	15
LS*021L6B	EAVB-021E-CAV	208-230	1	60	13.2	102.0	2	1/15	1.0	20	29	30	30	4.0	23
LS*021L6C	EAVA-021E-TAC	208-230	3	60	6.6	50.0	2	1/15	1.0	15	20	15	20	7.0	15
LS*021L6D	EAVA-021E-TAD	460	3	60	2.9	26.6	2	1/15	1.0	15	20	15	20	9.0	15
LS*030L6C	LAHA-032E-TAC	208-230	3	60	11.5	112.0	2	1/15	1.0	20	29	25	35	12.0	23
LS*030L6D	LAHA-032E-TAD	460	3	60	5.4	56.0	2	1/15	1.0	15	15	15	15	^	^
LS*030E6C	LACA-032E-TAC	208-230	3	60	11.5	112.0	2	1/15	1.0	20	29	25	35	12.0	23
LS*030E6D	LACA-032E-TAD	460	3	60	5.4	56.0	2	1/15	1.0	15	15	15	15	^	^

NOTES:

* = T for Outdoor, N for Indoor, S for Beacon II™

^ Power supplied by customer.

[†]Consult factory for 50 HZ applications.

Per UL and NEC, RLA values have been calculated by dividing the Maximum Continuous Current (MCC) by 1.56.

Replacement Parts

Replacement Parts List				
Model	PSC Motor	EC Motor	Fan Blade	Orbus Controller
A, B, C Cabinet	25309101, 230/1	25319201, 230/1	22901601, 14"	28962001
D Cabinet	25309001, 230/1 25309002, 460/1	25319101, 230/1	7173156, 22"	28962001

Right source. Right parts. Right now.

InterLink™ is your link to a complete line of dependable and certified commercial refrigeration parts, accessories and innovative electronic controls for all Larkin equipment. At InterLink, we provide our wholesalers with a comprehensive selection of product solutions and innovative technologies for the installed customer base. And every product is built to ensure the same high performance standards with which all Heatcraft Refrigeration Products brands are built — backed by a dedicated team to serve every customer need, delivering at the best lead times in the industry.

Dependable. Versatile. Courteous.

Finally, one simple source for all your replacement needs from a name you can trust.




www.interlinkparts.com
800.686.7278


Dimensional Drawings

OUTDOOR



LEFT VIEW



FRONT VIEW





A





B

3HP - ALTERNATE CABINET



C




D

7/16 DIA HOLE
TYP 4 PLCS


INDOOR

FRONT VIEW


A




B



C



D



Notes

Notes



2175 West Park Place Blvd. · Stone Mountain, GA 30087
Phone: 800.537.7775 · Fax: 770.465.5900
heatcraftrpd.com



Since product improvement is a continuing effort, we reserve the right to make changes in specifications without notice.

LK-HTSTB June 2015 | Version 001