

M6JM-H043-IAA-177

HFC, R-404A, 60Hz, 1-Phase, 115V

Availability: Standard US OEM NOTE :APPLICATION APPROVAL REQUIRED**Mechanical****Electrical**

Unit Height (in):	11.4	Max Fuse Size:	20
Unit Length (in):	14.4	Min Circuit Ampacity:	13.1
Unit Width (in):	11.5	Compressor:	ASE39C5E-IAA-103
Ship Weight (lbs):	40.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	47.0
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.25 SWEAT	Compressor RLA	10.0
Suction Connection Size (in)/Type:	0.375 SWEAT	UL:	Recognized
Discharge Line Size(in):	0.25	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE2
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	12	Fan Motor Quantity:	1

Performance

Release Date:	11-Jan-2017	Return Gas Temp. (°F):	40
Compressor:	ASE39C5E-IAA-103 x 1	Subcooling (°F):	5
Performance No:	10957	Air Flow Rate (CFM):	205

90 °F Ambient Air Temperature

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-5	2,560	113.0	23.0	4.0
0	2,730	114.7	24.7	4.0
5	2,950	116.6	26.6	4.0

10	3,210	118.9	28.9	4.1
15	3,510	121.4	31.4	4.2
20	3,830	124.2	34.2	4.3
25	4,170	127.1	37.1	4.4
30	4,510	130.1	40.1	4.5