

M6JM-H043-IAA-177

HFC, R-407C, 60Hz, 1-Phase, 115V

Availability: Standard US OEM NOTE :APPLICATION APPROVAL REQUIRED**Mechanical****Electrical**

Unit Height (in):	11.4	Max Fuse Size:	20
Unit Length (in):	14.4	Min Circuit Ampacity:	13.1
Unit Width (in):	11.5	Compressor:	ASE39C5E-IAA-103
Ship Weight (lbs):	40.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	47.0
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.25 SWEAT	Compressor RLA	10.0
Suction Connection Size (in)/Type:	0.375 SWEAT	UL:	Recognized
Discharge Line Size(in):	0.25	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE2
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	12	Fan Motor Quantity:	1

Performance

Release Date:	22-Apr-2019	Return Gas Temp. (°F):	40
Compressor:	ASE39C5E-IAA-103 x 1	Subcooling (°F):	5
Performance No:	16862	Air Flow Rate (CFM):	205

90 °F Ambient Air Temperature

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
15	4,710	134.0	44.0	4.9
20	5,060	136.9	46.9	4.9
25	5,400	139.8	49.8	4.9