

M6ZL-H064-IAA-179

HFC, R-404A, 60Hz, 1-Phase, 115V

Availability: Standard US OEM

Mechanical		Electrical	
Unit Height (in):	11.7	Max Fuse Size:	15
Unit Length (in):	16.6	Min Circuit Ampacity:	10.7
Unit Width (in):	14.2	Compressor:	RFT22C1E-IAA-102
Ship Weight (lbs):	51.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	54.5
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.25 SWEAT	Compressor RLA	7.9
Suction Connection Size (in)/Type:	0.5 SWEAT	UL:	Recognized
Discharge Line Size(in):	0.25	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE2
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	15	Fan Motor Quantity:	1

Performance

Release Date:	03-May-2017	Return Gas Temp. (°F):	40
Compressor:	RFT22C1E-IAA-102 x 1	Subcooling (°F):	5
Performance No:	11304	Air Flow Rate (CFM):	300

90 °F Ambient Air Temperature

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-30	1,470	99.5	9.5	3.2
-25	1,740	100.9	10.9	3.5
-20	2,030	102.3	12.3	3.7

-15	2,340	103.9	13.9	4.0
-10	2,660	105.5	15.5	4.3
-5	2,990	107.3	17.3	4.5
0	3,350	109.1	19.1	4.8
5	3,710	111.0	21.0	5.0
10	4,080	113.0	23.0	5.2