

M6ZL-H064-IAA-179

HFO, R-448A, 60Hz, 1-Phase, 115V

Availability: Standard US OEM

| Mechanical | | Electrical | |
|------------------------------------|------------|--------------------------------|------------------|
| Unit Height (in): | 11.7 | Max Fuse Size: | 15 |
| Unit Length (in): | 16.6 | Min Circuit Ampacity: | 10.7 |
| Unit Width (in): | 14.2 | Compressor: | RFT22C1E-IAA-102 |
| Ship Weight (lbs): | 51.0 | Compressor LRA - Low: | |
| Condenser Type: | Air | Compressor LRA - High: | 54.5 |
| CopeVap Water Storage: | NA | Compressor LRA - Half winding: | |
| Liquid Connection Size (in)/Type: | 0.25 SWEAT | Compressor RLA | 7.9 |
| Suction Connection Size (in)/Type: | 0.5 SWEAT | UL: | Recognized |
| Discharge Line Size(in): | 0.25 | UL File #: | SA633 |
| Water Inlet (in): | | UL Guide Card: | LZFE2 |
| Water Outlet (in): | | | |
| Oil Type: | POE | Amps Per Motor: | |
| Oil Recharge Amount (oz): | 15 | Fan Motor Quantity: | 1 |

Performance

| | | | |
|-----------------|----------------------|------------------------|-----|
| Release Date: | 03-May-2017 | Return Gas Temp. (°F): | 40 |
| Compressor: | RFT22C1E-IAA-102 x 1 | Subcooling (°F): | 5 |
| Performance No: | 11305 | Air Flow Rate (CFM): | 300 |

90 °F Ambient Air Temperature

| Evap Temp(°F) | Unit Capacity (BTU/hr) | Cond. Temp.(°F) | Temp. Diff.(°F) | EER(BTU/wh) |
|---------------|------------------------|-----------------|-----------------|-------------|
| -30 | 1,160 | 103.4 | 13.4 | 2.9 |
| -25 | 1,350 | 104.4 | 14.4 | 3.2 |
| -20 | 1,570 | 105.4 | 15.4 | 3.4 |

| | | | | |
|-----|-------|-------|------|-----|
| -15 | 1,840 | 106.8 | 16.8 | 3.7 |
| -10 | 2,140 | 108.2 | 18.2 | 4.0 |
| -5 | 2,470 | 109.9 | 19.9 | 4.3 |
| 0 | 2,830 | 111.6 | 21.6 | 4.6 |
| 5 | 3,220 | 113.5 | 23.5 | 4.9 |
| 10 | 3,620 | 115.5 | 25.5 | 5.2 |