

**M6ZL-H064-IAA-179**

HFO, R-449A, 60Hz, 1-Phase, 115V

Availability: Standard US OEM

Mechanical		Electrical	
Unit Height (in):	11.7	Max Fuse Size:	15
Unit Length (in):	16.6	Min Circuit Ampacity:	10.7
Unit Width (in):	14.2	Compressor:	RFT22C1E-IAA-102
Ship Weight (lbs):	51.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	54.5
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.25 SWEAT	Compressor RLA	7.9
Suction Connection Size (in)/Type:	0.5 SWEAT	UL:	Recognized
Discharge Line Size(in):	0.25	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE2
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	15	Fan Motor Quantity:	1

**Performance**

Release Date:	03-May-2017	Return Gas Temp. (°F):	40
Compressor:	RFT22C1E-IAA-102 x 1	Subcooling (°F):	5
Performance No:	11306	Air Flow Rate (CFM):	300

**90 °F Ambient Air Temperature**

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-30	1,160	103.3	13.3	2.9
-25	1,350	104.2	14.2	3.2
-20	1,570	105.3	15.3	3.4

-15	1,840	106.6	16.6	3.7
-10	2,140	108.1	18.1	4.0
-5	2,470	109.8	19.8	4.3
0	2,830	111.5	21.5	4.6
5	3,220	113.4	23.4	4.9
10	3,630	115.4	25.4	5.2