HYDRONIC SWITCHING RELAYS

Erie

Boiler Boss® Switching Relays

FEATURES:

- Simplified wiring and universal compatibility make installation easy.
- UL listed.
- Quick connect terminals for easy installation.
- Plug-in, pull-out relays with sealed contacts for reliability and service ease.
- Compatible with programmable or non-programmable thermostats.
- Enhances thermostat reliability by providing fully isolated 24 volt power supply



WITHOUT PRIORITY

# Zones	Max Combined Load	24 VAC Transformer	Dry Contacts	Auxiliary Relay	Field Replaceable Parts	ltem#
1	7.2 amps	10 VA	5, 6NO, 6NC	1 SPST	Relay and transformer	SR100

Honeywell

Hydronic Switching Relays

FEATURES

Voltage: Coil Voltage:

SPECIFICATIONS

Relay Coil Current:

- Provide intermediate switching of a line voltage device from a low voltage controller.
- Integral transformer provides low voltage power for control circuit.

120

40 amp

24

4	/	
	Honeywell	\mathbb{D}

		Control			
Application	Switch Action	Circuit	Mfr#	ltem#	Reman#
For switching one line voltage load.	SPST	3-wire	RA19A1006		R510-10R
For switching one line voltage load.	SPST	2-wire	RA89A1074	R510-15	R510-15R
For switching two line voltage loads having a common power source.	DPST: 1 pole line voltage, 1 low voltage or millivoltage.	2-wire	RA832A1066	R520-26	R520-26R
Provides DPST switching for hot water zone control systems or SPST control of two separate loads	· · · · · · · · · · · · · · · · · · ·	2-wire	R845A1030	R520-32	R520-32R

NOTE: Remanufactured products available only on exchange for similar defective units.

