HYDRONIC SWITCHING RELAYS

White-Rodgers

Hydronic Switching Relays

For switching line voltage loads such as circulator motors and

blower motors.

Voltage: 120V, Coil Voltage: 24V



WHITE-RODGERS

Switching Action	Control Circuit	Mfr#	Item#	Reman#
SPST	2-wire	809A-189	R510-44	R510-44R

Honeywell

Remanufactured Hydronic Switching Relays

Provide intermediate switching of a line voltage device from

a low voltage controller.

Application	Voltage (50/60 Hz)	Switch Action	Control Circuit	Coil Voltage	Relay Coil Current	Mfr#	Reman#
For 24V thermostat control of line voltage devices.	24 VAC	DPST	3-wire	24 VAC		R132A	R520-20R
For 24V thermostat control of line voltage devices.	120 VAC	DPST	2 or3 wire	24 VAC	0.35A	R182C1051	R530R

Argo

Universal Replacement Hydronic Switching Relays

For control of line voltage loads with a low voltage circuit.

FEATURES:

- Standardized replacement features.
- Interchangeable plug-in/plug-out relay.
- UL listed. Quick-connect terminals.

Anco	6
Ance	 AR822

Transformer Voltage:	120V @ 60 Hz, 15 VA.
Thermostat Current:	18 amps

Single Phase Switch Action	Single Phase Motor Rating @ 120 Vac	Motor Rating @ 240 Vac	Replaces	Transformer Voltage	Thermostat Current	Mfr#	ltem#
DPDT	10 amp, 1/3 HP	10 amp, 1/2 HP	American Stabilis MR-1000	120v @ 60 Hz, 15 VA	.18 amps	AR822	R512-10

NOTE: Remanufactured products available only on exchange for similar defective units.



4

