

# PILOT RELAYS: 10–15 AMPS

## T STYLE PILOT RELAYS

Product Selection Guide. For full product information, see our website.

MODEL #	UL	COIL VOLTAGE		RELAY CONTACTS	CONTACT RATINGS			HIGH/LOW SEPARATION	OVERRIDE SWITCH	HOUSING STYLE *	SHIPPING WEIGHT
		AC/DC	AC		RESISTIVE	MOTOR	PILOT DUTY				
RIBTU1C	•	10-30	120	1 SPDT	10 A @ 277 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 240-277 Vac	•		C	0.568 lb.
RIBTH1C	•	10-30	208-277	1 SPDT	10 A @ 277 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 240-277 Vac	•		C	0.620 lb.
RIBTU2C	•	10-30	120	2 SPDT	10 A @ 277 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 240-277 Vac	•		C	0.695 lb.
RIBTH2C	•	10-30	208-277	2 SPDT	10 A @ 277 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 240-277 Vac	•		C	0.705 lb.
RIBU1CW	•	10-30	120	1 SPDT	15 A @ 150 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 240-277 Vac	•		C	0.550 lb.
RIBH1CW	•	10-30	208-277	1 SPDT	15 A @ 150 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 240-277 Vac	•		C	0.553 lb.
RIBTU1S	•	10-30	120	1 SPST	10 A @ 277 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 277 Vac	•	1	C	0.573 lb.
RIBTH1S	•	10-30	208-277	1 SPST	10 A @ 277 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 277 Vac	•	1	C	0.652 lb.
RIBTU1SC	•	10-30	120	1 SPDT	10 A @ 277 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 277 Vac	•	2 +	C	0.690 lb.
RIBTH1SC	•	10-30	208-277	1 SPDT	10 A @ 277 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 277 Vac	•	2 +	C	0.661 lb.
RIBT2401D	•	24	120	1 DPDT	10 A @ 277 Vac	1/2 HP @ 120-240 Vac (N/O)	B300	•		C	0.609 lb.

RELAYS

## TRACK MOUNT PILOT RELAYS

Product Selection Guide. For full product information, see our website.

MODEL #	UL	COIL VOLTAGE		RELAY CONTACTS	CONTACT RATINGS			OVERRIDE SWITCH	TRACK MOUNT ^	SHIPPING WEIGHT
		AC/DC	AC		RESISTIVE	MOTOR	PILOT DUTY			
RIBRL1C	• 1	10-30		1 SPDT	10 A @ 277 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 240/277 Vac		DIN Rail	0.184 lb.
RIBRL1S	• 1	10-30		1 SPDT	10 A @ 277 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 240/277 Vac	1 #	DIN Rail	0.194 lb.
RIBR24D	• 1	24		1 DPDT	10 A @ 277 Vac	1/2 HP @ 120-240 Vac (N/O)	B300		DIN Rail	0.285 lb.
RIBR24SD	• 1	24		1 DPDT	10 A @ 277 Vac	1/2 HP @ 120-240 Vac (N/O)	B300	1 #	DIN Rail	0.285 lb.
RIBAN12C	• 2	12		1 SPDT	10 A @ 277 Vac	1 HP @ 250 Vac	C300		MT212 Series & DIN Rail	0.178 lb.
RIBAN24C	• 2	24		1 SPDT	10 A @ 277 Vac	1 HP @ 250 Vac	C300		MT212 Series & DIN Rail	0.180 lb.
RIBM12C	•	12		1 SPDT	15 A @ 125 Vac	1 HP @ 250 Vac	C300		MT4 Series	0.111 lb.
RIBM12S	•	12		1 SPST	15 A @ 125 Vac	1 HP @ 250 Vac	C300	1	MT4 Series	0.127 lb.
RIBM24C	•	24		1 SPDT	15 A @ 125 Vac	1 HP @ 250 Vac	C300		MT4 Series	0.110 lb.
RIBM24S	•	24		1 SPST	15 A @ 125 Vac	1 HP @ 250 Vac	C300	1	MT4 Series	0.129 lb.
RIBM2401D	•	24	120	1 DPDT	10 A @ 277 Vac	1/2 HP @ 120/240 Vac (N/O)	B300		MT4 Series	0.160 lb.
RIBM2402D	•	24	208-277	1 DPDT	10 A @ 277 Vac	1/2 HP @ 120/240 Vac (N/O)	B300		MT4 Series	0.172 lb.
RIBMU1C	•	10-30	120	1 SPDT	15 A @ 150 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 240-277 Vac		MT4 Series	0.134 lb.
RIBMH1C	•	10-30	208-277	1 SPDT	15 A @ 150 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 240-277 Vac		MT4 Series	0.143 lb.
RIBMU1S	•	10-30	120	1 SPST	15 A @ 150 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 277 Vac	1	MT4 Series	0.150 lb.
RIBMH1S	•	10-30	208-277	1 SPST	15 A @ 150 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 277 Vac	1	MT4 Series	0.190 lb.
RIBMU2C	•	10-30	120	2 SPDT	15 A @ 150 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 240-277 Vac		MT4 Series	0.249 lb.
RIBM2C	•	10-30	208-277	2 SPDT	15 A @ 150 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 240-277 Vac		MT4 Series	0.348 lb.
RIBMU1SM-250	•	10-30	120	1 SPST	15 A @ 125 Vac	1/3 HP @ 120-240 Vac (N/O)	345 VA @ 120/240 Vac (N/O)	1+monitor	MT4 Series	0.218 lb.
RIBMH1SM-250	•	10-30	208-277	1 SPST	15 A @ 125 Vac	1/3 HP @ 120-240 Vac (N/O)	345 VA @ 120/240 Vac (N/O)	1+monitor	MT4 Series	0.259 lb.
RIBMU1SC	•	10-30	120	1 SPDT	15 A @ 150 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 277 Vac	2 3	MT4 Series	0.178 lb.
RIBMH1SC	•	10-30	208-277	1 SPDT	15 A @ 150 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 277 Vac	2 3	MT4 Series	0.227 lb.
RIBM12C	•	12		1 SPDT	15 A @ 125 Vac	1 HP @ 250 Vac	C300		MT212 Series	0.087 lb.
RIBM12S	•	12		1 SPST	15 A @ 125 Vac	1 HP @ 250 Vac	C300	1	MT212 Series	0.103 lb.
RIBM24C	•	24		1 SPDT	15 A @ 125 Vac	1 HP @ 250 Vac	C300		MT212 Series	0.087 lb.
RIBM24S	•	24		1 SPST	15 A @ 125 Vac	1 HP @ 250 Vac	C300	1	MT212 Series	0.107 lb.
RIBM24S-J	•	24		1 SPST	15 A @ 125 Vac	1 HP @ 250 Vac	C300	1	MT212 Series	0.120 lb.
RIBM24C-4T	•	24		4 SPDT	15 A @ 125 Vac	1 HP @ 250 Vac	C300		MT212-6 Included	0.454 lb.
RIBM24S-4T	•	24		4 SPST	15 A @ 125 Vac	1 HP @ 250 Vac	C300	4	MT212-6 Included	0.550 lb.
RIBM2401D	•	24	120	1 DPDT	10 A @ 277 Vac	1/2 HP @ 120/240 Vac (N/O)	B300		MT212 Series	0.132 lb.
RIBMNU1C	•	10-30	120	1 SPDT	15 A @ 150 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 240-277 Vac		MT212 Series	0.136 lb.
RIBMNH1C	•	10-30	208-277	1 SPDT	15 A @ 150 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 240-277 Vac		MT212 Series	0.141 lb.
RIBMNU1S	•	10-30	120	1 SPST	15 A @ 150 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 277 Vac	1	MT212 Series	0.177 lb.
RIBMNH1S	•	10-30	208-277	1 SPST	15 A @ 150 Vac	1/3 HP @ 120-240 Vac (N/O)	480 VA @ 277 Vac	1	MT212 Series	0.221 lb.
RIBMNU1SM-250	•	10-30	120	1 SPST	15 A @ 125 Vac	1/3 HP @ 120-240 Vac (N/O)	345 VA @ 120/240 Vac (N/O)	1+monitor	MT212 Series	0.263 lb.
RIBMNH1SM-250	•	10-30	208-277	1 SPST	15 A @ 125 Vac	1/3 HP @ 120-240 Vac (N/O)	345 VA @ 120/240 Vac (N/O)	1+monitor	MT212 Series	0.248 lb.

UL = UL Listed : UL916 Energy Management, UL864 Fire ; USA & Canada

UL 1 = UL Listed : UL916 Energy Management ; USA & Canada

UL 2 = UL Listed : UL508 only ; USA & Canada

+ = SPDT with override requires 2 switches

\* = See Housing Guide on pages 86-87

^ = Track mount sold separately

# = Coil side relay override (requires unit to be powered)

For full product information, see data sheets on website. Shipping weights are approximate and may change due to packaging options.