

# 5-5/8" Diameter Double Shaft Fan/Blower Motors

## Room Air Conditioners - Fan Coils - Blowers

### Features:

- Auto Protector
- Sleeve Bearing
- CCWLE Rotation
- Continuous Air Over
- Energy Efficient S
- PSC
- 60 HZ
- Length Adapter and 2-1/4" - 2-1/2" Res. Rings\*\*
- 40° C Ambient
- 1/2" Dia. - Double Shaft
- Semi-enclosed Construction
- 48 Frame (5-5/8" Dia.)
- 36" Leads (30" Ground)



### "CONSERVATIONIST" (CAPACITOR NOT INCLUDED)

HP	RPM	Speeds	Volts	Amps		Stock Number	Alternate	Capacitor	Ring* Type	Dim. Ref.	Conn. Dia.	Notes
				Rated	Max.							
1/8	1075	3	115	2.0	2.7	RAL1006		5/370V	D	1	11	S
1/8	1075	3	208-230	.75	.9	RA1006		5/370V	D	1	11	S
1/6	1075	3	115	2.2	3.1	RAL1016		5/370V	D	2	12	S
1/6	1075	3	208-230	.95	1.2	RA1016		5/370V	D	1	11	S
1/6	1075	3	208-230	.96	1.1	SA1016		5/370V	**	1	11	1
1/6	1075	3	277	.8	.9	7RA1016		5/370V	D	3	12	S
1/4	1625	3	115	3.4	5.0	RAL1024		5/370V	D	4	13	S
1/4	1625	3	208-230	1.9	2.5	RA1024		5/370V	D	4	13	S
1/4	1075	3	115	3.4	4.4	RAL1026		5/370V	D	5	14	S
1/4	1075	3	208-230	1.5	1.9	RA1026		5/370V	D	6	14	S
1/4	1075	3	208-230	1.5	1.9	SA1026		5/370V	**	6	14	S
1/4	1075	3	277	1.3	1.6	7RA1026		5/370V	D	7	15	S
1/3	1625	3	115	4.0	5.6	RAL1034		5/370V	D	8	15	S
1/3	1625	3	208-230	2.0	2.8	RA1034		5/370V	D	8	15	S
1/3	1075	3	115	5.0	6.8	RAL1036		5/370V	D	9	17	S
1/3	1075	3	208-230	1.9	2.6	RA1036		5/370V	D	10	15	S
1/3	1075	3	208-230	2.2	2.4	SA1036VI		5/370V	**	11	15	S
1/3	1075	3	277	1.9	2.1	7RA1036		7.5/370V	D	12	16	S
1/2	1625	3	115	6.0	10.0	RAL1054		5/370V	D	13	17	S
1/2	1625	3	208-230	3.2	4.2	RA1054		5/370V	D	13	17	S
1/2	1075	3	115	5.2	7.6	RAL1056		10/370V	D	14	20	S
1/2	1075	3	208-230	2.7	3.4	RA1056		7.5/370V	D	13	18	S
1/2	1075	3	208-230	2.7	3.4	SA1056		7.5/370V	**	13	18	S
1/2	1075	3	277	2.2	3.2	7RA1056		10/370V	D	15	20	S
3/4	1625	3	208-230	3.8	5.0	RA1074		7.5/370V	D	16	20	S
3/4	1075	3	115	8.2	9.0	RAL1076		15/370V	D	14	19	S
3/4	1075	3	208-230	3.6	5.0	RA1076		7.5/370V	D	14	19	S

### Notes:

- Item to be discontinued when stock is depleted
- \*For ring type see page 155  
 \*\*SAmodels have extended thru bolts, no length adapter or hubs

### Approximate Dimensions

Ref.	BM	C	N	N1
1	3.74	20	8.26	8
2	3.86	20	8.14	8
3	3.86	20	8.02	8.12
4	4.36	20	7.64	8
5	4.24	20	7.76	8
6	4.11	20	7.89	8
7	3.99	20	7.89	8.12
8	4.61	20	7.39	8
9	4.86	20	7.89	7.25
10	4.61	20	8.14	7.25
11	4.11	20	7.95	7.94
12	4.61	20	7.64	7.75
13	5.11	20	7.64	7.25
14	5.36	20	7.39	7.25
15	5.36	20	7.26	7.38
16	5.61	20	7.14	7.25

Minimum R = BM + 3/4"  
 Maximum R = BM + 2"

