SHARKBITE® CATALOG



SHARKBITE THE MARK OF QUALITY





LEAD-FREE/SAFETY*

All SharkBite® fittings are made of Lead Free DZR brass and exceed ASSE 1061 Section 1V, 4.1 Materials-Dezincification (DZR)-ISO 6509 standards.

*Reference Page 26 for additional information.

VERSATILE

SharkBite fittings have the versatility to transition from Copper, PEX, CPVC, PE-RT, HDPE, Polybutylene and PVC.



PROVEN AND GUARANTEED

SharkBite's quality and performance is field-proven with more than 550 million connections. SharkBite owns the entire manufacturing process, from raw brass to finished product, making SharkBite the only push-to-connect brand that can ensure a clean, leak-free connection.



NO TOOLS

No glue, solder, clamps or unions required when using SharkBite fittings, providing a quick and efficient application that saves installers time, labor, and money.



FLEXIBILITY

SharkBite fittings can be rotated even after assembly allowing for easier installation in tight places.



BEHIND-THE-WALL

SharkBite fittings are approved to be used underground and behind walls without access panels.

CERTIFICATIONS

- Fittings are certified to 200°F (93°C) max and 200 psi max
- Design certified to NSF/ANSI 61 and ASSE 1061 product standard for use in potable water and hydronic heating water distribution

TABLE OF CONTENTS

SECTION 1: THE SHARKBITE CONNECTION SYSTEM	3
1-A: Core Fittings	3
1-B: Radiant Fittings	8
1-C: Transition Fittings	8
1-D: Fire Fittings	9
1-E: Flex Hoses	9
1-F: Stops & Fixture Supply Fittings	10
1-G: Additional Products	11
1-H: Kits	12
1-I: Tools	13
SECTION 2: SHARKBITE VALVES	14
2-A: Pressure Regulating Valves	14
2-B: Thermostatic Mixing Valves	14
2-C: Ball Valves	15
2-D: PVC Ball Valves	15
2-E: Check Valves	15
2-F: Temperature & Pressure Relief Valves	16
2-G: General Supply Valves	16
SECTION 3: SHARKBITE PEX BARB FITTINGS	10
3-A: PEX Barb Core Fittings	16
3-B: PEX Barb Transition Fittings	19
3-C: PEX Barb Poly Alloy Fittings	20
3-D: PEX Barb Fire Fittings	21
3-E: PEX Barb Stops & Fixture Supply Fittings	21
3-F: PEX Barb Additional Products	21
3-G: PEX Barb Accessories	22
3-H: PEX Barb Tools	23
BENEFITS OF SHARKBITE PEX	2
MADE IN THE USA	2
SECTION 4: SHARKBITE PEX PIPE	2
4-A: Potable Water PEX Pipe	26
4-B: Special Application PEX Pipe	27
MADE IN THE USA	2





VISIT US ONLINE OR ON THE GO

sharkbite.com

SHARKBITE **CONNECTION SYSTEM**

REDEFINING EFFICIENCY

For more than 20 years and with over 250 million fittings installed, SharkBite has been at the forefront of innovating solutions for helping the plumbing trade improve efficiency with enhanced jobsite performance. Being a leader through continuous innovation and providing solutions that address the challenges that plumbing professionals face every day is who we are. Whether you are repairing a water line, installing a water heater, remodeling a home or plumbing a system in a new construction job, SharkBite provides proven solutions that save time, reduce cost, and have the versatility to overcome the most difficult situations.

TOTAL SYSTEM

The SharkBite system includes a wide range of plumbing fittings. valves, PEX pipe, outlet boxes and other plumbing accessories, making it the only system that is a total end-to-end plumbing solution from meter to fixture. This means compatibility and peace of mind quality that is backed by a single manufacturer.

www.sharkbite.com

All SharkBite fittings are made of Lead Free DZR brass and exceed ASSE 1061 Section 1V, 4.1 Materials-Dezincification (DZR) - ISO 6509 standards.





PRODUCT DESCRIPTION PART NUMBER QTY/BAG

SECTION 1: THE SHARKBITE CONNECTION SYSTEM

1-A: CORE FITTINGS			
COU	PLINGS		
1/4"	(3/8" OD) X 1/4" (3/8" OD)	U004LF	6
3/8"	(1/2" OD) X 3/8" (1/2" OD)	U006LF	6
1/2"	X 1/2"	U008LF	12
3/4"	X 3/4"	U016LF	12
1" X 1	п	U020LF	6
æ	1-1/4" X 1-1/4" (For PEX applications, stiffeners are sold separately)	UXL0135	1
LARGE DIAMETER	1-1/2" X 1-1/2" (For PEX applications, stiffeners are sold separately)	UXL0141	1
_ 5	2" X 2" (For PEX applications, stiffeners are sold separately)	UXL0154	1
RED	UCING COUPLINGS		
1/4"	(3/8" OD) X 1/2"	U050LF	6
3/8"	(1/2" OD) X 1/2"	U009LF	6
3/4"	X 1/2"	U058LF	12
1" X 3	3/4"	U060LF	6
	1-1/4" X 1" (For PEX applications, stiffeners are sold separately)	UXL013528	1
LARGE	1-1/2" X 1" (For PEX applications, stiffeners are sold separately)	UXL014128	1
DIAM	1-1/2" X 1-1/4" (For PEX applications, stiffeners are sold separately)	UXL014135	1
	2" X 1-1/2" (For PEX applications, stiffeners are sold separately)	UXL015441	1



SharkBite slip couplings and tees are ideal for repairing and tapping into existing rigid pipe lines. The slip feature ensures the pipe is fully engaged into the fitting when the pipe is in a fixed position. The slip end is only suitable for use with Copper and CPVC pipe.

SLIP COUPLINGS (SLIP END ONLY SUITABLE FOR COPPER AND CPVC)

Slip couplings are the most efficient way to repair a burst pipe or leak. Slip fittings simply repair by doing the job that two couplings and extra pipe used to do. Only one end of the coupling has as stop, allowing the opposite end to slide freely over the end of a pipe. The fittings can then be released with a disconnect tool and slid back onto the other end of the pipe for a successful connection and leak repair.

1/2"	X 1/2"	U3008LF	3
3/4"	X 3/4"	U3016LF	3
1" X 1	н	U3020LF	1
æ	1-1/4" X 1-1/4" (For PEX applications, stiffeners are sold separately)	UXL0635	1
LARGE DIAMETER	1-1/2" X 1-1/2" (For PEX applications, stiffeners are sold separately)	UXL0641	1
5	2" X 2" (For PEX applications, stiffeners are sold separately)	UXL0654	1
FEMALE CONNECTORS			
1/4"	(3/8" OD) X 1/2" FNPT Reducing	U066LF	6
3/8"	(1/2" OD) X 1/2" FNPT Reducing	U070LF	6
1/2"	X 1/2" FNPT Straight	U072LF	12

HOW TO INSTALL SHARKBITE PUSH-TO-CONNECT PRODUCTS



CUT:

Cut the pipe square removing rough edges and debris. Mark the pipe to the correct insertion depth.



PUSH

Push pipe and fitting together up to the depth mark.



DONE.



Using the disconnect clip, fittings can be easily changed, removed and reused.











	PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG
æ	1-1/4" X 1-1/4" (For PEX applications, stiffeners are sold separately)	UXL0535	1
DIAMETER	1-1/2" X 1-1/2" (For PEX applications, stiffeners are sold separately)	UXL0541	1
Ξ	2" X 2" (For PEX applications, stiffeners are sold separately)	UXL0554	1
5°	STREET ELBOWS		
/2"	x 1/2" CTS Tail Adapter (CTS end inserts into any 1/2" SB fitting)	U615LF	6
/4":	x 3/4" CTS Tail Adapter (CTS end inserts into any 3/4" SB fitting)	U620LF	6
~	1-1/4" X 1-1/4" (For PEX applications, stiffeners are sold separately)	UXL0735	1
DIAMETER	1-1/2" X 1-1/2" (For PEX applications, stiffeners are sold separately)	UXL0741	1
_	2" X 2" (For PEX applications, stiffeners are sold separately)	UXL0754	1
M	IALE ELBOWS		
2"	X 1/2" FNPT	U308LF	6
4" .	X 3/4" FNPT	U314LF	3
ΑL	LE ELBOWS		
2"	X 1/2" MNPT	U280LF	6
4" .	X 3/4" MNPT	U286LF	6
D	UCING ELBOWS		
2"	X 3/8" (1/2" OD)	U272LF	12
1"	X 1/2"	U274LF	6
(3	3/4"	U278LF	3
0	DP-EAR ELBOWS		
"	(1/2" OD) X 1/2" FNPT	U332LF	6
" .	X 1/2"	U249LF	12
	X 1/2" FNPT	U334LF	6
	X 3/4" FNPT	U340LF	6
I	EAR EAR ELBOWS		
	X 1/2" Hy-Ear	U335LF	6
	HWASHER ELBOWS		
	(3/8" OD) X 3/8" MNPT	U276LF	6
	(3/8" OD) X 3/4" Garden Hose Nut	U2276LF	6
	X 3/8" MNPT	U281LF	6
ES			
	(3/8" OD) X 1/4" (3/8" OD) X 1/4" (3/8" OD)	U358LF	6
	(1/2" OD) X 3/8" (1/2" OD) X 3/8" (1/2" OD)	U360LF	6
	X 1/2" X 1/2"	U362LF	12
	X 3/4" X 3/4"	U370LF	6
1	" X " 	U374LF	3
DIAMEIEK	1-1/4" X 1-1/4" X 1-1/4"	UXL0835	1
	1-1/2" X 1-1/2" X 1-1/2"	UXL0841	1
_	7 X 7 X 7	UXL0854	1
	UCING TEES		
	(1/2" OD) X 3/8" (1/2" OD) X 1/2"	U364LF	6
	X 1/2" X 1/4" (3/8" 0D)	U359LF	6
2"	X 1/2" X 3/8" (1/2" OD)	U363LF	6



	PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG
3/4"	" X 1/2" X 1/2"	U454LF	6
3/4"	" X 3/4" X 1/2"	U412LF	6
3/4"	" X 1/2" X 3/4"	U444LF	6
1" X	1" X 3/4"	U416LF	3
	1-1/4" x 1/2" x 1-1/4"	UXL08351635	1
	1-1/4" x 3/4" x 1/2"	UXL08352216	1
	1 -1/4" x 3/4" x 3/4"	UXL08352222	1
	1-1/4" x 3/4" x 1"	UXL08352228	1
	1-1/4" x 3/4" x 1-1/4"	UXL08352235	1
	1-1/4" x 1" x 1/2"	UXL08352816	1
	1-1/4" x 1" x 3/4"	UXL08352822	1
	1-1/4" x 1" x 1"	UXL08352828	1
	1-1/4" X 1-1/4" X 1/2"	UXL08353516	1
	1-1/4" X 1-1/4" X 3/4"	UXL08353522	l
	1-1/4" X 1-1/4" X 1"	UXL08353528	1
	1-1/2" X 1-1/2" X 3/4"	UXL08414122	1
	1-1/2" x 1" x 3/4"	UXL08412822	1
	1-1/2" x 1" x 1"	UXL08412828	1
~	1-1/2" x 1" x 1-1/2"	UXL08412841	1
LARGE DIAMETER	1-1/2" x 1-1/4" x 3/4"	UXL08413522	1
35 25 25	1-1/2" x 1-1/4" x 1"	UXL08413528	1
Š	1-1/2" x 1-1/4" x 1-1/4"	UXL08413535	1
	1-1/2" x 1-1/2" x 1/2"	UXL08414116	1
	1-1/2" X 1-1/2" X 1"	UXL08414128	1
	1-1/2" X 1-1/2" X 1-1/4"	UXL08414135	1
	2" x 1-1/4" x 1-1/4"	UXL08543535	1
	2" x 1-1/2" x 3/4"	UXL08544122	1
	2" x 1-1/2" x 1"	UXL08544128	1
	2" x 1-1/2" x 1-1/4"	UXL08544135	1
	2" x 1-1/2" x 1-1/2"	UXL08544141	1
	2" x 1-1/2" x 2"	UXL08544154	1
	2" x 2" x 1/2"	UXL08545416	1
	2" x 2" x 3/4"	UXL08545422	1
	2" X 2" X 1"	UXL08545428	1
	2" X 2" X 1-1/4"	UXL08545435	1
	2" X 2" X 1-1/2"	UXL08545441	1
FEA	MALE CENTER TEES		
3/4"	x 3/4" x 3/4" (Utilizes a U766LF thread adapter)	U462LF	3
1" x	1" x 1" (Utilizes a U772LF thread adapter)	U464LF	3
	· · · · · · · · · · · · · · · · · · ·	0.0.0	





	PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG
	1-1/4" x 1-1/4" x 1/2" FNPT Branch Tee	UXL10353515	1
	1-1/4" x 1-1/4" x 3/4" FNPT Branch Tee	UXL10353520	1
	1-1/4" x 1-1/4" x 1" FNPT Branch Tee	UXL10353525	1
ETER	1-1/2" x 1-1/2" x 1/2" FNPT Branch Tee	UXL10414115	1
LARGE DIAMETER	1-1/2" x 1-1/2" x 3/4" FNPT Branch Tee	UXL10414120	1
LARGE	1-1/2" x 1-1/2" x 1" FNPT Branch Tee	UXL10414125	1
	2" x 2" x 1/2" FNPT Branch Tee	UXL10545415	1
	2" x 2" x 3/4" FNPT Branch Tee	UXL10545420	1
	2" x 2" x 1" FNPT Branch Tee	UXL10545425	1
FEM	ALE CENTER SLIP TEES (SLIP END ONLY SUITABLE FOR COPPER AN	D CPVC)	
1/2"	X 1/2" X 1/2" FNPT	U3482LF	3
3/4"	X 3/4" X 3/4" FNPT	U3486LF	3
SLIP	TEES (SLIP END ONLY SUITABLE FOR COPPER AND CPVC)		
1/2"	X 1/2" X 1/2"	U3362LF	3
3/4"	X 3/4" X 3/4"	U3370LF	3
æ	1-1/4" X 1-1/4" (For PEX applications, stiffeners are sold separately)	UXL0335	1
LARGE DIAMETER	1-1/2" X 1-1/2" (For PEX applications, stiffeners are sold separately)	UXL0341	1
5	2" X 2" (For PEX applications, stiffeners are sold separately)	UXL0354	l
SER	VICE SLIP TEE ADAPTER (SLIP END ONLY SUITABLE FOR COPPER AN	ID CPVC)	
1/2"	X 1/2" X 1/2" CTS Tail Adapter Service Line Tee (CTS end inserts into any 1/2" SB fitting)	U4482LF	6
END	CAPS		
3/8"	(1/2" OD)	U512LF	6
1/2"		U514LF	12
3/4"		U518LF	6
1"		U520LF	6
#	1-1/4" (For PEX applications, stiffeners are sold separately)	UXL0435	l
LARGE DIAMETER	1-1/2" (For PEX applications, stiffeners are sold separately)	UXL0441	1
^	2" (For PEX applications, stiffeners are sold separately)	UXL0454	1
	ING REDUCERS (USE TO CONNECT TO SMALLER PIPE SIZES)		
3/8"	(1/2" OD) X 1/2" CTS (CTS end inserts into any 1/2" SB fitting)	U719LF	6
	(1/2" OD) X 3/4" CTS (CTS end inserts into any 3/4" SB fitting)	U721LF	6
	X 1" CTS (CTS end inserts into any 1" SB fitting)	U722LF	6
3/4"	X 1" CTS (CTS end inserts into any 1" SB fitting)	U724LF	6
	1-1/4" x 1/2"	UXL123516	1
	1-1/4" x 3/4"	UXL123522	1
	1-1/4" x 1"	UXL123528	1
	1-1/2" x 1/2"	UXL124116	1
푎	1-1/2" x 3/4"	UXL124122	1
LARGE DIAMETER	1-1/2" x 1"	UXL124128	1
ARGE L	1-1/2" x 1-1/4"	UXL124135	1
3	2" x 1/2"	UXL125416	1
	2" x 3/4"	UXL125422	1
	2" x 1"	UXL125428	1
	2" x 1-1/4"	UXL125435	1
	2" x 1-1/2"	UXL125441	1





PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG
WATER SOFTENER FITTING		
3/4" X 1" FIP	U086LF	12



















1-C: TRANSITION FITTINGS				
POLYBUTYLENE TRANSITION COUPLINGS				
1/2" PB X 1/2" CTS	U4008LF	6		
3/4" PB X 3/4" CTS	U4016LF	6		
PVC TRANSITION COUPLINGS				
SharkBite PVC transition fittings connect Copper, PEX, CPVC, or PE-RT pipe to PVC pipe (Sch. 4 unions, or glue.	0, 80 and 120) without solder	ing, damps,		
1/2" CTS X 1/2" PVC	UIP4008	6		
3/4" CTS X 3/4" PVC	UIP4016	6		
1" CTS X 1" PVC	UIP4020	3		
PVC TRANSITION SLIP TEES				
1/2" CTS X 1/2" CTS X 1/2" PVC	UIP363	3		
1/2" PVC X 1/2" PVC X 1/2" CTS	UIP364	3		
3/4" CTS X 3/4" CTS X 3/4" PVC	UIP371	3		
3/4" PVC X 3/4" PVC X 3/4" CTS	UIP372	3		
1" CTS X 1" CTS X 1" PVC	UIP375	3		
1" PVC X 1" PVC X 1" CTS	UIP376	3		
PVC SLIP COUPLINGS				
1/2" PVC X 1/2" PVC	UIP3008	3		
3/4" PVC X 3/4" PVC	UIP3016	3		
1" PVC X 1" PVC	UIP3020	2		
PVC MALE CONNECTORS				
1/2" PVC X 1/2" MNPT	UIP120	6		
3/4" PVC X 3/4" MNPT	UIP134	6		
1" PVC X 1" MNPT	UIP140	3		
PVC CAPS	<u> </u>			
1/2"	UIP514	12		
3/4"	UIP518	12		
1"	UIP520	12		
PVC DEPTH GAUGE AND DISCONNECT CLIPS				
1/2"	UIP710	12		
3/4"	UIP712	12		
1"	UIP714	6		

PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG	
1-D: FIRE FITTINGS ONLY SUITABLE FOR USE WITH SHARKBITE PEX PIPE			
FIRE HORIZONTAL TEES			
3/4" x 3/4" x 1/2" FNPT	UF12128H	3	
1" x 3/4" x 1/2" FNPT	UF16128H	3	
1" x 1" x 1/2" FNPT	UF16168H	3	
FIRE VERTICAL TEES			
3/4" x 3/4" x 1/2" FNPT	UF12128V	3	
1" x 3/4" x 1/2" FNPT	UF16128V	3	
1" x 1" x 1/2" FNPT	UF16168V	3	
FIRE DROP-EAR ELBOWS			
3/4" x 1/2" FNPT	UF128U	3	
1" X 1/2" FNPT	UF168U	3	
FIRE THREADED FEMALE ADAPTERS		^	
3/4" X 1/2" FNPT	UF128S	3	
FIRE ANGLED ADAPTERS		•	
3/4" X 3/4" X 1/2" FNPT	UF12128A	3	
FIRE FEMALE ELBOWS			
3/4" X 1/2" FNPT Left	UF128L	3	
3/4" X 1/2" FNPT Right	UF128R	3	
1" X 1/2" FNPT Left	UF168L	3	
1" X 1/2" FNPT Right	UF168R	3	



1-E: FLEX HOSES

The SharkBite flexible connectors are used in residential and commercial applications to easily connect pipe in any combination. The SharkBite fitting allows the installer to connect to Copper, CPVC and PEX pipe eliminating the need for an additional transition fitting.

STAINLESS STEEL BRAIDED WATER HEATER CONNECTORS

The SharkBite water heater connectors are used in residential and commercial applications to connect the hot and cold supply lines to the water heater. The connectors are available in 12", 15", 18" and 24" lengths (with and without ball valve).

to the water fleater. The conflectors are available in 12, 13, 10 and 24 feights (with and without built valve).			
1/2" X 3/4" FIP, 12"	U3068FLEX12LF	12	
1/2" X 3/4" FIP, 15"	U3068FLEX15LF	12	
1/2" X 3/4" FIP, 18"	U3068FLEX18LF	12	
1/2" X 3/4" FIP, 24"	U3068FLEX24LF	12	
3/4" X 3/4" FIP, 12"	U3088FLEX12LF	12	
3/4" X 3/4" FIP, 15"	U3088FLEX15LF	12	
3/4" X 3/4" FIP, 18"	U3088FLEX18LF	12	
3/4" X 3/4" FIP, 24"	U3088FLEX24LF	12	
STAINLESS STEEL CORRUGATED WATER HEATER CONNEC	TORS		
3/4" X 3/4" FIP, 12"	SS3088FLEX12LF	12	
3/4" X 3/4" FIP, 18"	SS3088FLEX18LF	12	
3/4" X 3/4" FIP, 24"	SS3088FLEX24LF	12	
3/4" x 1" FIP, 24"	SS3086FLEX24LF	6	
1" x 1" FIP, 24"	SS3094FLEX24LF	6	
1" x 3/4" FIP, 24"	SS3096FLEX24LF	6	



PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG	
STAINLESS STEEL BRAIDED WATER HEATER CONNECTORS WITH BALL VA	ALVES		
1/2" X 3/4" FIP, 18"	U3068FLEX18BVLF	12	
3/4" X 3/4" FIP, 18"	U3088FLEX18BVLF	12	
STAINLESS STEEL CORRUGATED WATER HEATER CONNECTORS WITH BA	LL VALVES		
1/2" X 3/4" FIP, 18"	SS3068FLEX18BV	12	
3/4" X 3/4" FIP, 18"	SS3088FLEX18BV	12	
STAINLESS STEEL CORRUGATED WATER HEATER CONNECTORS KIT			
Kit contains one $3/4"$ FIP x $3/4"$ SB x $18"$ hose, one $3/4"$ FIP x $3/4"$ SB ball valve x $18"$ hose, and one $3/4"$ disconnect clip	24680	3	
STAINLESS STEEL BRAIDED WATER COUPLING HOSE			
1/2" X 1/2", 18"	U3008FLEX18LF	12	
3/4" X 3/4", 18"	U3016FLEX18LF	12	
STAINLESS STEEL BRAIDED WATER SOFTENER CONNECTOR			
The SharkBite water softener hose can be used for connection of new water softeners or replacement of existing connectors. The 3/4" SharkBite x 1" FIP swivel nut connectors makes for quick and easy installation.			
3/4" X 1" FIP, 24"	U3086FLEX24LF	6	

1-F: STOPS & FIXTURE SUPPLY FITTINGS


Connecting supply lines to fixtures and appliances using SharkBite stops & fixture supply fittings brings the speed and convenience of push-to-connect connections to the final phase of your plumbing jobs. Regular and chrome plated fittings are now available, including the newest 1/2" X 1/4" (3/8" OD) SharkBite stop valves. Stops in 1/2" X 3/8" or 1/4" compression sizes are also available. With these SharkBite push-to-connect fittings, stop valves and the 5' lengths or 50' coils of 1/4" (3/8" OD) PEX pipe, it's easy to make risers the exact length needed for connecting fixtures and appliances. No more problems with flexible lines that are too long or too short.



ANGLE STOPS		
1/2" X 3/8" Compression	23036-0000LF	12
1/2" X 3/8" Compression Loose Key	24731LF	6
1/2" X 1/4" (3/8" OD)	23048-0000LF	6
1/2" X 1/4" (3/8" OD) Loose Key	24733LF	6
1/2" X 1/4" Compression	23336-0000LF	6
1/2" X 1/2" Compression	23489	6
STRAIGHT STOPS		
1/2" X 3/8" Compression	23037-0000LF	12
1/2" X 3/8" Compression Loose Key	24732LF	6
1/2" X 1/4" (3/8" OD)	23049-0000LF	6
1/2" X 1/4" (3/8" OD) Loose Key	24734LF	6
1/2" X 1/4" Compression	23337-0000LF	6
1/2" X 1/2" Compression	23490	6
TEE STOPS		
1/2" X 1/2" X 1/4" Compression	24983	6
1/2" X 1/2" X 3/8" Compression	24984	6
3/4" X 3/4" X 1/4" Compression	24985	6
3/4" X 3/4" X 3/8" Compression	24986	6
1/2" X 1/2" X 1/4" (3/8" OD)	24987	6
DUAL OUTLET STOP	·	•
1/2" Angle Stop X 3/8" X 3/8" OD Comp Dual Outlet Stop	25558LF	6
	·	•

PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG	
DUAL TEE STOP VALVE ADAPTERS			
Insert onto stub-out then fit any of the eight SharkBite stop valves to create any combination desir	ed.		
1/2" CTS X $1/2$ " CTS X $1/2$ " (CTS ends insert into any $1/2$ " SB fitting. Recommended use with Angle/Straight Stops.)	U782LF	6	
STOP VALVE CONNECTORS			
1/4" (3/8" OD) X 3/8" Compression Stop Valve Connector (Converts 3/8" comp stop to SharkBite)	U3523LF	6	
1/4" (3/8" OD) X 1/4" Compression Nut	U3524LF	6	
STOP VALVE TEE ADAPTERS			
1/4" (3/8" OD) X 1/4" (3/8" OD) X 3/8" Compression	U3358LF	6	
1/4" (3/8" OD) X 1/4" (3/8" OD) X 1/4" (3/8" OD) Tube	U4358LF	6	
FAUCET CONNECTORS			
1/4" (3/8" OD) X 1/2" NPSM	U3525LF	6	
TOILET CONNECTORS			
1/4" (3/8" OD) X 7/8" Ballcock Threads Toilet Connector	U3531LF	6	
1/4" (3/8" OD) X 7/8" Ballcock Threads Toilet Elbow	U3537LF	6	
ANGLE STOP SUPPLY LINES			
1/2" X 7/8" Ballcock Click Seal® Toilet Connector x 12"*	24656	6	
1/2" X 1/2" NPSM ClickSeal® Faucet Connector x 20"*	24657	6	

1-G: ADDITIONAL PRODUCTS MANIFOLDS WITH PUSH-TO-CONNECT BRANCHES Manifolds are traditionally used in PEX systems, but this SharkBite manifold will also allow for easy incorporation into Copper or CPVC systems. Use SharkBite push-to-connect fittings to install these manifolds anywhere in a plumbing system. All manifolds have a 1" trunk with 3/4" tube inlets and outlets and 1/2" push-to-connect ports (2" on center). Manifold Bracket Set (for 1"-1.5" diameter manifolds) 1 25484Z 3/4" x 1/2" Outlet 3-Port Manifold - Open 25552LF 3 3/4" x 1/2" Outlet 3-Port Manifold - Closed 25553LF 3 3/4" x 1/2" Outlet 4-Port Manifold - Open 25554LF 3 3/4" x 1/2" Outlet 4-Port Manifold - Closed 25555LF 3 RADIANT HEATING MANIFOLDS (1" FNPT X 1/2" SHARKBITE PEX LOOPS) 3 Loop 24930 4 Loop 24931 24932 1 5 Loop 1 6 Loop 24933 7 Loop 24934 1 8 Loop 24935 1 9 Loop 24936 1 24937 1 10 Loop 1 11 Loop 24938 24939 1 12 Loop 24940 1 13 Loop SHARKBITE RADIANT MANIFOLD ACTUATORS (4-WIRE, WITH END SWITCH) SharkBite Radiant Manifold Actuator 24963





PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG
WATER HAMMER ARRESTORS		
Provides maintenance-free, continuous protection against water hammer. Can be p connectors allow the arrestor to be installed in seconds, even on wet pipe.	ositioned vertically or horizontally and t	ne SHARKBITE
1/2" Residential	22630LF	1
1/2" Commercial	22631LF	1
3/4" Residential	22632LF	1
1" Commercial	22633LF	1
STUB OUT ELBOWS		
The SharkBite stub-out elbows come with pre-fitted mounting brackets that provide (studs, joists and subfloors) by simply rotating or repositioning the mounting brack		ooden surfaces
1/2" SB X 1/2" Copper Tube 8" Length	U351LFA	6
PRESSURE GAUGES		
1/2" SB Tee with Pressure Gauge	24436	1
3/4" SB Tee with Pressure Gauge	24438	1
3/4" SB Pressure Gauge in Retail Packaging	24438A	5
1" SB Tee with Pressure Gauge	24440	1
1/2" CTS Pressure Gauge (inserts into any 1/2" SB fitting)	24442	1
3/4" CTS Pressure Gauge (inserts into any 3/4" SB fitting)	24444	1
TEMPERATURE GAUGES		
1/2" SB Tee with Temperature Gauge	24437	1
3/4" SB Tee with Temperature Gauge	24439	1
1" SB Tee with Temperature Gauge	24441	1
1/2" CTS Temperature Gauge (inserts into any 1/2" SB fitting)	24443	1
3/4" CTS Temperature Gauge (inserts into any 3/4" SB fitting)	24445	1
PUSH-TO-CONNECT HOME RUN MANIFOLDS		
12 Port with Brass Valves	PM012SB	1
12 I OII WIIII DIU33 VUIVG3		

1-H: KITS				
WATER HEATER INSTALLATION KITS (KITS INCLUDE 2 SHARKBITE CONNECTOR FITTINGS AND A DISCONNECT CLIP)				
1/2" X 3/4" FNPT	22604LF	12		
3/4" X 3/4" FNPT	22441LF	12		
CONTRACTOR KITS (KIT INCLUDES TOOLBOX)				
Kit Contains 2 each (U008LF, U016LF, U058LF, U072LF, U088LF, U120LF, U134LF, U248LF, U256LF) and 1 each (U362LF, U370LF, U514LF, U518LF, U710, U711, U713 and U702)	22486LF	1		
Contractor Tool Box Only	U3001A	1		
FAUCET CONNECTION KIT IN BAGGED PACKAGING (FAUCET KITS COME WITH 2 FAUCET CONNECTORS, 2 ANGLE STOPS, AND 1 COIL OF 10' 1/4" WHITE PEX PIPE)				
Faucet Connector with Angle Stop	25087	3		
Faucet Connector with Straight Stop	25538	3		
TOILET CONNECTION KIT IN BAGGED PACKAGING (TOILET KITS COME WITH 1 TO COIL OF 5' 1/4" WHITE PEX PIPE.)	OILET CONNECTOR, 1 AN	GLE STOP, AND 1		
Toilet Connector with Angle Stop	25088	6		
Toilet Connector with Straight Stop	25539	3		
ICE MAKER CONNECTION KIT IN BAGGED PACKAGING (ICE MAKER KITS COME WITH 1 SERVICE SLIP TEE, 1 ANGLE STOP, 1 VALVE CONNECTOR, 10' 1/4" WHITE PEX PIPE)				
Ice Maker Connector with Angle Stop	25024	1		

PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG	
DISHWASHER INSTALLATION KIT IN BAGGED PACKAGING (DISHWASHER KIT COMES WITH 1 DUAL OUTLET STOP, 1 STOP VALVE CONNECTOR, 1 DISHWASHER ELBOW, 1 GARDEN HOSE NUT)			
Dishwasher Installation Kit	25568	3	
SHOWER/TUB INSTALLATION KIT IN BAGGED PACKAGING			
KIT Contains 2 Drop Ear Elbows, 2 Female Connectors, 2 Female Elbows and 1 Disconnect Clip	25567	3	
WATER FILTER INSTALLATION KIT IN BAGGED PACKAGING (WATER FILTER & CONNECTOR, AND 1 DISCONNECT CLIP)	IT COMES WITH 1 SLIP CO	OUPLING, 1 MALE	
Kit Contains 1 - 3/4" Slip Connector, 1 - 3/4" Male Connector, and 1 - 3/4" Disconnect Clip	25561	6	
Kit Contains 1 - 1" Slip Connector, 1 - 1" Male Connector, and 1 - 1" Disconnect Clip	25562	6	
ICE MAKER OUTLET BOX			
1/2" SB X 1/4" Compression	25096	1	
1/2" SB X 1/4" Compression with Water Hammer Arrestor	25097	1	
WASHING MACHINE OUTLET BOX			
1/2" SB X 3/4" MHT	25098	1	
1/2" SB X 3/4" MHT with Water Hammer Arrestor	25099	1	
FACEPLATE REPLACEMENTS			
Ice Maker Box Replacement Faceplate for 25032, 25033, 25096, 25097	25478	1	
Washing Machine Box Replacement Faceplate for 24763, 25031, 25098, 25099	25464	1	
WASHING MACHINE VALVES			
1/2" X 3/4" MHT Straight Valve	25559LF	6	
1/2" X 3/4" MHT Angle Valve	25560LF	6	

	1-I: T00LS						
DEB	URR & GAUGE TOOLS						
Use fo	Use for 1/4", 3/8", 1/2", 5/8", 3/4" and 1" copper and CPVC pipe U702 1						
LARGE DIAMETER	Use for 1-1/4", 1-1/2", 2"	UXLG03	1				
DISC	ONNECT CLIPS						
1/4"		U706	12				
3/8"		U708	24				
1/2"		U710	24				
5/8"		U3712	24				
3/4"		U712	24				
1"		U714	12				
DISC	ONNECT TONGS						
1/2"		U711	1				
3/4"		U713	1				
1"		U715	1				
DE-N	DE-MOUNT CLIPS						
æ	1-1/4"	UXLDC35	1				
LARGE DIAMETER	1-1/2"	UXLDC41	1				
	2"	UXLDC54	1				






	PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG
LAR	GE DIAMETER PEX STIFFENERS		
æ	1-1/4"	SBTL35	1
LARGE	1-1/2"	SBTL41	1
	2"	SBTL54	1
WR	AP FOR FITTING BURIAL		
10′ x	2" X 0.02" Silicone Wrap	25406	1

SECTION 2: SHARKBITE VALVES

2-A: PRESSURE REGULATING VALVES

The innovative, labor reducing EB45 and the EB25 pressure regulating valves are available with double union and direct SharkBite connectors. The EB45 is factory set at 45 or 60 psi and is adjustable to 10-70 psi. The EB25 is set at 45 psi and features a twist cap with a numerical pressure indicator for easy one-man adjustment.





2-B: THERMOSTATIC MIXING VALVES

Direct or double union SharkBite push-to-connect connectors provide a simplified, time and labor saving installation. Heatguard valves deliver water at a safe 120°F (49°C) or lower from all outlets, while allowing the thermostat to be set at a germ-killing 140°F (60°C) or higher which aids in preventing the growth of legionella bacteria in the water heater. The higher tank temperature means hot water demands can be satisfied longer. Every valve is tested for performance and includes a unique adjuster tool that minimizes tampering with the valve setting. Rugged, simple construction incorporates a precise engineered polymer piston and the latest in thermostatic technology.

HG110-D LEAD FREE (ASSE 1017, 1069, & 1070, CSA B 125.3. DISTRIBUTION AND IN-LIN	IE)	
1/2" HG110-D with Integrated SharkBite Connections and Integral Checks	24548	1
3/4" HG110-D with Integrated SharkBite Connections and Integral Checks	24549	1
1/2" HG110-D with SharkBite Union Connections	24504	1
3/4" HG110-D with SharkBite Union Connections	24505	1
HG160 LEAD FREE (ASSE 1069 & 1070, CSA B 125.3. IN-LINE)		
1/2" HG160 with SharkBite Connections	24529	1
3/4" HG160 with SharkBite Connections	24530	1



PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG
HG110-HX		
3/4" HG110-HX with SharkBite Connections and Integral Checks	24867	1

2-C: BALL VALVES			
BALL VALVES			
1/2" X 1/2"	22222-0000LF	12	
3/4" X 3/4"	22185-0000LF	12	
1" X 1"	22223-0000LF	6	
1-1/4"	UXLBV35	1	
1-1/4 1-1/2"	UXLBV41	1	
2"	UXLBV54	1	
BALL VALVES WITH FNPT CONNECTORS			
1/2" X 1/2" FNPT	22182-0000LF	6	
3/4" X 3/4" FNPT	22186-0000LF	6	
1" X 1" FNPT	22187-0000LF	3	
BALL VALVES WITH DRAIN/VENT			
1/2" x 1/2" x 1/8" NPSM Drain Thread	22304-0000LF	12	
3/4" x 3/4" 1/8" NPSM Drain Thread	22305-0000LF	12	
1" x 1" 1/8" NPSM Drain Thread	22306-0000LF	6	
BALL VALVE WITH DRAIN/VENT AND MOUNTING BRACKET			
1/2" x 1/2" 1/8" NPSM Drain Thread	24615-0000LF	12	
3/4" x 3/4" 1/8" NPSM Drain Thread	24616-0000LF	6	
1" x 1" 1/8" NPSM Drain Thread	24617-0000LF	6	
1/8" NPSM	24377	1	
SLIP BALL VALVE (ONLY SUITABLE FOR COPPER AND CPVC)			
1/2" x 1/2"	24735LF	6	
3/4" x 3/4"	24736LF	6	
1" x 1"	24737LF	3	

2-D: PVC BALL VALVES		
PVC BALL VALVES		
3/4" PVC X 3/4" CTS	25550LF	6
1" PVC X 3/4" CTS	25551LF	6

2-E: CHECK VALVES		
CHECK VALVES		
1/2" X 1/2"	U2008-0000LF	6
3/4" X 3/4"	U2016-0000LF	6
1" X 1"	U2020-0000LF	3
DUAL CHECK VALVES (ASSE 1024 & CSA B64.6)		
3/4" BF1, Dual Check, SharkBite Inlet & Outlet	BF13434SB	1
1" BF1, Dual Check, SharkBite Inlet & Outlet	BF10101SB	1
1" X 3/4" BF5, Dual Check, Meter Swivel Nut Inlet, SharkBite Outlet	BF5M0134SB	1
1-1/4" X 1" BF5, Dual Check, Meter Swivel Nut Inlet, SharkBite Outlet	BF5M1401SB	1





























PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG	
2-F: TEMPERATURE & PRESSURE RELIEF VALVES			
T&P RELIEF VALVES			
3/4" NCLX-5LX with SharkBite Outlet Connection	24609-0150	1	

2-G: GENERAL SUPPLY VALVES		
GATE VALVE WITH DRAIN		
1/2" x 1/2"	24634LF	12
3/4" x 3/4"	24635LF	12
HOSE BIBBS		
1/2" x 3/4" MHT 90 Deg Hose Bibb — Quarter Turn	24620LF	6
3/4" x 3/4" MHT 90 Deg Hose Bibb — Quarter-Turn	24621LF	6
1/2" x 3/4"MHT 90 Deg Hose Bibb — Multi-Turn	24626LF	6
3/4" x 3/4" MHT 90 Deg Hose Bibb - Multi-Turn	24627LF	6
1/2" x 3/4" MHT No-Kink 45 Deg Hose Bibb — Quarter Turn	24630LF	6
3/4" x 3/4" MHT No-Kink 45 Deg Hose Bibb — Quarter-Turn	24631LF	6
1/2" x 3/4" MHT No-Kink 45 Deg Hose Bibb — Multi-Turn	24632LF	6
3/4" x 3/4" MHT No-Kink 45 Deg Hose Bibb - Multi-Turn	24633LF	6
GARDEN VALVES		
1/2" x 3/4" MHT	24622LF	6
3/4" x 3/4" MHT	24623LF	6
ANTI-SIPHON FROST-FREE SILLCOCK		
1/2" x 3/4" MHT 8"	24628LF	4
1/2" x 3/4" MHT 10"	24629LF	4
1/2" x 3/4" MHT 12"	24636LF	4
1/2" x 3/4" MHT 15"	24637LF	4
1/2" x 3/4" MHT 18"	24638LF	4

SECTION 3: SHARKBITE PEX BARB FITTINGS

3-A: PEX BARB CORE FITTINGS

The SharkBite PEX/Barb Connection System is the best option for connecting PEX pipe in water distribution systems when lower material cost is desired. Robustly constructed with Lead Free DZR brass, the SharkBite barb fittings are corrosion resistant. With a wide range of fittings, manifolds, valves, clamp rings, crimp rings, ball valves and tools available, the SharkBite PEX/Barb Connection System is perfect for your next plumbing project.

COU	PLINGS		
3/8"	x 3/8"	UC006LF	10
1/2"	x 1/2"	UC008LF	25
5/8"	x 5/8"	UC012LF	10
3/4"	x 3/4"	UC016LF	25
l" x l	п	UCO20LF	10
æ	1-1/4"	UC0135	20
LARGE DIAMETER	1-1/2"	UC0141	20
=	2"	UC0154	15

	PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG			
RED	UCING COUPLINGS					
3/8"	X 1/2"	UCO09LF	10			
1/2"	X 3/4"	UCO58LF	25			
3/4"	X 5/8"	UCO57LF	10			
3/4" 2	X 1"	UCO60LF	25			
	1-1/4" x 3/4"	UC013522	20			
	1-1/4" x 1"	UC013528	20			
LARGE DIAMETER	1-1/2" x 3/4"	UC014122	15			
PIA	1-1/2" x 1"	UC014135	20			
	1-1/2" x 1-1/4"	UC014135	20			
	2" x 1-1/2"	UC015441	20			
THR	EADED FEMALE ADAPTERS					
1/2"	X 3/4" FNPT	UC068LF	25			
1/2"	X 1/2" FNPT	UCO72LF	25			
3/4" 2	X 3/4" FNPT	UC088LF	25			
1" X 1	" FNPT	UCO94LF	10			
THR	EADED MALE ADAPTERS					
3/8"	X 1/2" MNPT	UC118LF	10			
1/2"	X 1/2" MNPT	UC120LF	25			
1/2"	X 3/4" MNPT	UC116LF	25			
3/4" 2	X 1/2" MNPT	UC138LF	25			
3/4"	X 3/4" MNPT	UC134LF	25			
3/4"	X 1" MNPT	UC139LF	10			
1" X 3	/4" MNPT	UC142LF	10			
1" X 1	"MNPT	UC140LF	10			
SWE	AT FEMALE ADAPTERS					
1/2"	X 1/2"	UC600LF	25			
3/4" 2	X 3/4"	UC606LF	25			
1" X 1	11	UC605LF	10			
SWE	AT MALE ADAPTERS					
1/2"	X 1/2"	UC607LF	25			
3/4" 2	X 3/4"	UC608LF	25			
1" X 1	11	UC609LF	10			
ELB	DWS					
3/8" 2	X 3/8"	UC246LF	10			
1/2"	X 1/2"	UC248LF	25			
3/4" 2	X 3/4"	UC256LF	25			
1" X 1	11	UC260LF	10			
1-1/4	" x 1-1/4"	UC0235	10			
1-1/2	" x 1-1/2"	UC0241	10			
2" x 2	ıı	UC0254	10			
RED	REDUCING ELBOWS					
1 100						
1/2"	X 3/8"	UC272LF	10			
		UC272LF UC274LF	10 25			















	PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG
DRO	PP-EAR ELBOWS		
1/2"	X 1/2" FNPT Drop Ear	UC334LF	25
	X 3/4" FNPT Drop Ear	UC340LF	25
3/4"	X 1/2" FNPT Drop Ear	UC342LF	25
ADA	PTER ELBOWS		
1/2"	X 1/2" MNPT	UC280LF	25
1/2"	X 3/4" MNPT	UC278LF	25
3/4"	X 3/4" MNPT	UC286LF	25
3/4"	X 3/4" Female Sweat	UC626LF	25
3/4"	X 3/4" Male Sweat	UC628LF	25
TEES	S		
3/8"	X 3/8" X 3/8"	UC360LF	10
1/2"	X 1/2" X 1/2"	UC362LF	25
3/4"	X 3/4" X 3/4"	UC370LF	25
1" X	1" X 1"	UC374LF	10
æ	1-1/4"	UC0835	10
LARGE DIAMETER	1-1/2"	UC0841	5
_ 5	2"	UC0854	5
BUL	LNOSE TEES		
1/2"	X 1/2" X 3/4" Bull Nose	UC408LF	25
3/4"	X 3/4" X 1" Bull Nose	UC413LF	10
RED	UCING TEES		
3/8"	X 3/8" X 1/2"	UC364LF	10
1/2"	X 3/8" X 3/8"	UC452LF	10
1/2"	X 1/2" X 3/8"	UC363LF	10
1/2"	X 3/8" X 1/2"	UC434LF	10
3/4"	X 3/4" X 3/8"	UC417LF	10
3/4"	X 3/4" X 1/2"	UC412LF	25
3/4"	X 1/2" X 1/2"	UC454LF	25
3/4"	X 1/2" X 3/4"	UC444LF	25
1" X :	3/4" X 3/4"	UC414LF	10
1" X	1" X 1/2"	UC415LF	10
1" X	1" X 3/4"	UC416LF	10
1" X :	3/4" X 1"	UC418LF	10

	PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG
	l-1/4" x l" x l"	UC08352828	10
	1-1/4" "x 1-1/4" x 1/2"	UC08353516	10
	1-1/4" x 1-1/4" x 3/4"	UC08353522	10
	1-1/4" x 1-1/4" x 1"	UC08353528	10
	1-1/2" x 1-1/2" x 1"	UC08413528	5
~	1-1/2" x 1-1/2" x 1/2"	UC08414116	5
LARGE DIAMETER	1-1/2" x 1-1/2" x 3/4"	UC08414122	10
_ =	1-1/2" x 1-1/2" x 1"′	UC08414128	5
	1-1/2" x 1-1/2" x 1-1/4"	UC08414135	5
	2" x 2" x 1/2"	UC08545416	5
	2" x 2" x 3/4"	UC08545422	5
	2" x 2" x 1"	UC08545428	5
	2" x 2" x 1-1/2"	UC08545441	5
SWI	VEL ADAPTERS		
3/8"	X 3/8" NPSM	UC527LF	10
1/2"	X 1/2" NPSM	UC526LF	25
1/2"	X 3/4" NPSM	UC534LF	25
3/4"	X 3/4" NPSM	UC530LF	25
3/4"	X 1" NPSM	UC529LF	10
1" X 1	I" NPSM	UC594LF	10
SWI	VEL ELBOWS		
3/8"	X 1/2" NPSM	UC531LF	10
1/2"	X 1/2" NPSM	UC532LF	25
SWI	VEL TOILET CONNECTION ELBOWS		
1/2"	X 7/8" BC Straight	UC528LF	10
3/8"	X 7/8" BC Elbow	23068LF	6
1/2"	X 7/8" BC Elbow	23067LF	6
PLU	GS		
3/8"		UC512LF	10
1/2"		UC514LF	25
3/4"		UC518LF	25
]"		UC520LF	10
Æ	1-1/4"	UCO435	40
LARGE DIAMETER	1-1/2"	UC0441	30
5	2"	UC0454	20
	3-B: PEX BARB TRANSITION FITTING	NGS	
POL	YBUTYLENE TRANSITION COUPLINGS (WITH PB CRIMP RING)		
3/8"		UC4006LF	10
1/2"		UC4008LF	25
1/ 2			



PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG
3-C: PEX BARB POLY ALLO	YFITTINGS	
The SharkBite PEX poly alloy fittings range is an advanced plı DZR brass products.	umbing solution when corrosi	on may effect
COUPLINGS		
1/2" x 1/2"	UP008	25
3/4" x 3/4"	UP016	25
l"x l"	UP020	25
REDUCING COUPLINGS		
3/4" X 1/2"	UP058	25
1" X 3/4"	UP060	25
CONNECTORS		
1/2" X 1/2" MNPT	UP120	25
3/4" X 3/4" MNPT	UP134	25
1" X 1" MNPT	UP140	25
3/4" X 1/2" MNPT	UP138	25
ELBOWS		
1/2 x 1/2"	UP248	25
3/4" x 3/4"	UP256	25
l"x l"	UP260	2 5
MALE ELBOWS		
1/2" X 1/2" MNPT	UP280	25
REDUCING ELBOWS		
3/4" X 1/2"	UP274	25
TEES		
3/8" x 3/8" x 3/8"	UP360	10
1/2" x 1/2"x 1/2"	UP362	25
3/4" x 3/4" x 3/4"	UP370	25
1" x 1" x 1"	UP374	25
REDUCING TEES		
1/2" X 1/2" X 3/4"	UP408	25
3/4" X 1/2" X 1/2"	UP454	25
3/4" X 3/4" X 1/2"	UP412	25
3/4" X 1/2" X 3/4"	UP444	25
1" X 3/4" X 3/4"	UP414	25
1" X 1" X 1/2"	UP415	25
1" X 1" X 3/4" PLUGS	UP416	25
	UDE14	25
1/2" 3/4"	UP514 UP518	25 25
3/4 "	UP520	25 25
ADAPTERS	UF3ZU	23
1/2" x 1/2" NPSM	UP526	25
3/8" x 1/2" NPSM	UP527	10
3/0 X 1/2 NF3M 1/2" X 1/2" NPSM Elbow	UP532	25




PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG
3-D: PEX BARB FIRE FITTINGS		
FIRE HORIZONTAL TEES		
3/4" x 3/4" x 1/2" FNPT	UCF12128H	1
1" x 3/4" x 1/2" FNPT	UCF16128H	1
1" x 1" x 1/2" FNPT	UCF16168H	1
FIRE VERTICAL TEES		
3/4" x 3/4" x 1" FNPT	UCF12128V	1
1" x 3/4" x 1/2" FNPT	UCF16128V	1
1" x 1" x 1/2" FNPT	UCF16168V	1
FIRE DROP-EAR ELBOWS		
3/4" x 1/2" FNPT	UCF128U	1
1" X 1/2" FNPT	UCF168U	1
FIRE THREADED FEMALE ADAPTERS		
3/4" X 1/2" FNPT	UCF128S	1
FIRE ANGLED ADAPTERS		
3/4" X 3/4" X 1/2" FNPT	UCF12128A	1
FIRE FEMALE ELBOWS		
3/4" X 1/2" FNPT Left	UCF128L	1
3/4" X 1/2" FNPT Right	UCF128R	1
1" X 1/2" FNPT Left	UCF168L	1
1" X 1/2" FNPT Right	UCF168R	1




3-E: PEX BARB STOPS & FIXTURE SUPPLY FITTINGS			
PEX CHROME PLATED QUARTER TURN ANGLE STOPS			
1/2" X 3/8" OD Compression (Quarter Turn)	23058LF	24	
1/2" X 1/4" OD Compression (Quarter Turn)	23056LF	6	
PEX CHROME PLATED QUARTER TURN STRAIGHT STOP	S		
3/8" X 3/8" (Quarter Turn)	23382LF	6	
1/2" X 3/8" OD Compression (Quarter Turn)	23057LF	24	
PEX CHROME PLATED STRAIGHT STOPS			
1/2" X 3/8" Compression	23059LF	24	
1/2" X 3/8"	23062LF	6	
1/2" X 1/2" MPT	23061LF	6	
1/2" X 1/2"	23063LF	12	
PEX CHROME PLATED ANGLE STOPS			
1/2" X 3/8" Compression	23060LF	12	
1/2" X 3/4" MHT	23064LF	6	
PEX CHROME PLATED ANGLE DUAL OUTLET STOPS			
1/2" X 3/8" X 3/8" Compression Angle Stop	23066LF	6	

3-F: PEX BARB ADDITIONAL PRODUCTS				
COPPER STUBOUT ELBOWS (ALL COPPER STUBOUT ELBOWS ARE LEAD FREE)				
1/2" X Closed (4" X 8")	22791	12		
3/8" X 1/2" (4" X 4")	23069	6		
1/2" X 1/2" (4" X 4")	23070	6		











PRODUCT DESCRIPTION	PART NUMBER	QTY/BAG
PEX BEND SUPPORTS, SUSPENSION CLAMPS AND INSULATORS		
3/8" J Hook PEX Pipe Clamp (10 Pack)	23065	12
1/2" J Hook PEX Pipe Clamp (10 Pack)	23220	12
1/2" J Hook PEX Pipe Clamp (100 Pack)	23220Z100	5
3/4" J Hook PEX Pipe Clamp (10 Pack)	23221	12
1/2" Insulated Suspension Clamp (10 Pack)	23071A10	6
3/4" Insulated Suspension Clamp (10 Pack)	23072A10	6
1" Insulated Suspension Clamp (10 Pack)	23073A10	6
1/2" Pipe Insulator (10 Pack)	23074A10	6
3/4" Pipe Insulator (10 Pack)	23075A10	6
1" Pipe Insulator (10 Pack)	23076A10	6
1/2" Polymer Bend Support with mounting bracket	23050	12
3/4" Polymer Bend Support	23051	6
1/2" Metal Pipe Support	23053	12
3/4" Metal Pipe Support	23054	12
RADIANT INSTALLATION COMPONENTS		•
1/2" PEX Wire Mesh Installation Clips (25 Pack)	25485Z25	1
1/2" PEX Foam Insulation Twist Clips (25 Pack)	25486Z25	1
1/2" PEX Conduit Slab Support	25490Z	10

3-H: PEX BARB TOOLS			
PEX CRIMP TOOLS			
1/2", 3/4" PEX Combo Crimp Tool	23251	1	
3/8", 1/2", 3/4" PEX Pocket Crimp Tool	23383	1	
PEX CRIMP TOOL KIT			
3/8", 1/2", 3/4", 1" PEX Crimp Ring Tool Kit (Crimp Ring Gauge included)	23100	1	
1-1/4", 1-1/2", 2" Crimp Tool	24675	1	
PEX CLAMP TOOLS			
PEX Clamp Tool One-hand Operation	UC961	1	
PEX Clamp Tool Standard Handles	23081	1	
PEX PIPE CUTTER			
PEX Pipe Cutter	U701	1	
CRIMP RING GAUGE			
3/8", 1/2", 3/4", 1" PEX Crimp Ring Gauge	23080	6	
CRIMP RING REMOVAL TOOL			
PEX Crimp Ring Removal Tool	23055	6	
PEX DECOILER			
PEX Decoiler	UFH034	1	







Health/Safety

No glue, solder, or solvents required for the connection process, which keeps potentially dangerous chemicals out of plumbing systems. Additionally, SharkBite PEX Pipe eliminates the need for open flames in the house that could be a potential fire hazard. There is no risk of copper traces in water from breakdown of pipe that has been linked to heart disease and Alzheimer's.



Versatile

SharkBite PEX Pipe can be installed in dry or wet conditions.

SharkBite PEX Pipe can lend itself to many applications due to its physical properties of flexibility, reliability and installation ease such as hydronic heating, fire protection, etc.



Chlorine Resistance

SharkBite PEX Pipe is tested to the highest level of chlorine resistance standards, testing at 100% chlorine at 140°F.



Proven and Guaranteed

SharkBite PEX Pipe has been around for more than 35 years with over 12 Billion feet of pipe installed worldwide.



Freeze Resistant

SharkBite PEX Pipe is freeze resistant as the pipe can expand and contract as water freezes and thaws within the pipe.



Able to bend pipe around corners which removes the need for 45° or 90° elbows in certain situations. SharkBite's new coiling process increases the flexibility of our coiled pipe even more.



Cost Effective

SharkBite PEX Pipe is substantially more cost effective than Copper pipe—SharkBite PEX Pipe costs a third of the price of Copper. SharkBite PEX Pipe is a fixed cost as prices don't fluctuate daily like Copper pipe.

PROUDLY AMERICAN MADE





D (SHARKBITE)

SHARKBITE PEX – CERTIFICATIONS



NSF/ANSI 14 NSF/ANSI 61



ASTM F 876



ASTM F 877



CSA B137.5



AWWA C904



UL 1821

SharkBite PEX Pipe is an cost effective piping solution approved for use in both hot and cold plumbing installations. Meeting the highest chlorine resistance standards and utilizing the most energy efficient manufacturing processes, our PEX pipe is proudly produced in Alabama. We own our manufacturing process from start to finish, so every piece of SharkBite PEX Pipe is guaranteed from concept to delivery.


PEX pipe was introduced to North America in 1984 based on European market success, and was tested extensively for durability and material performance. All USA-installed PEX pipe must meet the qualification requirements as specified in the ASTM PEX Standards. SharkBite PEX Pipe can bend up to six times the outside diameter of the pipe—which is the maximum bend radius recommended by PEX pipe manufacturers.

SharkBite PEX Pipe can be used in a variety of applications including:

- Domestic plumbing
- · Fire suppression systems (residential fire sprinklers)
- Municipal water service pipe for use in underground applications
- Radiant heating systems for suspended floor systems or in slab construction
- Snow and ice melt systems for sidewalks, driveways, entrances, and ramps
- Turf conditioning for greenhouses, golf courses, and sports fields
- · Water reuse and reclamations systems

DISCOVER THE FLEXIBILITY OF SHARKBITE PEX PIPE.







SharkBite PEX Pipe is a cross-linked polyethylene pipe for use in a wide range of residential and commercial plumbing applications. Manufactured without an oxygen barrier for potable water systems and with an oxygen barrier for radiant floor and hydronic heating applications. A repeating SharkBite imprint pattern provides a visual aid to determine if the pipe has been inserted all the way into the SharkBite push-to-connect fitting. This feature only works if the pipe is cut between the SharkBite imprint pattern.

APPROVALS: The SharkBite pipe with and without oxygen barrier is approved for use in all model codes in the US and Canada, for use in hydronic and potable water systems, and is certified to the following standards: ASTM F876, ASTM F877, CSA B137.5 and AWWA C904.

	4-A: POTABLE W	ATER PEX PIPE			
PEX PIPE (COILS)	WHITE	RED	BLUE		
1/4" (3/8" OD) 50'	U850W50			1	\$20.00
1/4" (3/8" OD) 100′	U850W100				\$40.00
3/8" 50'	U855W50			1	\$22.50
3/8" 100′	U855W100	U855R100	U855B100	1	\$45.00
1/2" 25'	U860W25W	U860R25W	U860B25W	1	\$12.50
1/2" 50'	U860W50W	U860R50W	U860B50W	1	\$25.00
1/2" 100'	U860W100W	U860R100W	U860B100W	1	\$50.00
1/2" 300'	U860W300W	U860R300W	U860B300W	1	\$150.00
1/2" 500'	U860W500W	U860R500W	U860B500W	1	\$250.00
1/2" 1000′	U860W1000W	U860R1000W	U860B1000W	1	\$500.00
3/4" 25'	U870W25W	U870R25W	U870B25W	1	\$22.50
3/4" 50'	U870W50W	U870R50W	U870B50W	1	\$45.00
3/4" 100'	U870W100W	U870R100W	U870B100W	1	\$90.00
3/4" 300'	U870W300W	U870R300W	U870B300W	1	\$270.00
3/4" 500'	U870W500W	U870R500W	U870B500W	1	\$450.00
1" 100′	U880W100W	U880R100W	U880B100W	1	\$160.00
1" 300'	U880W300W	U880R300W	U880B300W	1	\$480.00
1" 500'	U880W500W	U880R500W	U880B500W	1	\$800.00
1-1/4" 100′	U885W100			1	\$300.00
1-1/2" 100′	U890W100			1	\$450.00
2" 100'	U895W100			1	\$850.00
PEX PIPE (STRAIGHT LENGTHS)	WHITE	RED	BLUE		
1/4" (3/8" OD) 5'	U850W5			20	\$2.00
3/8" 5'	U855W5			10	\$2.25
3/8" 10'	U855W10			10	\$4.50
1/2" 2'	U860W2	U860R2	U860B2	60	\$2.00
1/2" 5'	U860W5	U860R5	U860B5	10	\$2.50
1/2" 10'	U860W10	U860R10	U860B10	10	\$5.00
1/2" 20′	U860W20	U860R20	U860B20	10	\$10.00
3/4" 2'	U870W2	U870R2	U870B2	30	\$3.60
3/4" 5'	U870W5	U870R5	U870B5	10	\$4.50
3/4" 10'	U870W10	U870R10	U870B10	10	\$9.00
3/4" 20′	U870W20	U870R20	U870B20	10	\$18.00
1" 5'	U880W5	U880R5	U880B5	5	\$8.00
1" 10'	U880W10	U880R10	U880B10	5	\$16.00



PRODUCT DESCRIPTION	PART NUMBER	PART NUMBER	PART NUMBER	PACK/ QTY	LIST PRICE
1" 20'	U880W20	U880R20	U880B20	5	\$32.00
1-1/4" 20'	U885W20			5	\$60.00
1-1/2" 20'	U890W20			5	\$90.00
2" 20'	U895W20			3	\$170.00

PRODUCT DESCRIPTION	PART NUMBER	PACK/ QTY	LIST PRICE	
4-B: SPECIAL APPLICATION PEX	PIPE			
RECLAIMED WATER PEX PIPE (PURPLE COILS) FOR USE WITH NON-POTABLE WATER APPLICATIONS AND SHALL NOT BE INSTALLED IN UV-EXPOSED ENVIRONMENTS	RECLAIMED			
SharkBite reclaimed water PEX is cross-linked polyethylene pipe for gray water, rainwater harve tured with a purple color background, the pipe meets color code requirements of national and stalines. SharkBite reclaimed water PEX is manufactured and available in $1/2$ " to 1".				
1/2" 100'	U860P100	1	\$60.00	
1/2" 300′	U860P300	1	\$180.00	
3/4" 100'	U870P100	1	\$110.00	
3/4" 300′	U870P300	1	\$330.00	
1" 100′	U880P100	1	\$190.00	
1" 300′	U880P300	1	\$570.00	
OXYGEN BARRIER PEX PIPE (ORANGE COILS)	OXYGEN BARRIER			
Use for radiant floor and hydronic heating applications. The oxygen diffusion barrier is applied t the pipe wall in hydronic heating applications. This prevents corrosion of ferrous metal parts in the		xygen perm	eation through	
3/8" 100′	U8550100	1	\$70.00	
3/8" 300'	U8550300	1	\$210.00	
3/8" 500′	U8550500	1	\$350.00	
1/2" 100′	U8600100	1	\$70.00	
1/2" 300′	U8600300	1	\$210.00	
1/2" 500′	U8600500	1	\$350.00	
1/2" 1000′	U86001000	1	\$700.00	
5/8" 300′	U8650300	1	\$300.00	
3/4" 100′	U8700100	1	\$130.00	
3/4" 300′	U8700300	1	\$390.00	
3/4" 500′	U8700500	1	\$650.00	
3/4" 1000′	U87001000	1	\$1,300.00	
1" 100′	U8800100	1	\$225.00	
1" 300′	U8800300	1	\$675.00	
1" 500′	U8800500	1	\$1,125.00	
OXYGEN BARRIER PEX PIPE (ORANGE STRAIGHT LENGTHS)	OXYGEN BARRIER			
1/2" 20'	U860020	10	\$14.00	
3/4" 20'	U870020	10	\$26.00	
1" 20′	U880020	5	\$45.00	
1" 20′	U880020	5	\$45.00	





SHARKBITEPUSH-TO-CONNECT FITTINGS

- The SharkBite push-to-connect range is made from Lead Free DZR brass and all products were converted as of October 2012.
- The standard material versions of SharkBite push-to-connect fittings are no longer in production, but we do continue to offer a small range of 5/8" fittings in standard material, specifically intended for radiant heating applications. As a running change, these fittings will be converted to Lead Free in due course.
- Our SharkBite 2XL large Diameter fittings have been Lead Free since their introduction in February 2011.

SHARKBITE PEX/BARB FITTINGS

- Our PEX/barb range is made from Lead Free DZR brass and all products were converted as of October 2012.
- We have also implemented an extended range of engineered polymer barb fittings.





As of January 2014 a new Federal law came into effect that introduced a similar requirement across the whole country.

More information is available on our websites at:

www.cashacme.com

www.sharkbite.com

In this document, products are marked "Lead Free" or "Non-Potable" as applicable.

- "Lead Free" indicates that a product is suitable for use in an application that is anticipated or intended to deliver water for human consumption.
- "Non-Potable" designates that a product is only suitable for applications that are not anticipated or intended to deliver water for human consumption.

If a product is not marked "Lead Free" or "Non-Potable" it is either:

- Not designed to come into contact with water (e.g. tools, crimp rings, pipe hangers), or
- It is a replacement part or component for a valve or piece of Original Equipment, where it is necessary for the function of that valve or equipment to use the identical specification component with which it was originally designed and certified.

* A device is defined as Lead Free if its wetted surface has a weighted average lead content not exceeding 0.25%.



LIMITED WARRANTY

SHARKBITE, CASH ACME, AND HOLDRITE PRODUCTS

WHAT DOES THIS WARRANTY COVER?

Subject to conditions outlined in this statement, RWC (in the USA, Reliance Worldwide Corporation and in Canada, Reliance Worldwide Corporation (Canada) Inc.) warrants to owners of real property in the United States and Canada that SharkBite and Cash Acme products, when used and installed in accordance with the requirements set forth, shall be free from defects in material and workmanship for the applicable Warranty Period. This Limited Warranty is in effect for installations made after January 1, 2018 and is applicable to products installed in the country in which they were purchased.

Proof of purchase is required to validate the Warranty Period. If proof of purchase is not available, the Warranty Period commencement shall default to the date of manufacture for each product. If the product suspected of a defect does not have a clear date of manufacture on it, a proof of purchase will be required

WHAT ARE THE CONDITIONS OF THIS WARRANTY?

1. All products must be installed in accordance with all then applicable codes, good plumbing practice, in accordance with any local, state, provincial or federal requirements, and installed in a potable water or radiant heating application unless a non-potable water service is specifically allowed for in the pertinent product literature.

2. The installer must use construction techniques compliant with then applicable codes to install the product and use the product within the design parameters specified in any installation guidelines and technical notes for the applicable system. This shall include field pressure testing prior to concealing with concrete or by other means and wrapping any brass fitting when buried. Failure to install RWC products according to manufacturer's installation instruction will void all applicable warranties and may result in severe water damage.
3. Products must at all times be used in a manner consistent with their intended use and be used in installations and environments acceptable to their material and design specifications, including not being installed in a system that may operate at temperatures or at pressures that exceed the approved ratings which can be found on the product, packaging or installation instructions.

4. Additional product specific conditions of this Limited Warranty and the Warranty Period are documented in the section entitled "HOW LONG DOES THE LIMITED WARRANTY COVERAGE LAST AND WHAT OTHER SPECIFIC CONDITIONS EXIST FOR EACH PRODUCT?". 5. Without limiting the foregoing, this Limited Warranty does not apply and you do not have a right of reimbursement if the product failure or resulting damage is caused by: (a) evidence of tampering, mishandling, neglect, abuse, accidental damage, freeze damage (it is expressly understood that failure as a result of any freezing fluids within the pipes does not constitute a defect in material or workmanship and shall not be covered by this warranty) or unauthorized modifications or repairs that cause damage to warranted products; (b) exposure to harmful, unauthorized, or unanticipated chemicals or substances or corrosive water conditions; (c) exposure to ultraviolet light; (d) faulty installation including failure to follow proper burial instructions; (e) damage from abnormal operating conditions including exposure pressures and temperatures beyond the specified operating range: (f) failure to properly test and pass common testing methods (including pressure testing) after the installation and before the product or system is put in service; (g) components not manufactured or sold by RWC; or (h) acts of nature such as earthquakes, fire, flood or lightning.

6. Although RWC provides a plumbing system to facilitate a complete installation, other manufacturers pipe and/or fittings may be installed in any given installation provided manufacturing of the pipe and/or fittings demonstrates compliance with the applicable ASTM/CSA standards, and the product has been certified by a recognized third-party testing agency. The RWC product in the given installation will continue to be covered under this Limited Warranty although limits on Warranty Period may apply. RWC will be responsible only for proven defects in material or workmanship in RWC products. Problems in products manufactured by another company should be reported to that manufacturer.

HOW DO YOU GET SERVICE?

In order to be eligible for service under this Limited Warranty you must return the defective product to RWC for inspection and testing within thirty (30) days after detection of alleged failure or defect occurring within applicable Warranty Period (with shipping charges prepaid) to the original place of purchase. If the alleged defect involves a connection or joint with a RWC product, the fitting must be returned with a section of the pipe still inserted.

You must include the model number of the product (if available), the original date of purchase, proof of purchase and the nature of the alleged product failure or defect. Products returned without shipping charges prepaid will be refused. For questions or inquiries, in the U.S. call 1(877)700-4242 and in Canada 1(888)820-0120.

WHAT WILL RWC DO?

If, after inspection, we find that a product covered by this Limited Warranty has failed due to a defect in material or workmanship during the specified Warranty Period, we will repair or replace, at our sole option, free of charge, the defective product during normal working hours and through a place of business as determined by RWC.

Not withstanding anything to the contrary in this Limited Warranty, if RWC determines that any damages to the real property in which a defective product was installed were the direct result of a leak or failure caused by a defect in material or workmanship in any RWC product covered by this Limited Warranty and occurring within the first ten years after date of purchase or during the applicable Warranty Period, whichever is shorter, and if reasonable steps were taken to promptly limit or stop the effects of such leak or failure as soon as it was discovered, then RWC will reimburse the property owner for the reasonable costs of repairing or replacing such damaged real property to include flooring, drywall and painting and other real property damaged by the leak directly caused by the allegedly defective RWC product when the RWC SharkBite Connection System product was installed by a licensed professional plumbing contractor. Except as specified above or otherwise specifically authorized in writing by RWC, RWC shall not pay for any costs or expenses for transportation, relocation, labor, repairs or any other work associated with removing and/or returning failed or defective products or installing replacement products.

This shall constitute the sole and exclusive remedy for any defective product.

WHAT DOES THIS LIMITED WARRANTY NOT COVER?

RWC shall not be responsible for any other incidental, indirect, contingent, special or consequential damages, including without limitation, economic loss, lost profits or the cost of repairing or replacing other property which is damaged if these warranted products do not work properly, other costs resulting from labor charges, delays, vandalism, negligence, fouling caused by foreign material, damage from adverse water conditions, adverse chemical environments, or any other circumstances over which RWC has no control. This limitation applies even if RWC could have foreseen or has been advised of the possibility of these damages. This Limited Warranty shall be invalidated by any abuse, misuse, misapplication or improper installation of the product. Any remaining warranty coverage may not be assigned or transferred after the period ending ten years following the installation. RWC does not guarantee or in any way warrant the integrity or workmanship of the contractor/installer.

MISCELLANEOUS

Some States/Provinces do not allow limitations on how long an implied warranty lasts, and some States/Provinces do not allow the exclusion or limitation of incidental or consequential damages. Therefore, the above limitations may not apply to you. This Limited Warranty gives you specific legal rights, and you may have other rights that vary from State/Province to State/Province. You should consult applicable State/Provincial laws to determine your rights.

SO FAR AS IS CONSISTENT WITH APPLICABLE STATE/ PROVINCIAL/FEDERAL LAW, THE EXPRESS WARRANTY SET FORTH HEREIN IS THE ONLY WARRANTY GIVEN BY RWC WITH RESPECT TO THE SHARKBITE® AND CASH ACME® PRODUCTS AND RWC MAKES NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, AND HEREBY SPECIFICALLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

This Limited Warranty and any claims arising from breach of contract, breach of warranty, tort, or any other claim arising from sale or use of RWC's products shall be governed and construed under the laws of the State of Georgia. No action on the part of RWC under this Limited Warranty shall be construed as an admission of liability of that the product is not fit for its intended use.

CLASSIFICATION	PRODUCT CATEGORY	LIMITED WARRANTY PERIOD	COMMENTS
	SharkBite Brass and Poly PEX Barb Fittings in conjunction with SharkBite PEX Pipe and SharkBite Rings/ Clamps	Twenty-Five (25) Years	SharkBite PEX Pipe Only - ASTM F876/CSA B137.5 SharkBite Copper Crimp Rings – ASTM F1807 or F2159 Stainless Steel Clamp Rings – ASTM F2098
SharkBite Connection Systems	SharkBite EvoPEX Fittings in conjunction with SharkBite PEX Pipe	Twenty-Five (25) Years	SharkBite PEX Pipe Only - ASTM F876/CSA B137.5
	SharkBite Universal Push-To-Connect Fittings in conjunction with SharkBite PEX Pipe	Twenty-Five (25) Years	SharkBite PEX Pipe Only - ASTM F876/CSA B137.5
	SharkBite Universal Push-To- Connect Fittings and SharkBite Large Diameter Push-To-Connect Fittings in Application with Copper, PEX, CPVC and/or PE-RT	Twenty-Five (25) Years	Must be used with: Copper-ASTM B 88 hard drawn copper tube K, L, and M PEX-ASTM F876/CSA B137.5 CPVC-ASTM D2846 or CSA B137.6 PE-RT-ASTM F2769
	SharkBite Universal Push-To- Connect Fittings and SharkBite Large Diameter Push-To-Connect Fittings in Application with HDPE	Five (5) Years	Must be used with: • HDPE SDR-9 ASTM D2737
	SharkBite PEX Pipe	Twenty-Five (25) Years	If used with: • ASSE 1061, ASTM F1807, ASTM F2098, and/or ASTM F2159 Fittings
	SharkBite Brass PEX Barb Fittings/ Copper Manifold	Five (5) Years	If used with PEX Pipe and Clamps/Rings that conform to: PEX – ASTM F876/CSA B137.5 Copper Crimp Rings – ASTM F1807 Stainless Steel Clamp Rings – ASTM F2098
	SharkBite Poly PEX Barb Fittings	Five (5) Years	Must be used with Non-SharkBite PEX Pipe and Clamps/ Rings that conform to: PEX – ASTM F876/CSA B137.5 Copper Crimp Rings – ASTM F2159 Stainless Steel Clamp Rings – ASTM F2098
SharkBite, Cash Acme, and	SharkBite EvoPEX Fittings	Five (5) Years	Must be used on Non-SharkBite PEX Pipe that conform to ASTM F876/CSA B137.5
HOLDRITE Products	SharkBite Home Run Manifolds	Ten (10) Years	Must be installed per installation instructions
	SharkBite Tools	One (1) Year	From date of purchase; used in accordance with instructions
	SharkBite and Cash Acme Thermostatic Mixing Valves	Five (5) Years	Must be installed per installation instructions
	Other SharkBite and Cash Acme Valves	Two (2) Years	Must be installed per installation instructions
	SharkBite Accessories (Ball Valves, Supply Hoses, Supply Stops, Supply Valve Box Systems, Kits, Manifolds, etc.)	Two (2) Years	Must be installed per installation instructions
	SharkBite Quick-Connect POM Plastic Fittings	One (1) Years	Must be used with: Polyethylene, Nylon, PEX, and Soft Copper (must be round and in good condition)
	HOLDRITE Pipe Support Products	One (1) Years	Must be installed per installation instructions
	HOLDRITE Testrite	One (1) Years	Must be installed per installation instructions
	HOLDRITE Hydroflame Pro	One (1) Years	Must be installed per installation instructions



Part Number Page	Part Number	Page	Part Number	Page	Part Number	Page	Part Number	Page
22182-0000LF15	23103	24675		SBTL35	14 412 F	6	U860R100W	26
22185-0000LF15	23103CP25			SBTL41		6	U860R300W	
22186-0000LF15	23103CP100		10	SBTL54		6	U860R500W	
22187-0000LF15	23104			SS3068FLEX18BV				26
22222-0000LF15	23104CP2522			SS3086FLEX24LF	9 U462LF.	6		26
22223-0000LF15	23220			SS3088FLEX18BV	10 U464LF.	6		26
22304-0000LF15	23220Z100		15	SS3088FLEX18LF			U860W10	
22305-0000LF15	23221			SS3088FLEX24LF				26
22306-0000LF15	23251		15	U004LF		8		26
22441LF12	23336-0000LF10		15 11	U006LF				.26 .26
22461LF	23337-0000LF10 23358-004514			U009LF	3 UDZULF.		U860W100W	
22463LF22	23382LF			U012			U860W500W	
22486LF12	23383		11	U016LF			U860W1000W	
22604LF	23489		11	U020LF				27
22630LF12	23490		11	U050LF		4		26
22631LF12	23807-004514	24936	11	U057	8 U701		U870B5	26
22632LF12	23808-004514		11	U058LF		13		26
22633LF	23893-004514			U060LF		13		26
22675-004514	23894-004514]]	U066LF	3 U708	13		26
22783	23896-0060			U068LF		13		26
22784	23945-006014 23955-004514		11 10	U070LF		13	U870B100W U870B300W	
22786	23956-004514			U086LF			U870B500W	
22787	24377			U088LF		13	U870020	
22788	24383-004514			U092LF			U8700100	
22789	24384-004514		10	U094LF			U8700300	
22790	24436			U110LF			U8700500	27
22791	24437			U116LF			U87001000	27
23036-0000LF10	24438			U118LF				27
23037-0000LF10	24438A			U120LF		4		27
23048-0000LF10	24439		l3	U126		4	U870R2	
23049-0000LF10 2305023	24440		13 13	U134LF		11 26		.26 .26
23051	24442			U139LF				26
23053	2444312		14	U140LF		0		26
23054	24444			U142LF	4 U855B10	026	U870R50W	
23055	24445	25478		U244LF		027	U870R100W	
23056LF21	24449-004514		11,22	U246LF		027	U870R300W	
23057LF	24504			U248LF		027	U870R500W	
23058LF21	24505			U249LF		0		26
23059LF	24529			U252 U256LF		26)26	U870W5 U870W10	.26 .26
23061LF	24548		14	U260LF			U870W20	
23062LF	24549			U272LF		026	U870W25W	
23063LF	24609-015016		15	U273		26		26
23064LF 21	24615-0000LF15		15	U274LF		26	U870W100W	
23065	24616-0000LF15			U276LF			U870W300W	26
23066LF	24617-0000LF15		11	U278LF		26	U870W500W	
23067LF	24620LF 16		!]	U280LF		W26		26
23068LF	24621LF16		11	U281LF		W26	U880B10	
23069	24622LF			U286LF		OW26 OW26	U880B20 U880B100W	
23071A10	24626LF16			U314LF		0W26	U880B300W	
23072A10	24627LF16			U332LF		00W 26	U880B500W	
23073A10	24628LF			U334LF		27		27
23074A10	24629LF16	25567	13	U335LF		027	U880020	
23075A10	24630LF16			U340LF		027	U8800100	
23076A10	24631LF16		SB 15	U351LFA		027	U8800300	
23080	24632LF		15	U358LF		0027	U8800500	
23081	24633LF16		15	U359LF		027	U880P100	
23100	24634LF 16			U360LF		0	U880P300	
23101CP25	24635LF16 24636LF16		12	U363LF		26	U880R10	
23101CP10022	24637LF16			U364LF		26		27
2310222	24638LF 16			U366			U880R100W	
23102CP2522	24656		22	U370LF		W26	U880R300W	
23102CP10022	24657	SBDC35415	4 13	U374LF		W26	U880R500W	26

Part Number Page	Part Number	Page	Part Number	Page	Part Number	Page	Part Number	Page
U880W526	UC134LF17	UC0841	18	UIP376	8 UXL0854	5	UXLBV35	
U880W1026	UC013516	UC0854	18	UIP514	8 UXL0935	4	UXLBV4115	
U880W2027	UC138LF17	UC952		UIP518		4	UXLBV54	
U880W100W	UC139LF			UIP520 UIP710			UXLDC35	
U880W500W	UC014116			UIP712			UXLDC54	
U885W2027	UC142LF17			UIP714	8 UXL014135.	3	UXLG0313	
U885W10026	UC0154			UIP3008				
U890W2027 U890W10026	UCO23517 UCO24117		19	UIP3016 UIP3020				
U895W2027	UC246LF17			UIP4008				
U895W10026	UC248LF17	UC013522		UIP4016				
U2008-0000LF15	UC0254	UC013528		UIP4020				
U2016-0000LF15	UC256LF	UC014122		UP008	20 UXL115450M	4		
U2020-0000LF15 U2276LF5	UC260LF	UC014135		UP016	20 UXL123516.			
U3001A12	UC273LF17	UC015441		UP058				
U3008FLEX18LF10	UC274LF17	UC08352828 .		UP060				
U3008LF	UC278LF		19	UP120				
U3016FLEX18LF10	UC280LF18	UC08353522 .		UP134				
U3016LF	UC286LF	UC08353528 . UC08413528 .		UP138				
U3068FLEX12LF9	UC340LF18	UC08414116		UP248				
U3068FLEX15LF9	UC342LF18	UC08414122 .	19	UP256	20 UXL125428.			
U3068FLEX18BVLF10	UC360LF18		19	UP260				
U3068FLEX18LF9 U3068FLEX24LF9	UC362LF	UC08414135 . UC08545416 .		UP274 UP280				
U3086FLEX24LF10	UC364LF18	UC08545410 .		UP360		5 6		
U3088FLEX12LF9	UC370LF18		19	UP362		26		
U3088FLEX15LF9	UC374LF18		19	UP370		3 6		
U3088FLEX18BVLF10	UC408LF	UCF128L		UP374		5 6		
U3088FLEX18LF9 U3088FLEX24LF9	UC412LF	UCF128R UCF128S		UP408				
U3120LF	UC414LF18	UCF128U		UP414		3 6		
U3134LF 4	UC415LF18	UCF168L	21	UP415		66		
U3140LF	UC416LF18	UCF168R		UP416		2 6		
U3358LF	UC417LF	UCF168U UCF12128A		UP444		}		
U3370LF	UC434LF18	UCF12128H		UP514		36		
U3482LF	UC043519	UCF12128V		UP518				
U3486LF	UC0441	UCF16128H		UP520		2 6		
U3523LF	UC444LF18 UC452LF18	UCF16128V UCF16168H		UP526		3		
U3525LF	UCO454	UCF16168V		UP532		5 6		
U3531LF	UC454LF18	UF128L	9	UXL0135	3 UXL08414122	26		
U3537LF	UC512LF19	UF128R		UXL0141		36		
U3712	UC514LF		9 9	UXL0154		5		
U4016LF	UC520LF19	UF168L		UXL0241		? 6		
U4358LF	UC526LF19	UF168R		UXL0254	4 UXL08544128	3 6		
U4482LF	UC527LF19			UXL0335		5 6		
UC006LF	UC528LF	UF12128A UF12128H	9	UXL0341		6 6		
UC009LF	UC530LF19	UF12128V		UXL0435		6		
UC012LF16	UC531LF19	UF16128H		UXL0441		6		
UCO16LF	UC532LF			UXL0454		6		
UCO20LF	UC534LF	UF16168H	9	UXL0535		i 6		
UC058LF17	UC600LF17	UFH034		UXL0554		6 57		
UC060LF	UC605LF17		8	UXL0635	3 UXL10353520			
UC068LF17	UC606LF17		8	UXL0641	3 UXL10353525	5		
UC072LF17	UC607LF17		8	UXL0654		5		
UC088LF	UC608LF	UIP363 UIP364		UXL0735)		
UC116LF17	UC626LF18			UXL0754		;		
UC118LF17	UC628LF18		8	UXL0835	5 UXL10545420			
UC120LF17	UC0835 18	UIP3/5	8	UXL0841	5 UXL10545425	i		



CERTIFICATIONS

The SharkBite push-to-connect fittings have been certified and listed to ASSE 1061 and NSF/ANSI 61. The SharkBite push-to-connect fittings are listed by IAPMO and are certified for potable and hydronic heating water distribution (Note: Glycol mixture for hydronics is acceptable up to and including 100%). The SharkBite push-to-connect fittings have been certified for underground applications and as a manufactured joint without access panels and they meet UPC, IPC and cUPC requirements. Any SharkBite fitting listed as Lead Free is compliant with NSF/ANSI 372. Please consult with local plumbing codes concerning specific applications.

The SharkBite pipe without oxygen barrier is approved for all model codes in the US and Canada for use in potable water systems and is certified to the following standards: ASTM F 876, ASTM F 877, CSA B137.5 and AWWA C904.

The SharkBite pipe with oxygen barrier is approved for use in all model codes in the US and Canada for use in hydronic and potable water systems and is certified to the following standards: ASTM F 876, ASTM F 877, CSA B137.5 and AWWA C904.

Note: The SharkBite push-to-connect fittings are not approved for use with chrome-plated pipe. SharkBite Polybutylene couplings are designed to work with ASTM D3309 spec polybutylene, do not install onto damaged or decayed PB pipe.



Reliance Worldwide Corporation

www.rwc.com





www.sharkbite.com | www.cashacme.com