

Si-30

Mini condensate removal pump

Compact design for install remotely above the air conditioning unit.



- Up to 5.5 tons
- Suspended ceiling units
- Wall mounted units Floor mounted units
- · Ducted units

- **Performance**
- 5 gph max. flow
- 33' max. discharge



Mounting bracket



Locking power cord



Drain safe device


Sauermann




Si-30 tech specs

Max. Flow rate	5.0 gph
Max. Suction head	10ft
Max. Discharge head	33ft; flow rate = 1 gph
Max. Pressure	46ft; flow rate = 0 gph
Sound level at 3.3ft	20 dBA according to EN ISO 3744 (measured at LNE lab, pump operating with water, out of application)
Power supply	120 V ~ 60 Hz - 14 W (SI30UL01UN12) 230 V ~ 50/60 Hz - 14 W (SI30UL01UN23)
Insulation class	Double insulation
Detection levels	On: 5/8" / Off: 7/16" / Safety: 3/4"

Safety switch	NC 8A resistive - 250 V
Thermal protection	240°F auto-reset
Operating conditions	70%: 3s ON – 5s OFF
Pump dimensions	L 2 ⁵ / ₈ " x W 1 ³ / ₄ " x H 2 ³ / ₈ "
Safety standards	UL / CSA certified by Intertek
RoHS & WEEE directives	Compliant
Packaging	1.1 lbs - L 5 ⁵ / ₁₆ " x W 5 ⁵ / ₁₆ " x H 3 ¹⁷ / ₃₂ "
Masterpack	20 pieces







Recommended accessories





- ACC00909: 16ft roll
- ACC00910: 164ft roll



Self-sealing fitting to connect discharge tube to drain pipe.

 ACC00919, 5 pcs, for ¹/₄" i.d.

What's in the box

- Si-30 piston pump with clear pvc tube fitted with a pre-mounted drain safe device
- 5' power cable: 2 power wires, 2 safety contact wires
- · Anti-vibration rubber damper
- Detection unit Si2958, 2' cable
- Detection unit installation kit:
 - Rubber elbow
 - Vent tube
 - Mounting rail
 - Adhesive
- 6 tie wraps