

# FLUX HVAC/R PLUMBING

QUALITY BRAZED JOINTS REQUIRE FLUX TO PROTECT THE JOINT DURING HEATING AND PROMOTE COMPLETE BRAZE ALLOY FLOW. TO ENSURE THE BEST CONNECTIONS HARRIS DESIGNED, DEVELOPED, AND PRODUCED A VARIETY OF FLUXES FOR SPECIFIC APPLICATIONS TO MEET OUR CUSTOMER'S NEEDS.

## QUICK SELECTION GUIDE



DESCRIPTION	BRIDGIT	STAY - CLEAN®	STAY-SILV® WHITE	STAY-SILV® BLACK	ECOSMART™ BLACK	ECOSMART™ GREEN
4 OZ BOTTLE	BRPF1- BRPF4POP	SCLF4 - SCAF4				
6.5 OZ BOTTLE			SSWF7 - SSWF7POP			
16 OZ BOTTLE		SCLF16				
32 OZ BOTTLE	BRPF4WS	SCLF32				
1 LB BOTTLE	BRPF1					
1 GALLON		SCLF1G				
55 GALLONS		SCLF55				
6.5 OZ JAR						ESF70ZPG
4 OZ JAR		SCPF4 - SCPF4POP				
1/4 LB JAR			SSWF1/4			
1/2 LB JAR			SSWF1/2	SSBF1/2	ESF1/2PB - ESF1/2DB	ESF1/2PG - ESF1/2DG
1 LB JAR		SCPF1	SSWF1	SSBF1	ESF1PB	ESF1PG
5 LB JAR			SSWF5	SSBF5	ESF5PB	ESF5PG
25 LB PAIL			SSWF25		ESF25DB	ESF25PG
30 LB PAIL				SSBF30		
40 LB PAIL					ESF40DB	ESF40DG
60 LB PAIL			SSWF60	SSBF60		