



Use Malco adjustable nylon ties to install flexible duct to take-offs, or secure bundles, up to 15 in. (3.81 cm) diameter.

Made of 100% nylon, Malco ties offer a minimal tensile strength of 175 pounds.

Adjustable Tie Tensioning Tool

High leverage tensioning tool with auto cut-off, for continuous use on-the-job. The TY6 Tensioning Tool is designed for a heavy user of nylon ties. An adjustment knob allows installer to set desired tension for securing flex duct to a take-off collar. When the tie is tight, a breakaway spring mechanism releases the tool's lower handle, causing the blade to engage and automatically flush cut off the excess tail of the nylon tie. No extra operation for manual trimming is required. Nylon tie installation is fast and easy with the TY6. Works on all ties including thin designs.

Operating the TY6 is easy on the installer too! Contoured handles, with stops, are easier to grasp. Also, smooth lever action and vinyl cushion grips minimize hand and arm fatigue on big jobs.

The TY6 features a hardened steel body, long wearing parts, and a weather resistant nickel chrome finish to assure many years of dependable service.

All Malco Tie Tools are designed to work on standard 175 lb. (778 N) ties as well as thinner 125 lb. (556 N) ties.

Catalog	Description	Length in. (mm)	Net Wt.	
Number			oz. (g)	
TY6	High Leverage Tie Tool	8-1/2 (216)	15 (425)	_
TY4	Manual Cut-Off Tie Tool	6 (152)	10 (284)	
TY4G	Manual Cut-Off Tie Tool /Gripped	6 (152)	11 (312)	_

