

APPION™

Star Performance

G5Twin™

CYLINDER / CONDENSER



Industrial Heavy Duty

- Chillers
- Supermarkets
- Ships
- Ice Rinks
- Horizontally Opposing Twin Cylinders and Twin Condensers for ultra-fast recovery.
- Permanently-lubricated, bearing-lined crankcase is **isolated from refrigerant**, eliminating bearing contamination.
- Pumps liquid and vapor with no throttling.
- 7-inch, 10-blade turbine fan blasts over **600 cfm of cooling air** over the twin condensers and twin cylinder heads.

Dimensions and Power		
Length	13.75 in	349 mm
Height	10.30 in	262 mm
Width	9.40 in	239 mm
Weight	24 Lbs	11 Kgs
Power	115 VAC, 60 Hz, 10 Amps Int'l: 230 VAC, 50 Hz, 5 Amps	

**Pumps R410a
Liquid/Vapor**

Flip Over for →
G1 Single
SINGLE CYLINDER RECOVERY

Up to 4x
Faster

New & Improved Performance for 2016

G5 Twin Recovery Rates			
Refrigerant	Push-Pull	Liquid	Vapor
R-134a	15.87 lb/min 7.20 kg/min	10.14 lb/min* 4.60 kg/min*	0.46 lb/min** 0.21 kg/min**
R-22	16.62 lb/min 7.54 kg/min	10.36 lb/min 4.70 kg/min	0.62 lb/min 0.28 kg/min
R-407C	17.61 lb/min 7.99 kg/min	11.93 lb/min 5.41 kg/min	0.55 lb/min 0.25 kg/min
R-410A	20.50 lb/min 9.30 kg/min	17.20 lb/min 7.80 kg/min	0.55 lb/min 0.25 kg/min

* Using high speed direct liquid mode; 8.16 lb/min (3.7 kg/min) with standard recovery.

** With external cooling accessory; 0.44 lb/min (0.20 kg/min) with standard recovery.



Industrial/Commercial Recovery

At **only 24 lbs.** (11 kgs.), the G5 Twin is the **smallest and lightest** recovery machine capable of handling the tough demands of industrial/commercial refrigerant recovery.



See how to get the fastest possible recovery speeds with the G5Twin.

G1 Single™

SINGLE CYLINDER RECOVERY



Economical Standard Duty

- Ductless Splits
- PTACs
- Heat Pumps
- Vending
- Easy to use, ideal for residential and appliance recovery jobs.
- Comparable recovery rates to larger machines, without the bulk and hassle.
- Permanently-lubricated crankcase is isolated from refrigerant, eliminating bearing contamination.
- No purge cycle required.

High Speed/High Pressure Turbine Fan - Over 600cfm



Modular Construction for Easy Repair

Permanently Lubricated Heavy Duty Crankcase Isolated From Refrigerant

Pumps R410a Liquid/Vapor

Flip Over for →
G5 Twin
CYLINDER / CONDENSER

Dimensions and Power

Length	11.38 in	289 mm
Height	10.30 in	262 mm
Width	9.40 in	239 mm
Weight	22 Lbs	10 Kgs
Power	115 VAC, 60 Hz, 10 Amps Int'l: 230 VAC, 50 Hz, 5 Amps	

G1 Single Recovery Rates			
Refrigerant	Push-Pull	Liquid	Vapor
R-134a	9.44 lb/min 4.28 kg/min	5.20 lb/min 2.36 kg/min	0.22 lb/min 0.10 kg/min
R-22	10.80 lb/min 4.90 kg/min	8.55 lb/min 3.88 kg/min	0.26 lb/min 0.12 kg/min
R-407C	11.33 lb/min 5.14 kg/min	5.84 lb/min 2.65 kg/min	0.31 lb/min 0.14 kg/min
R-410A	12.17 lb/min 5.52 kg/min	4.32 lb/min 1.96 kg/min	0.26 lb/min 0.12 kg/min



For More Information Visit:
www.AppionTools.com