

Pipe Joint Compounds



- **Blue Joint™** (Slow drying blue)
- **Sure Joint™** (Slow drying gray)
- **Lock Joint™** (Fast drying blue)
- **Seal Joint #55™** (Fast drying tan yellow)

Thread Sealant

ComStar's Thread Sealants are excellent for sealing, lubricating and protecting NPT thread connections on iron, galvanized steel, stainless steel, copper, brass, aluminum and on plastic pipe and gasket material. For use on lines containing oils, gasoline, natural gas, water, air steam, ammonia diluted acids and alkalines. Good for services temperature between -60°F to 450°F, liquid pressure up to 10,000 PSI and gas pressure up to 2500 psi.

- Locks out leaks
- Contains no lead
- Assures a tight, positive pressure seal
- Will not harden, separate or drip

Available in a 2 oz. tube, 1/4 pt., 1/2 pt., 1 pint & quart containers



Stock No. 10-515
(1/4 pt.)
Slow dry all-purpose (Blue)



Stock No. 10-415
(1/4 pt.)
Slow dry all-purpose (Gray)



Stock No. 10-615
(1/4 pt.)
Fast dry HVAC systems high & low temperature (Blue)



Stock No. 10-715
(1/4 pt.)
Fast dry heavy duty (Tan yellow)

