IECHNICAL DATA SHEET DIVERSITECH

Specifications

Product DiversiTech Pull-out Disconnect Switches: DDS-30, DDS-60

(fusible), DDS-60U and EDS-60U (non-fusible)

Application HVAC circuitry

Power Rating 30A (DDS-30) or 60A at 240VAC, 10 horsepower max

Indoor/Outdoor Use indoor/outdoor

Package Medium Metal case with 180 degree opening door

Advantages Convenient design allows for easy access to controls via

wide-opening, reversible door with full dead front. Fused models benefit from having fuses located in easy pull-out handle with indicator lights for blown fuses. Line, load, and ground terminals aligned for easy wiring. EDS-60U Low-profile model also available for tighter spaces.

Directions Please refer to an electronic copy of this product's

brochure at www.diversitech.com/literature/lit-fly-disc.pdf

HAZMAT Hazard None.



Producer of Goods DiversiTech

Domestic/Foreign Commodity Foreign

SKU Specific Package Metrics

UPC DDS-30 - 095247082445

DDS-60 - 095247082452 **DDS-60U** - 095247082421 **EDS-60U** - 095247089420

Unit Dimensions DDS-30 - 2-5/8"L x 5"W x 7-1/2"H

DDS-60 - 2-3/4"L \times 5-1/8"W \times 8-5/8"H **DDS-60U** - 2-3/8"L \times 5"W \times 7-1/2"H **EDS-60U** - 2-1/2"L \times 4.8"W \times 6.3"H

Unit Weight DDS-30 - 2.7 lbs.

DDS-60 - 3.3 lbs. **DDS-60U** - 2.5 lbs. **EDS-60U** - N/A

 $\textbf{Case Dimensions} \quad \textbf{DDS-30} - 14\text{"L} \times 11\text{"W} \times 8\text{-}1\text{/}4\text{"H}$

DDS-60 - 16"L x 11"W x 9-1/4"H DDS-60U - 13"L x 11"W x 8-1/4"H

EDS-60U - N/A

Case Weight DDS-30 - 28.6 lbs.

DDS-60 - 33.7 lbs. **DDS-60U** - 26.6 lbs. **EDS-60U** - N/A

Quantity per Package 10





Pull-out Disconnect Switches