## TECHNICAL DATA SHEET DIVERSITECH



## **Product**

EcoPad™ Equipment Pads

## **Advantages**

EcoPad™ equipment pads are made from injection molded plastic. Their application is mainly as a base pad for ground supported equipment. Unlike other plastic pads, EcoPad™ rugged design provides uniform and generous ribbing for optimum self-leveling ground support without inserts. The pads should be installed on roughly leveled soil or ground. EcoPad™ equipment pads, due to their plastic composition, are not recommended for use in applications requiring pad contact with excessive heat or open flame. Enclosed is a table s howing the allowable load estimates. Both 2″ and 3″ pads have the same weight capacity.



2" Pad Size	Estimated Allowable Load*
EP2424-2	173
EP2430-2	216
EP2436-2	259
EP2626-2	203
EP3030-2	270
EP3036-2	324
EP3232-2	307
EP3244-2	422
EP3434-2	347
EP3636-2	389
EP3640-2	432
EP3648-2	518
EP3842-2	479

<sup>\*</sup>EcoPads are limited to 80 lb concentrated load per 2" diameter disc. Max weight when pad is uniformly loaded.

3" Pad Size	Estimated Allowable Load*
EP1838-3	205
EP2424-3	172
EP2436-3	259
EP2448-3	346
EP3030-3	270
EP3232-3	307
EP3244-3	422
EP3434-3	347
EP3636-3	389
EP3640-3	432
EP3648-3	518
EP3870-3	798
EP4040-3	480
EP4558-3	783
EP4848-3	691
EP5042-3	630
EP5060-3	900
EP5070-3	1050
EP5252-3	811
EP5658-3	974