



ASA-WFT

INSULATION ADHESIVE

Duro Dyne ASA-WFT is a fast tacking, quick bonding solvent base aerosol spray duct liner adhesive. It may be used for bonding low and high density duct liner or wrap to the interior or exterior of metal ductwork. Duro Dyne ASA-WFT bonds rubber, fiberglass, plastic, and other types of insulation to steel.

FEATURES:

- Convenient spray can
- Fast Tacking
- Non-flammable

PROPERTIES	
TYPE	Solvent Cement
SOLIDS	25
WEIGHT	10.4 lbs./gal.
SOLVENT SYSTEM	Aliphatic (Hexane) and Ketone (Acetone)
COLOR	Amber
ODOR	None
VISCOSITY	1960 CPS
FLAMMABILITY	Adhesive-Non Flammable; Propellant - Flammable
EFFECT OF FREEZING	No Damage
STORAGE LIFE	6 months @ 70°F
SUGGESTED SURFACE PREPARATION	Surfaces must be clean and dry, free of dust, dirt, grease, oil and other foreign material.
METHOD OF APPLICATION:	Aerosol Spray



Ordering Information

Item #	Code	Description	Quantity	Weight (lbs.)
5015	ASA-WFT	Web Aerosol Spray Adhesive	12 Per Ctn.	14

Skid Quantity 90 boxes or 1080 cans

Duro Dyne East Division, Bay Shore, NY 631-249-9000 Fax: 631-249-8346
Duro Dyne Midwest Division, Hamilton, OH 513-870-6000 Fax: 513-870-6005
Duro Dyne West Division, Fontana, CA 562-926-1774 Fax: 562-926-5778
Duro Dyne Canada, Lachine, Quebec, Canada 514-422-9760 Fax: 514-636-0328
www.durodyne.com E-mail: durodyne@durodyne.com



© Duro Dyne Corp.
Printed in USA 06/17
BC006005