The LuxPro[®] Imprint Program

What's the most important name on any thermostat? It's not the brand name. It's the installer's name that matters. A thermostat that bears the name of the installing contractor is a powerful marketing tool that can help maintain the business relationship after the initial sale. LuxPro can personalize any thermostat for virtually any application. There are no set-up fees and minimum quantities are surprisingly low. From logotype design to final packaging, LuxPro can help get you started with your own private brand.



For immediate response to LUXPRO ordering and pricing inquiries, call 856-234-7905, press 4, and ask for your LuxPro expert.

Special Contractor Techline

LUXPRO Technical Support: 856-234-8803, press 7 If a tech is not available at the time, leave a message and your call will be returned within 15 minutes.

For individual Spec Sheets and Installation / Operating Manuals, please visit http://www.luxproproducts.com.



Lux Products Corporation 6000 Commerce Parkway, Suite I Phone: 856-234-7905 | Fax: 856-234-7825

www.luxproproducts.com



Thermostats and Accessories

LuxPro[®] Pro-Fit Series Thermostats



and PSP122E Everything 'Stat®

Universal Replacement Deluxe Thermostats

Profile: Universally compatible Everything 'Stat[®] offering highly accurate, *fully programmable* temperature control of single or multistage heating and cooling systems.

Compatibility:

- Most 24V Heating and A/C Systems
- Up to 2 Stage Heat / 2 Stage Cool: Gas, Oil, or Electric (non Heat Pump) Systems
- Up to 3 Stage Heat / 2 Stage Cool: Heat Pumps
- 2 Wire Heat Only Hydronic Systems (Hot Water Baseboard & Radiator)
- 2 Wire Hydronic Air Handlers
- Millivolt Systems

Features:

•

- · Universal Compatibility
- Replaces Almost Every System Control
- Controls Auxiliary and Emergency Heat
- System Powered with Battery Backup, or Battery Powered (batteries included)
- Auto or Manual Changeover
- Adjustable 1-5 Minute A/C Compressor Delay
- Emergency and Auxiliary Heat Indicators
- Energy Usage Monitor
- Large, Hybrid Dot-Matrix Display
 Luxlight[®] EL (Electro Luminescent) Display
 - ⁻ LL (LICCUO LUIIIIIC
- Filter Monitor
- Clean Cycle[®] Programmable IAQ Intermittent Fan (Patent No. 6,988,671)

- Battery Free Memory For All Programs and Settings
- Advanced Keyboard Lockout
- User Programmable 3 Digit Lock Code
- Programmable High And Low Setting Limits
- Defeatable Audible Button Response
- Menu Driven Setup Done From The Front Panel
- Temperature Offset (User Calibration)
- Multi-Stage Adj. Temperature Differential
- Programmable Length Minimum Run Time
- Programmable Auto-Changeover Dead-Band
- Residual Fan Delay and Fan Overrun
- 0 and B Terminals
- 3-Year Warranty



PSPA711 Compatibility:

- Most 24V Heating and A/C Systems
- 1 Stage Heat / 1 Stage Cool: Gas, Oil, Electric, or Single Stage Heat Pump Systems
- 2 Wire Heat Only Hydronic
 Systems (Hot Water Baseboard & Radiator)
- 2 Wire Hydronic Air Handlers
- Millivolt Systems

Features:

- 7-Day Programming
- 4 Periods Per Day
- Auto or Manual Changeover
- Exclusive Lux Speed Dial[®] Makes
- Reprogramming Easy
- System or Battery Powered with Battery Free Memory Storage (batteries included)
- Keyboard Lockout
- Filter Monitor
- Temporary Temperature Override (Residential CAT24 Compliant)

PSPHA732 Compatibility:

- Up to 3 Stage Heat / 2 Stage Cool: Heat Pump Systems
- Will Operate Auxiliary and Emergency Heat

- Manual Hold
- Adjustable 2 or 5 Minute A/C Compressor Delay
- Energy Usage Monitor
- Luxlight[®] EL (Electro Luminescent) Display
- Clean Cycle[®] Programmable IAQ Intermittent Fan (Patent No. 6,988,671)
- 0 and B Terminals
- 3-Year Warranty

Auto Changeover Series

Deluxe Programmable Thermostats

Profile: Fully programmable, digital thermostat with auto changeover for control of single stage heating and cooling systems.



 Up to 2 Stage Heat / 2 Stage Cool: Gas, Oil, or Electric (non Heat Pump) Systems
 2 Wire Heat Only Hydronic

Systems

• 2 WIRe Heat Unity Hydronic Systems (Hot Water Baseboard & Radiator)

PSPA722 Compatibility:

Most 24V Heating and A/C

- 2 Wire Hydronic Air Handlers
- Millivolt Systems

LuxPro Deluxe Programmable Thermostats



Compatibility:

- Most 24V Heating and A/C Systems ٠
- 1 Stage Heat / 1 Stage Cool: Gas, Oil, Electric, or Single Stage Heat Pump Systems •
- . 2 Wire Heat Only Hydronic Systems (Hot Water Baseboard & Radiator)
- 2 Wire Hydronic Air Handlers •
- Millivolt Systems •

Features:

- 7-Day Programming
- 4 Periods Per Day
- Smart Recovery Selectable
- Large, Easy-to-Read, Display
- Manual Hold
- Touch Screen Lockout Code
- Adjustable 2 or 5 Minute Delay
 F / C Temperature Display
- Audible Keypad Entry Response

- Filter Monitor
- Luxlight® EL (Electro Luminescent) Display
- · Energy Usage Monitor
- Temporary Temperature
- Override
- 12 / 24 Hour Clock
- · System Powered with Battery Backup or Battery Powered
- (batteries included)
- 0 and B Terminals Battery Free Memory For All
- Programs and Settings
- 3-Year Warranty



PSP721U

7-Day Deluxe Programmable Thermostat

Profile: Easy to use programmable thermostat (each day of the week can be programmed separately) for heating and cooling systems.

Compatibility:

- Most 24V Heating and A/C Systems
- Up to 2 Stage Heat / 1 Stage Cool: Gas, Oil and Electric Systems
- Up to 2 Stage Heat / 1 Stage Cool Heat Pump Systems ٠
- Will Operate Auxiliary and Emergency Heat ٠
- 2 & 3 Wire Hydronic Systems (Hot Water Baseboard & Radiators)
- Millivolt Systems (Wall Heaters / Furnaces & Gas Fireplaces)

Features:

- · Each day can be programmed differently
- 3-Wire Zone Valve Compatible · 4 Periods per day - Morning,
- Day, Evening, Night
- Quick Copy Programming copy any daily program and repeat it on any other day(s)

Exclusive Lux[®] Speed Dial[®]

for easy programming

of the week

Lighted Display

Filter Monitor

- Programmable Keypad Lock (10,000 different codes)
 - Smart Recovery Selectable
 - Manual Hold
 - Temporary Temperature Override
 - Easy Installation

Πf 12:33Pt 01/27/07 LUXPRO

PSPU721T and PSPU732T Universal

Touch Screen, 7-Day Deluxe Programmable Thermostats

Profile: Easy to use programmable thermostat (each day of the week can be programmed separately for heating and cooling systems.

PSPU721T Compatibility:

- Up to 2 Stage Heat / 1 Stage Cool: Gas, Oil, and Electric Systems
- Up to 2 Stage Heat / 1 Stage Cool: Heat Pump & Dual Fuel Systems

PSPU732T Compatibility:

- Most 24V Heating and A/C Systems (with Common Wire)
- Up to 2 Stage Heat / 2 Stage Cool: Gas, Oil, and Electric Systems
- Up to 3 Stage Heat / 2 Stage Cool: Heat Pump & Dual Fuel Systems

Features:

- Large, dot-matrix TRUE TOUCH-SCREEN with adjustable contrast
- 7-DAY PROGRAMMABLE with 4 events per day and a COPY option for each day
- User Selectable Programmable or Non-Programmable (Manual) Operation
- · Patented ENERGY WATCH, monitors the KWh consumption and dollar cost of operating the HVAC system
- FILTER MONITOR feature indicates when to change the air filter
- INSTALLER MESSAGE provides a handy reminder for service or contact in case of a heating or cooling emergency
- SECURITY feature prevents operating thermostat without entering 4-digit PIN
- AUTOMATIC CHANGEOVER mode no need to manually switch between heating or cooling
- DEHUMIDIFICATION (PSPU732T only)
- AUTOMATIC HUMIDITY CONTROL (PSPU732T only) based upon outdoor temperature**
- DUAL FUEL capable switch-over to fossil fuel heating and increase energy efficiency and savings**

**(When used with the optional wireless temperature and receiver kit, Model No. WTR064)

OPTIONAL OUTDOOR WIRELESS TEMPERATURE TRANSMITTER AND RECEIVER KIT - Model No. WTR064

Accurately Displays Current Outdoor Temperature and Enables Dual Fuel Capability on the LUXPRO® PSPU721T / PSPU732T Thermostats

Developed by: AED Electronics, Inc. MADE IN CHINA PATENTS: 7, 185,825; 7, 156,318; 7,145,110; 7,050,026; 7,028,912; 6,902,117; 6,786,421;



The LuxPro[®] Promise

At Lux Products Corporation, we are dedicated to bringing our customers the best line of thermostats, today and well into the future. Our entire line of over thirty programmable, digital, and mechanical thermostats are designed to be a reliable, simple and precise part of our customers' lives, so that everyone can enjoy the benefits and comforts of advanced temperature control.



LuxPro Deluxe Programmable Thermostats



P621U

5-1-1 Day Deluxe Universal **Programmable or Non-Programmable Thermostat**

Profile: Easy to use programmable or non-programmable thermostat (separate Weekday, Saturday, and Sunday) for heating and cooling systems.

Compatibility:

- Universal Compatibility for Conventional Heat & A/C and Heat Pumps with Up to 2-Stage Heat / 1 Stage-Cool
- 2 & 3 Wire Hydronic Systems (Hot Water Baseboard & Radiator)
- Millivolt Systems (Wall Heaters / Furnaces & Gas Fireplaces)

Features:

- Weekdays, Saturday & Sunday Can Be Different (2 or 4 periods/day)
- · Large Display with Backlight
- Adjust. Heating and Cooling Limits
- Keyboard Lockout
- Comprehensive Graphical Filter Monitor
- Selectable Smart Recovery
- Dual Powered (2 AA Batteries Included)
- User Selectable Programmable or Non-Programmable (manual) Operation
- Manual Temperature Hold
- Temporary Temperature Override
- Adjustable Temp. Differential Cycle Rate
- Adjustable 2nd Heat Stage Offset Setting User Temperature Calibration (+/- 5°F
- degrees)
- 5 / 2 Minute Selectable Time Delay
- Battery Free Memory Storage
- 12 / 24 Hour Clock Display
- 3-Year Warranty



P521U

5-2 Day Deluxe Universal **Programmable or Non-Programmable Thermostat**

Profile: Easy to use programmable or non-programmable thermostat (separate weekday and weekend) for heating and cooling systems.

Compatibility:

- Universal Compatibility for Conventional Heat & A/C and Heat Pumps • with Up to 2-Stage Heat / 1 Stage-Cool
- 2 & 3 Wire Hydronic Systems (Hot Water Baseboard & Radiator) •
- Millivolt Systems (Wall Heaters / Furnaces & Gas Fireplaces)

Features:

- Separate Weekday and Weekend Programs (2 or 4 periods/day)
- · Large Display with Backlight
- Adjust. Heating and Cooling Limits
- Keyboard Lockout
- Programmable Air Filter Monitor
- Selectable Smart Recovery
- Dual Powered (2 AA Batteries Included)
- User Selectable Programmable or Non-Programmable (manual) Operation
- Manual Temperature Hold
- Temporary Temperature Override
- Adjustable Temp. Differential Cycle Rate
- Adjustable 2nd Heat Stage Offset Setting
- User Temperature Calibration (+/- 5°F degrees)
- 5 / 2 Minute Selectable Time Delay
- Battery Free Memory Storage
- 12 / 24 Hour Clock Display
- 3-Year Warranty



PSP511LC

5-2 Day Deluxe Programmable Thermostat

Profile: Easy to use programmable thermostat (separate weekday and weekend) for heating and cooling systems.

Compatibility:

- Most 24V Heating and A/C Systems
- 1 Stage Heat / 1 Stage Cool: Gas, Oil, Electric, or Single Stage Heat Pump Systems
- 2 Wire Heat Only Hydronic Systems (Hot Water Baseboard & Radiator)
- 2 Wire Hydronic Air Handlers

Features:

- Exclusive Lux Speed Dial® -Makes Reprogramming Easy • 5-2 Programming
- · Separate Weekday and
- Weekend Programming
- 4 Periods Per Day Separate Programs for
- Heating and Cooling Keyboard Lockout
- Manual Hold

I I IXPRO

- Large, Easy-to-Read, Liquid
 12 / 24 Hour Clock
- Crystal Display Luxlight[®] EL (Electro
- Luminescent) Display Soft Touch Buttons
- 5 Minute Compressor Delay • User Temperature
- Calibration
- Temporary Temperature Override
- F / C Temperature Display

- System or Battery Powered (batteries included)
- Battery Free Memory Storage
- On Screen Low Battery Indicator
- Programmable Filter Timer with Filter Change Indicator
- 0 and B Terminals
- 3-Year Warranty



PH521

5-2 Day Deluxe Programmable or Non-Programmable Thermostat

Profile: Easy to use programmable or non-programmable thermostat (separate weekday and weekend) for 1 or 2 stage heating and 1 stage cooling heat pump systems.

Temperature Hold

(service mode)

• Dual Fuel Operation

• 3-Year Warranty

• Temporary Temperature Override

Adjustable Temperature Swing 1-9

• Temporary Compressor Protection Bypass

• Temperature Calibration (+/- 5°F) Feature

4

Compatibility:

- Up to 2 Stage Heat / 1 Stage Cool: Heat Pump Systems
- Will Operate Auxiliary and Emergency Heat •

Features:

- Separate Weekday and Weekend Programs
- Preprogrammed 4 periods per day
- User Selectable Programmable or
- Non-Programmable (Manual) Operation
- Programmable (4 digits) keyboard lock
- Adjustable heat / cool temperature limits • Dual Power - 2 AA batteries included
- Backlight Display Celsius or Fahrenheit

LuxPro Digital Thermostats



PSD111 and PSDH121

Multi-Positional Heating and Cooling Thermostats

Profile: Multi-positional, Non-programmable digital thermostat.



Pro-Spec[™] Series System Powered **Digital Thermostats**

Profile: Digital Electronic Non-Programmable thermostat for heating and cooling systems.

PSD011W Compatibility:

- Most 24V Heating and A/C Systems (With Common Wire)
- 1 Stage Heat / 1 Stage Cool: Gas, Oil, Electric, or Single Stage Heat Pump Systems
- 2 Wire Heat Only Hydronic Systems (Hot Water Baseboard & Radiator)
- 2 Wire Hydronic Air Handlers

PSD011B Compatibility:

- Most 24V Heating and A/C Systems •
- Electric, or Single Stage Heat Pump Systems
- (Hot Water Baseboard & Radiator)
- 2 Wire Hydronic Air Handlers

PSDH021W Compatibility:

- (With Common Wire)
- Pumps

PSDH021B Compatibility:

- Most 24VAC Heat Pump Systems
- Single Stage and 2 Heat / 1 Cool: Heat Pumps

Features:

- Large LED Illuminated Digital Display
- Attractive Slim Design
- Adjustable Temperature Stops
- Soft Touch Buttons
- Default Set Temps: 65°F Heat / 78°F Cool
- F / C Temperature Display
- 5 Minute Delay
- Easy Installation
- Optional Wall Plate Available
- 0 / B Terminal
- 3-Year Warrantv
- "W" suffix models are system powered and require Common wire; "B" suffix models are battery powered (batteries included).

PSD010B Compatibility:

- 24V 2 Wire Heating Only Systems 1 Stage Heat Gas or Oil Systems With No Fan
- 2 Wire Heat Hydronic System (Hot Water, Baseboard & Radiator)
- Millivolt Systems (Wall Heaters / Furnaces & Gas Fireplaces)

PSD010BF Compatibility:

- Most 24V Heating Systems
- 1 Stage Heat Only: Gas, Oil or Electric (Non Heat-Pump) Systems
- 2 Wire Heat Only Hydronic Systems (Hot Water, Baseboard & Radiator)
- Millivolt Systems (Wall Heaters / Furnaces & Gas Fireplaces)

PSD022B Compatibility:

- Most 24V Heating and A/C Systems
- Up to 2 Stage Heat / 2 Stage Cool: Gas, Oil, **Electric Heating and Air Conditioning** Systems
- Single Stage Heat Pumps
- 2 Wire Heat Only Hydronic Systems (Hot Water, Baseboard & Radiator)
- Millivolt Systems (Wall Heaters / Furnaces & Gas Fireplaces)



1 Stage Heat / 1 Stage Cool: Gas, Oil, •

- 2 Wire Heat Only Hydronic Systems •

 - Millivolt Systems

Most 24V Heat Pump Systems

Single Stage and 2 Heat / 1 Cool: Heat

- Electronic Accuracy
- Large, Easy-to-Read Digital Display
- Luxlight[®] EL (Electro Luminescent) Display
- System or Battery Powered (batteries included)
- Optional Wall Plate Available

- Display Temperature User Calibration
- 3-Year Warranty

PSDH121 Compatibility: Up to 2 Stage Heat / 1 Stage Cool: Heat Pump Systems • Will Operate Auxiliary and Emergency Heat

•

Pump Systems

Millivolt Systems

- Features:
- Multi Positional Vertical or Horizontal Mounting

PSD111 Compatibility:

• 2 Wire Hydronic Air Handlers

• Most 24V Heating and A/C Systems

• 1 Stage Heat / 1 Stage Cool: Gas, Oil, Electric, or Single Stage Heat

2 Wire Heat Only Hydronic Systems (Hot Water Baseboard & Radiator)

- 5 or 2 Minute Delay
- Low Battery Indicator
- F / C Temperature Display
- 0 and B Terminals

LuxPro[®] Mechanical Thermostats



Compatibility:

- 1 Stage Heat Only: 2-Wire Gas or Oil Systems (PSM30SA)
- 1 Stage Heat / 1 Stage Cool: Gas, Oil, Electric, or Single Stage Heat Pump Systems (PSM40SA)
- Systems with Built In Time Delays (PSM40SA)
- 2 Wire Heat Only Hydronic Systems (Hot Water Baseboard & Radiator)
- 2 Wire Hydronic Air Handlers
- Millivolt Systems

PSM30SA and PSM40SA Mechanical Snap-Action Thermostats

Profile: Mechanical snap-action thermostats for heating and cooling systems.

Features:

• 3-Year Warranty

Clean Attractive Design

Snap-Action Mechanism

· Adjustable Heat Anticipator

• 0 and B Terminals (PSM40SA)

• PSM30SA Heating Only Snap Action

• PSM40SA 1 Heat / 1 Cool Snap Action



PSM400SA

Compatibility:

- 1 Stage Heat Only: 2-Wire Gas or Oil (non Heat Pump) Systems (PSM200SA)
- 1 Stage Heat / 1 Stage Cool: Gas, Oil, or Electric (non Heat Pump) Systems (PSM400SA)
- Systems with Built In Time Delays
- 2 Wire Heat Only Hydronic Systems (Hot Water Baseboard & Radiator)
- 2 Wire Hydronic Air Handlers
- Millivolt Systems

PSM200SA and PSM400SA Mechanical Snap-Action Thermostats

Profile: Mechanical snap-action thermostats for heating (PSM200SA) and heating and cooling (PSM400SA) systems.

Features:

- Horizontal Style
- Clean, Attractive Design
- Snap-Action Switch Mechanism
- Adjustable Heat Anticipator
- PSM200SA Heat Only
- PSM400SA Heating and Cooling
- 3-Year Warranty



PSMH45

Mechanical Thermostat 2 Stage Heat, 1 Stage Cool Heat Pump

Profile: Mercury bulb mechanical thermostat with adjustable second stage heat anticipator for 2 stage heat, 1 stage cool heat pump systems.

Compatibility:

- Up to 2 Stage Heat / 1 Stage Cool: Heat Pump Systems
- Will Operate Auxiliary and Emergency Heat

Features:

- Horizontal Style
- Clean Attractive Design
- Mercury Bulb Accuracy
- Adjustable, Second Stage Heat Anticipator
- Emergency Heat Position with Indicator Light
- Auxiliary Heat Indicator Light
- 3-Year Warranty



PSM010 and PSM011 Mechanical Thermostat

Profile: Non-Programmable thermostat for heating only systems.

Compatibility:

- Most 24V Heating and A/C Systems
- 1 Stage Heat / 1 Stage Cool: Gas, Oil, or Electric (Non Heat Pump) Systems (PSM011)
- 2 Wire Heat Only Hydronic Systems (Hot Water Baseboard & Radiator)
- 1 Stage Heat Only (PSM010)

Features:

- Push Button Back Light
- Soft Rubber Set Temperature Ring
- Large Easy To Use Mode Switch
- Easy Installation
- Needs No Batteries
- · Contains No Mercury
- 3-Year Warranty



LuxPro[®] Line Voltage Thermostats

LuxPro Locking Thermostat Guards



PSPLV512

Single or Double Pole Line Voltage Programmable Thermostat

Profile: Easy-to-use programmable thermostats (weekday and weekend programming) for line voltage heating systems.

Compatibility:

- 1 Stage Heat Only: 120/240 VAC Single or Double Pole Applications
- · Baseboard, Ceiling Cable and Other Radiant Heating Systems

Features:

- Exclusive Lux Speed Dial® -Makes Reprogramming Easy
- Weekday and Weekend Programming
- Heat On / Off Switch • 4 Periods Per Day
- Large, Easy-to-Read Display Manual Hold
- Temporary Temperature Override System Cycle Adjustment
- 3-Year Warrantv



LV1, LV2 and LV3 Line Voltage Mechanical Thermostats

Profile: Mechanical thermostats for line voltage heating and cooling systems.

Compatibility:

- 1 Stage Heat Only: Single Pole 120/240 VAC Systems (LV1)
- 1 Stage Heat Only: Double Pole 120/240 VAC Systems (LV2)
- 1 Stage Cool Only: Single Pole 120/240 VAC Systems (LV3)

Features:

- Contains No Mercury · Easy to Install and Use
- Clean Attractive Design
 • 3-Year Warranty



PSP300

5-2 Day Programmable **Outlet Thermostat**

Profile: Easy to use programmable outlet thermostat for window air conditioners and portable space heaters.

Compatibility:

- Window Air Conditioners 120 VAC, 15 Amp Plug
- Electric Space Heaters 120 VAC, 15 Amp Plug

Features:

- Designed for Window Air Conditioners and Portable Space Heaters - 120 Volt 15A Units
- 4 Periods Per Dav
- ETL Approved

I I IXPRO

- Exclusive Lux Speed Dial[®] -Makes Reprogramming Easy
- 120VAC Outlet Powered
- 3-Year Warranty



BB2001-005

9½" (240 mm) wide/width 5³/₄" (146 mm) tall/height 4" (100 mm) deep/depth



BB3001-004

63/4" (172 mm) wide/width 5⁷/₆" (149 mm) tall/height 31/4" (83 mm) deep/depth

BB2001-005 (small), BB3001-004 (large)

Locking Thermostat Guards

Whether your customer is looking for additional assurance or needs to deter tampering with settings, thermostat locking guards provide the protection desired. Made of strong, durable plastic, these guards come in two sizes to fit all thermostats. Perfect for applications such as offices, rental properties and warehouses, the LuxPro thermostat guards limit unwanted access and eliminate accidental fluctuations when someone bumps into the thermostat.

Features:

- · Fits All Thermostats
- Two Sizes
- Limits Unwanted Access
- One Key Included
- Tamper Resistant
- Strong, Durable Plastic



7

	1 1	I I IV DDD THERMOSTATS	PI	Pro-Fit Series	t Seri	ies			D	Deluxe	Program		mable						Dig	Digital						W	Mechanical	nical				Line	Line Voltage	ane	
		System Specifications & Operational Features							PSPU732T	N127929					PH521	LLLOSA	121HO29											A2004M29	OLOM29	LIOMSA	PSPLV512	IVI	ras	ГЛЗ	b2b300
		Orientation - Horizontal (H), Vertical (V) Either Vertical or Horizontal Orientation							т	т						×	×											т			>	>	>	>	>
		Shape - Square (S), Round (R) Gas, Oil (Fumace or Boiler)	×>				× :		××	××	×:				S	×:		×:	×:			++	++		S X			×:	<u>د</u> ×	<u>د ×</u>					
		electric Forced Air Furnace Multi-Stage Heat Pump	< ×						<	< ×	< ×			~	×	~	×	~	×	×	×					~		~		~					
		Single-Stage Heat Pump Gas / Electric Fan Option	× ×	-		+	-	+	××	××	××	_	+	××	××	××	×	××	××	×	+	+	+	-	+	××		×							
		Millivolt Systems Window A/C and Space Heater Control	×		×	×	×			×	×			×		×			×					~	×		×	×							$ $ $ $ \times
		1 Cool-only 1 Hord Solo	×>			×	×>		×>	×>	×>			×>		×>		×>	×>	$\left \right $								×>	>	×>	>	>	>	×	\times
		1 Heat-Ully 1 Heat /1 Cool	< ×	+		+	-	+-	< ×	< ×	< ×	< < ×	< ×	< ×	×	< ×	×	< ×	+	+	×	<	+		-	+	-	< ×	<	< ×	<	<	<		<
		2 Heat / 1 Cool 2 Heat / 2 Cool	× ×	××		_		+	××	×	×	+	×		×		×			+	×	+	$\frac{1}{1}$		+	_	_								
		3 Heat / 2 Cool Switch Tune - Mercury (M) Snan Artion (SA)	×	×		×			×															2				ΔS	ΔS	ΔS					
		Relay Outputs	×	++	+	+			×	×	×	+	+	+	×	×	×	×	+	+	+	×	+		+	+	+	5	5	5					
		0 & B Terminals Auxiliary Heat Indicator	× ×			_			××	××	××	_	_		××	×	××	×			××		$\frac{1}{1}$			×									
		Emergency Heat Indicator	×	×		×		\times	×	\times	×		×		×		×		\square					×											
		Heat Pump Lockout 7 Day Programming	×		^ ×	×	×	××	××	×																									
		5-1-1 Day Programming		\square	$\left \right $	$\left \right $					×	>	>	>	>		Ħ	\square	$\left \right $	$\left \right $	$\left \right $	$\left \right $			$\left \right $										
	1 1	9-2 Day Fruglamming Special Program Feature			-	+						<	<	<	<						+	+			_										
	Implementation Imple	Title 24 - Residential (R), Commercial (C) System or Battery Powered / Backin	<u>ه</u> ×	\vdash	\vdash	\vdash		\vdash	œ	œ ×	\vdash	\vdash	\vdash	\vdash	œ ×	×	×														æ				æ
		Battery Powered Only	<	+	-	-	-			-	+	-	+	-		<	:			×		-	+	~	-						×				
	into	System Powered Only Batterv Backup		+	+	+		×	×		+	+							+	+	×	+			_										×
		Line Voltage 120 / 240 VAC		\square	$\left \right $	$\left \right $												\square	\square		\square	+			+						×	×	×	×	>
		Comfort & Convenience Features																																	<
		Auto- Changeover	×	_		_		_	×																										
		Preprogrammed Speed Dial® / Speed Slide™ Reprogramming	××		+	+	-	+	×	××	××	~ × × ×	× ×	××	××																××				××
		Touch Screen Reprogramming	>			\vdash			×>	>	>				>	>	>	>	>	>											>				>
	Image: constrained by the constrated by the constrained by the constrained by	Large Full Dot Matrix Display	<	++	+	+	-	+	< ×	<	<	+	+		<	< ×	< ×	<	<	<	+	+	+								<				<
		Large Hybrid Dot Matrix Display Luxlinht® FL (Flectro Luminescent) Display	× ×	× ×	×	×	××			×	××	×	××			×	×				-	+	_		_										
			<	+	+	+		+	×	<	<	<	<	×	×	<	<	+	+	+	+	+	+						×	×					
		°F / °C Selectable 12 / 24 Hour Clock	× ×	+	-	+	-	+	××	××	××		-	××	××	×	×	+	+	+	+	+	+		_						××				×
		Adjustable Temperature Differential	×	+	\vdash	+		+	×>	×	×		+	×	×	×	×	\square	\square	\square											\times				×
		Unsplays helative nummury Humidification							< ×																										
	x x	Dehumid fification Smart Recovery Selectable	×			_			×	×	×		×	_	×																				
		Programming Copy Feature	×	\mathbb{H}		\mathbb{H}	+	\mathbb{H}	×	\times	\times		\mathbb{H}	\mathbb{H}	\times								\mathbb{H}								:				
x x	I I	Low battery Indicator Battery Free Memory Storage	× ×	_		+	××	×	×	××	××		+	××	××	×	×		×	×	×	×	_		_						××				××
1 1	Image: Contract of the contract	Energy Monitor Either Monitor and Indirator	×>				× >	× >	~ >	>	>	>	>																						
x x	x x	Audible Keypad Entry Response	< ×	×	+	+	+	+	< ×	<	<	<	<									+			+										
	X X	Daylight Savings Time Button Manual Temperature Hold	× ×		-	+	-	+	×	×	×	×	×	×	×							+	_		_						×				×
x x	Image: Contract of the contract	Temporary Temperature Override	< × :			+	+	+	< × :	< ×	< ×		< ×	< ×	\times																~				$\langle \times $
Image: Network in the sector of the secto		Adjustable Vacation Hold Custom Installer Message	×					××	× ×																_										
	Bleek X <td>Optional Outdoor Wireless RF Sensor Maximum Host Tommorature Setting</td> <td>></td> <td>></td> <td>$\left \right$</td> <td>$\left \right$</td> <td></td> <td>×</td> <td>×</td> <td></td> <td>></td> <td>\square</td> <td>></td> <td></td> <td>></td> <td></td> <td></td> <td>></td> <td> ></td> <td> ></td> <td>+</td> <td>\square</td> <td>+</td> <td></td> <td>\square</td> <td></td>	Optional Outdoor Wireless RF Sensor Maximum Host Tommorature Setting	>	>	$\left \right $	$\left \right $		×	×		>	\square	>		>			>	>	>	+	\square	+		\square										
X X	X X	Minimum Cool Temperature Setting	< >	< >	+	+					< >	+	< >	+	< >			< >	<	<	+	-	-		-										
Result X <td>Break X<td>Programmable Fan Control</td><td>××</td><td>+</td><td>+</td><td>+</td><td></td><td>+</td><td>××</td><td></td><td>; ;</td><td></td><td></td><td>+</td><td>; ></td><td></td><td></td><td>;</td><td>;</td><td>;</td><td>:</td><td>+</td><td></td><td></td><td>\square</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td>	Break X <td>Programmable Fan Control</td> <td>××</td> <td>+</td> <td>+</td> <td>+</td> <td></td> <td>+</td> <td>××</td> <td></td> <td>; ;</td> <td></td> <td></td> <td>+</td> <td>; ></td> <td></td> <td></td> <td>;</td> <td>;</td> <td>;</td> <td>:</td> <td>+</td> <td></td> <td></td> <td>\square</td> <td></td>	Programmable Fan Control	××	+	+	+		+	××		; ;			+	; >			;	;	;	:	+			\square										
Break X X X X Y <td>Break X<td>reypau Lock Programmable Keypad Lock</td><td>× ×</td><td>+</td><td>+</td><td>+</td><td></td><td></td><td>× ×</td><td></td><td>~</td><td>×</td><td>×</td><td>~</td><td>~</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td>	Break X <td>reypau Lock Programmable Keypad Lock</td> <td>× ×</td> <td>+</td> <td>+</td> <td>+</td> <td></td> <td></td> <td>× ×</td> <td></td> <td>~</td> <td>×</td> <td>×</td> <td>~</td> <td>~</td> <td></td>	reypau Lock Programmable Keypad Lock	× ×	+	+	+			× ×		~	×	×	~	~																				
		Progr. Heat / Cool Fan Delay on Make / Break Short Crole Protection / Event Value)	×	×	+	+		>	>		+	>		>	>	1	>	+		>					+	+	_	_			>		1	1	>
	X X X X X X X X X X X X X	Short Cycle Protection (1.55 min. Selectable)	×	-	_	-		<	<		×	<	×	<	<	×	<		<	<	<	<	<	_	-	-					<			\top	<