

Product Specifications

Style #GPD700



Salt & pepper,
13-gauge, HPPE
fiber blended
shell with black
NitriX® Grip
Technology
palm coating,
ANSI Cut Level 2

MAGID® D-ROC® SEAMLESS MACHINE KNIT GLOVES

PRODUCT DESCRIPTION

Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	High performance polyethylene (HPPE) fiber blended shell; NitriX® Grip Technology sandy nitrile palm coating
Color(s)	Salt & pepper shell; black palm coating
Size(s)	6 - 12
Cuff/Finish	Color-coded elasticized overcast: white (6), green (7), brown (8), yellow (9), black (10), grey (11), blue (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)

FEATURES & BENEFITS

- Cool and breathable HPPE fiber blended shell provides excellent dexterity and flexibility
- NitriX® Grip Technology palm coating ensures a solid, secure grip in wet or dry applications
- Dark color hides dirt and grime to extend wear
- Color-coded overcast acts as a visual aid for sizing
- Elasticized finish on cuff reduces fraying
- Machine washable for longer service life
- ANSI Level 2 Cut Resistance and ANSI Level 6 Abrasion Resistance

APPLICATIONS

Assembly, machining, automotive manufacturing, metal handling, maintenance and construction

AVAILABLE STYLES

Size	6	7	8	9	10	11	12
Part Number	GPD7006	GPD7007	GPD7008	GPD7009	GPD70010	GPD70011	GPD70012

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	Result	ANSI Level
ASTM F-1790-97 Cut Resistant	-	593 grams	2
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	>20,000 revolutions	6

European Standard: EN 388:2003 Protective Gloves Against Mechanical Risks

Test Method	Clause	Result	EN Level
Blade Cut Resistance	6.2	8.5 cut index	3

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.

Definitions	Critical Defects: Imperfections which will result in the failure of the glove to perform its intended purpose. (AQL- 1.0%)
	Major Defects: Imperfections which may result in the failure of the glove to perform its intended purpose, cause user discomfort or be cosmetically objectionable. (AQL- 2.5%)
Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.

Originator	Efi Vrshek	Date	02/14/2013	
Revised By		Date		Revision #



**Magid Glove & Safety
Manufacturing Company LLC**
2060 North Kolmar Avenue • Chicago, IL 60639
Call toll-free: 800.444.803

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.