

LS 300



UV-RESISTANT LINE SET TAPE



TYPICAL APPLICATIONS

- For taping outdoor HVAC components

PRODUCT FEATURES

- UV-resistant
- Easy to unwind
- Economical
- Can be applied in a variety of temperature ranges and used in humid conditions

CONSTRUCTION

Overall Grade/Function: HVAC

Backing: BOPP film black with white print

Adhesive: Acrylic-based

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

US Green Building Council – LEED® Point contributor product

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



**BLACK PRINTED
(BPT)**

PHYSICAL PROPERTIES

STANDARD

METRIC

Tensile Strength	37 lbs/in width	64.8 N/10 mm
Adhesion to Stainless Steel	35 oz/in width	3.83 N/10 mm
Thickness	2.85 mils	0.07 mm
Elongation	180%	180%
Service Temperature Range	-35 F to 210 F	-37 C to 99 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

