

Description: 18 AWG 8/C CL2P Thermostat  
Compliance: UL Standard 13; NEC Article 725

#### Construction:

Conductors 18 AWG Solid Bare Copper  
No. of Conductors 8  
Assembly Tubed jacket over cabled insulated conductors

#### Insulation

Type Plenum PVC  
Color Red, Wht, Grn, Blu, Ylw, Brn, Org, Blk  
Thickness 0.006" nom.  
Diameter 0.052" nom.  
Cable Lay Length 6.0" nom

#### Jacket

Type Plenum PVC  
Color Beige  
Thickness 0.015" nom.  
Diameter 0.204" nom.  
Legend (Ink Print)

HONEYWELL THERMOSTAT CABLE P/N 4766 8C18 3038058 (ETL) CL2P (RoHS)  
C(UL) FT6 w/o# XXXXXX-XXXXXX XXXXXFT

#### Packaging

4 x 250' Reels, or 1 x 500' Reel or Box

#### Properties

Temperature Rating -20 to 60 °C  
Operating Voltage 300 Volts max.  
Capacitance 39 pf/ft nom.  
Characteristic Impedance 55 Ohms nom.  
DC Resistance 6.5 Ohms/M' at 20°C  
Flame Rating UL 910, NFPA 262, C(UL) FT6