

SPINALCORD™ Jacketed Metal Clad Mini Split Cable

Part Number: 1075

Description 14 AWG 4 Stranded THHN/THWN Conductors, Metal Cladded with Jacket

Ratings Type MC, Direct Burial, Sunlight Resistant, Oil Resistant I

Approvals UL Listed

Construction

Conductor Type 14 AWG 7 Strand Bare Copper

Conductor Count 4

Insulation Colors Black, White, Red, Green

Insulation Type PVC w/ Nylon

Insulation Thickness PVC: 0.015" nom.

Nylon: 0.005" nom.

Armor Type Aluminum interlocking armor

Armor Outer Diameter 0.473" nom.

Jacket Material PVC

Jacket Thickness 0.050" nom.

Overall Outer Diameter 0.574" nom.

Flame Rating UL 1569

Print Legend HONEYWELL #1075 – SPINALCORD™ MINI SPLIT CABLE 14 AWG 4C THHN/THWN E189204
(UL) TYPE MC 600V DIR BUR SUN RES OIL RES I (RoHS) W/O# DD/MM/YYYY

Electrical & Environmental

Temperature -20°C to 90°C Dry / 75°C Wet

Voltage 600V max.

RoHS Compliant Yes

Packaging & Colors

Standard Packaging 250' Reel

5 x 50' Coils in a box

Standard Color(s) Black

Other packaging and color options available at <http://www.honeywellcable.com>