

# THREAD SEALANTS

## LEAK-TITE® BLUE

### Economical Thread Sealant with PTFE



- Contains PTFE particles for greater sealing power
- Will not harden or dry out over time; remains flexible for easy disassembly
- Non-toxic, contains no solvents
- Sticks to hot, oily threads
- Ideal for use on production lines and fabrication shops
- Easy clean-up, will not stain hands or clothing
- For use on metal and PVC plastic pipe threads
- For sealing water, air, steam, natural gas, refrigerants, gasoline and ammonia
- Do not use on oxygen service; use Slic-tite® PTFE thread tape or OXY-TITE® paste
- Sealing temperature: -50°F to 500°F (-45°C to 260°C)
- Pressures: to 1,500 PSI (102 BAR) for gas, to 5,000 PSI (340 BAR) for liquid
- No V.O.C.'s



| PART NO. | SIZE        | CASE QTY. |
|----------|-------------|-----------|
| 46009    | 1/4 pt. BIC | 24        |
| 46029    | 1 pt. BIC   | 24        |
| 46013    | 1 qt.       | 12        |
| 46049    | 1 qt. BIC   | 12        |
| 46069    | 55 gal.     | 1         |

BIC = Brush in Cap



## PIPETITE® PASTE

### Soft Set Pipe Thread Compound




- Soft set pipe thread compound
- For refrigerants, butane, gasoline, oil, as well as water, steam, air, natural gas and LP gas
- Use on metal threads
- Do not use on oxygen service; use Slic-tite® PTFE thread tape or OXY-TITE® paste
- Sealing temperature: up to 400°F (204°C)
- Pressures: to 2,600 PSI (177 BAR) for gas, to 5,000 PSI (340 BAR) for liquid
- No V.O.C.'s



| PART NO. | SIZE        | CASE QTY. |
|----------|-------------|-----------|
| 12109    | 1/4 pt. BIC | 24        |
| 12110    | 1/2 pt. BIC | 24        |
| 12112    | 1 pt. BIC   | 24        |

BIC = Brush in Cap



## T-O-T®

### Pipe Thread Compound



- No-drip, siliconized for fast application on metal threads
- For water, steam, air and natural gas service
- Lead-free, non-toxic
- Do not use on oxygen service; use Slic-tite® PTFE thread tape or OXY-TITE® paste
- Sealing temperature: up to 350°F (177°C)
- Pressures: to 350 PSI (24 BAR) for gas, to 500 PSI (34 BAR) for liquid
- No V.O.C.'s



| PART NO. | SIZE        | CASE QTY. |
|----------|-------------|-----------|
| 12219    | 1/2 pt. BIC | 24        |
| 12208    | 5 lb.       | 6         |

BIC = Brush in Cap



# THREAD SEALANTS

## OXY-TITE®

### Pipe Thread Sealant for Oxygen

- PTFE thread sealant for oxygen services
- Each batch tested to ASTM G-72
- Pressure: to 2,600 PSI (180 BAR)

- Sealing temperature: -320°F to 450°F (-196°C to 232°C)
- No V.O.C.'s



| PART NO. | SIZE  | CASE QTY. |
|----------|-------|-----------|
| 42805    | 4 oz. | 6         |



## PIPETITE-STIK®

### Soft Set Pipe Thread Compound



- Certified by NSF to meet ANSI/NSF Std. 61 for use on potable water
- Thread compound in handy stick form
- For water, steam, air, natural gas and LP gas
- Use on metal threads
- Classified by Underwriters Laboratories, U.S.A
- Non-toxic, lead-free

- Do not use on oxygen service; use Slic-tite® PTFE thread tape or OXY-TITE® paste
- Sealing temperature: up to 350°F (177°C)
- Pressures: to 350 PSI (24 BAR) for gas, to 2,000 PSI (136 BAR) for liquid



| PART NO.                    | SIZE      | CASE QTY. |
|-----------------------------|-----------|-----------|
| Standard Size               |           |           |
| 11175                       | 1-1/4 oz. | 144       |
| King Size Dozen Display Box |           |           |
| 11176                       | 4 oz.     | 72        |



## PLASTO-JOINT STIK®

### Plastic Thread Sealant

- Pipe thread compound in handy stick form
- For use on ABS, PVC, and CPVC plastic pipe and fittings and on metal threads

- Do not use on oxygen service; use Slic-tite® PTFE thread tape or OXY-TITE® paste
- Sealing temperature: up to 250°F (121°C)

- Pressures: to 300 PSI (20 BAR) for gas, to 500 PSI (34 BAR) for liquid
- Ideal for pool and spa installation



| PART NO.           | SIZE      | CASE QTY. |
|--------------------|-----------|-----------|
| Dozen Display Pack |           |           |
| 11775              | 1-1/4 oz. | 144       |
| 13675              | 1-1/4 oz. | 36        |



## Slic-tite® STIK WITH PTFE

### Thread Sealant in a Stick



- High-performance thread compound in handy stick form
- Contains PTFE particles for greater sealing power
- Non-toxic, non-staining, non-drying
- Designed for professional servicemen and tradesmen
- Clean – white-washes off easily
- Use on metal and PVC pipe thread connections for water, air, natural gas, steam, gasoline, oil, refrigerants and ammonia

- Do not use on oxygen service; use Slic-tite® PTFE thread tape or OXY-TITE® paste
- Sealing temperature: -50°F to 350°F (-46°C to 177°C)
- Pressures: to 500 PSI (34 BAR) for gas, to 5,000 PSI (340 BAR) for liquid



| PART NO.           | SIZE      | CASE QTY. |
|--------------------|-----------|-----------|
| Dozen Display Pack |           |           |
| 41600              | 1-1/4 oz. | 24        |

