RECEIVERS

Refrigeration Research Receivers have been made continuously for over 50 years. They are used widely by original equipment manufacturers throughout the industry. They are backed by a reputation for quality and service.

Available in a broad range of types and sizes, these receivers with valves and fittings attached are hydrogen brazed for cleanliness and pressure tested for reliability. A 430°F Fusible plug is installed on all receivers except #2030, #2039, and #9028. All valves are supplied with steel stem caps with copper gaskets and brass flare nuts and caps. All receivers are powder coated for excellent corrosion resistance. Pressure tested for 500 p.s.i. maximum working pressure.

Type 1		*PUMP	DIAMETER & LENGTH			WT.	(ŲL)
-	PART NUMBER	DOWN CAPACITY	OVER END CAPS	INLET	OUTLET	LBS.	CODE Indent.
	2030	2 lb.	3 x 10	1/4 ID Sweat	1/4 ID Sweat	2.4	HN
	2039	1.5 lb.	3 x 7	1/4 ID Sweat	1/4 ID Sweat	2	HN
Vertical Mount							
Type 2							
Horizontal Mount	<u>•</u> 1947	3 lb.	3 1/2 x 9	3/8 ID Sweat	3/8 SAE Valve	3.3	PN
Type 3	5774	2 lb.	3 x 10	1/4 SAE Fitting	1/4 SAE Valve	3	HN
71	9028	2 lb.	3 x10	1/4 ID Sweat	1/4 ID Sweat Valve	3	HN
	1920	2 lb.	3 1/2 x 7 1/2	1/4 SAE Fitting	1/4 SAE Valve	2.9	PN
	1917	3 lb.	3 1/2 x 10	1/4 SAE Fitting	1/4 SAE Valve	3.5	PN
	9017	3 lb.	3 1/2 x 10	1/4 ID Sweat	1/4 ID Sweat Valve	3.5	PN
	1921	4 lb.	4 x 10	1/4 SAE Fitting	1/4 SAE Valve	4.5	KN
	9021	4 lb.	4 x 10	1/4 ID Sweat	1/4 ID Sweat Valve	4.5	KN
	1918	6 lb.	5 x 10	1/4 SAE Fitting	1/4 SAE Valve	7.2	DN
	5315	6 lb.	5 x 10	3/8 SAE Fitting	3/8 SAE Valve	7.3	DN
	6848	6 lb.	5 x 10	3/8 ID Sweat	3/8 ID Sweat Valve	7.3	DN
	1911	10 lb.	6 x 12	3/8 SAE Fitting	3/8 SAE Valve	10.9	MN
	6801	10 lb.	6 x 12	3/8 ID Sweat	3/8 ID Sweat Valve	10.9	MN
	3212	16 lb.	6 x 18	1/2 SAE Fitting	1/2 SAE Valve	15.6	MN
Vertical Mount	9027	16 lb.	6 x18	1/2 ID Sweat	1/2 ID Sweat Valve	15.6	MN
	3213	22 lb.	6 x 24	1/2 SAE Fitting	1/2 SAE Valve	18	MN
Type 4	1916	8 lb.	4 x 19	1/4 Sweat	1/4 SAE Valve	7.5	KN
	1915	12 lb.	5 x 18	1/4 Sweat	3/8 SAE Valve	11.4	DN
Horizontal Mount	1919	19 lb.	5 x 28	3/8 Sweat	3/8 SAE Valve	16.6	DN
Type 5	1922	15 lb.	5 X 23	3/8 Sweat	3/8 SAE Valve	14.5	DN
Horizontal Mount	№ 1923	15 lb.	5 x 23	1/2 Sweat	1/2 SAE Valve	15	DN
nonzontai wount							

*90% AT 90° for R22, R134a and R502 - For R12 multiply by 1.1 - For R402b and R404a multiply by 0.9 500 psi Working Pressure

<u>y</u> <u>(4)</u>

U LISTED

