

Factory Number	Model Number	Uni-Line Number	BTU	Regulator Size	Inlet/Outlet Size	Actuator Type	Pilot Outlet	Temperature Range	Capillary Length	Comments
110ER	1-010-300	120-402	75K	3.5 NAT	1/2" X 3/8"	24V AC	1/4"			OBSOLETE -REPLACEMENT 720-007
110ERCHC	43-132-641	120-407	100K	Convertible	1/2" X 3/8"	24V AC	1/4"			OBSOLETE -REPLACEMENT 720-007
110ERCHC20-2E	58120	120-472	80K	Convertible	1/2" X 3/8"	24V AC	1/4"			OBSOLETE -REPLACEMENT 720-472
110ERCHCS0-2C	58316	120-474	80K	Convertible	1/2" X 3/8"	24V AC	1/4"			OBSOLETE -REPLACEMENT 720-474
110ERCHCSO-2D	58312	120-473	80K	Convertible	1/2" X 3/8"	24V AC	1/4"			OBSOLETE -REPLACEMENT 720-474
110S	40-000-241	120-204	85K	None	1/2" X 3/8"	Hydraulic	1/4"	78 - 110 ° F	36"	BROODER/SPA;REPLACES O.E.M.#40-00-0241
110S	1-411-200	120-201	85K	None	1/2" X 3/8"	Hydraulic	1/4"	58 - 90 ° F	36"	REPLACES DAY AND NIGHT 01-0228:SPACE HEATING.
110S	1-421-108	120-200	85K	None	1/2" X 3/8"	Hydraulic	1/4"	78 - 110 ° F	18"	BROODER/SPA-HAS SPECIAL MOUNTING HOLES
110SR	75-037-013	120-202	85K	4.0 NAT	1/2" X 3/8"	Hydraulic	1/4"	58 - 90 ° F	36"	THIS VALVE NO LONGER HAS REGULATOR.
110SS	69-436-425	120-203	85K	None	1/2" X 3/8"	Hydraulic	1/4"	36 - 68 ° F	36"	
220RLPTS8P	75-104-103	110-286	100K	10.0 LP	1/2" X 1/2"	THERMOCOUPLE	1/4"	180 ° F		1/2" I.F. OUTLET.FOR COMMERCIAL APPLICATIONS ONLY.
220RLPTS8P	75-138-104	110-285	100K	10.0 LP	1/2" X 1/2"	THERMOCOUPLE	1/4"	180 ° F	1-1/2"	1/2" I.F. COMMERCIAL APPLICATIONS ONLY
220RLPTS8P	80-138-104	110-280	100K		1/2" X 1/2"	THERMOCOUPLE	1/4"	180 ° F	1-1/2"	
220RLPTSP	80-137-036	110-262	100K	10.0 LP	1/2" X 1/2" RH THREAD	thermocouple	1/4"	160 ° F	1 -3/8"	1/2" INVERTED FLARE OUTLET
220RLPTSP	75-140-036	110-270	100K	10.0 LP	1/2" X 1/2"	THERMOCOUPLE	1/4"	160 ° F	1-3/4"	1/2" I.F. OUTLET:
220RLPTSP	75-144-036	110-267	100K	10.0 LP	1/2" X 1/2"	THERMOCOUPLE	1/4"	160 ° F	2-3/8"	1/2" I.F. OUTLET
220RLPTSP	75-938-034	110-266	85K	10.0 LP	1/2" X 3/8"	THERMOCOUPLE	1/4"	160 ° F	1-1/2"	3/8" I.F. OUTLET
220RLPTSP	75-137-036	110-265	100K	10.0 LP	1/2" X 1/2" LH THREAD	THERMOCOUPLE	1/4"	160 ° F	1-3/8"	1/2" I.F. OUTLET
220RTSP	75-607-006	110-202		4.0 NAT	1/2" X 1/2"	THERMOCOUPLE	1/4"	160 ° F	1-3/8"	INVERTED FLARE OUTLET-UNIKIT
7000AE	324-505-516	700-407	100K	None	1/2" X 1/2"	24VAC 12VDC	1/4"			REWORKED VALVE
7000AER	324-501-517	700-408	100K	3.5 NAT	1/2" X 1/2"	24VAC 12VDC	1/4"			REWORKED VALVE
7000AERB-3-LP-S7C	4G0-507-879	700-435	100K	2.8" to 11" LP	1/2" X 1/2"	24VAC 12VDC	1/4"			REWORKED VALVE
7000AERB-5-S7C	4G0-506-927	700-434	100K	2.0" to 4.0" NAT	1/2" X 3/4"	24VAC 12VDC	1/4"			
7000AERC	321-503-514	700-419	100K	Convertible	1/2" X 1/2"	24VAC 12VDC	1/4"			REWORKED VALVE
7000AGO	314-545-000	700-811	100K	None	1/2" X 1/2"	Hydraulic	1/4"			REWORKED VALVE
7000AGOR	314-541-001	700-812	100K	3.5 NAT	1/2" X 1/2"	Hydraulic	1/4"			
7000AM	4E5-000-012	700-101	100K	None	1/2" X 1/2"	Hydraulic	1/4"			INCLUDES 1/2X 3/8"BUSHINGS(2)
7000AMR	324-001-013	700-102	100K	3.5 NAT	1/2" X 1/2"	Manual	1/4"			REWORKED VALVE. Includes 3/4 X 1/2 bushings (2)
7000AMSGO	335-545-000	700-881	100K	None	1/2" X 1/2"	Millivolt	1/4"			REWORKED VALVE
7000AMSGOR	335-541-151	700-882	100K	3.5 NAT	1/2" X 1/2"	Millivolt	1/4"			
7000AMSGOR-LP	335-542-167	700-888	160K	11" LP	1/2" X 1/2"	Millivolt	1/4"			
7000AMV	358-705-440	700-509	100K	None	1/2" X 1/2"	Millivolt	1/4"			REWORKED VALVE
7000AMV	344-815-401	700-501	100K	None	1/2" X 1/2"	Millivolt	1/4"			
7000AMVR	344-811-400	700-502	100K	3.5 NAT	1/2" X 1/2"	Millivolt	1/4"			HAS COAXIAL THERMOPILE CONNECTION
7000AS	314-325-199	700-215	100K	None	1/2" X 1/2"	Snap Action Hydraulic	1/4"	110-180 ° F	36"	includes 2 reducer bushings 1/2" x 3/8"
7000AS	4E5-325-015	700-201	100K	None	1/2" X 1/2"	Snap Action Hydraulic	1/4"	58 - 90 ° F	36"	(2) 1/2"x3/8" bushings
7000AS-1H	4E5-375-607	700-209	100K	None	1/2" X 1/2"	Snap Action Hydraulic	1/4"	45 - 95 ° F	18",48"	
7000ASR	4E5-321-014	700-202	100K	3.5 NAT	1/2" X 1/2"	Snap Action Hydraulic	1/4"	58 - 90 ° F	36"	

Factory Number	Model Number	Uni-Line Number	BTU	Regulator Size	Inlet/Outlet Size	Actuator Type	Pilot Outlet	Temperature Range	Capillary Length	Comments
7000ASR-1H	4E5-371-606	700-210	100K	3.5 NAT	1/2" X 1/2"	Snap Action Hydraulic	1/4"	45 - 95 ° F	18",48"	
7000ASR-LP	4E5-322-145	700-216	160K	10" LP	1/2" X 1/2"	Snap Action Hydraulic	1/4"	58 - 90 ° F	36"	
7000AST-3	4E5-220-015	700-203	100K	None	1/2" X 1/2"	Snap Throttle Hydraulic	1/4"	58 - 90 ° F	36"	Use on Natural Gas Only
7000AST-3-1H	4E5-270-607	700-206	100K	None	1/2" X 1/2"	Snap Throttle Hydraulic	1/4"	45 - 95 ° F	18",48"	Use on Natural Gas Only
7000AST-LP-3	4E5-224-015	700-204	160K	None	1/2" X 1/2"	Snap Throttle Hydraulic	1/4"	58 - 90 ° F	36"	
7000AST-LP-3-1H	4E5-274-607	700-207	160K	None	1/2" X 1/2"	Snap Throttle Hydraulic	1/4"	45 - 95 ° F	18",48"	
7000ASTR-3	4E5-221-014	700-205	100K	None	1/2" X 1/2"	Snap Throttle Hydraulic	1/4"	58 - 90 ° F	36"	
7000ASTR-3-1H	4E5-271-606	700-208	100K	3.5 NAT	1/2" X 1/2"	Snap Throttle Hydraulic	1/4"	45 - 95 ° F	18",48"	
7000ASTR-4	4E2-211-023	700-213	100K	4.0 NAT	1/2" X 3/8"	Snap Throttle Hydraulic	1/4"	58 - 90 ° F	18"	
7000ASTR-LP-4	4E2-212-164	700-212	160K	11" LP	1/2" X 3/8"	Snap Throttle Hydraulic	1/4"	58 - 90 ° F	18"	
7000BDER2-3-LP-S7C	3D9-50A-923	700-051	480K	2.8" to 11" LP	3/4" X 3/4"	24V AC	1/4"			UNIVERSAL 2 STAGE IID VALVE
7000BDER2-4-S7A	REWORK 700-41C	700-053	300K	1.3" to 3.5" NAT	3/4" X 3/4"	24V AC	1/4"			2-STAGE UNIVERSAL REWORKED VALVE
7000BDER-LP-S7A	3A2-502-5AB	700-055	485K	11" LP	3/4" X 3/4"	24V AC	1/4"			REWORKED VALVE LP WITH SLOW OPEN 0- 5 SECS
7000BDER-S7A	3A3-501-765	700-052	300K	3.5 NAT	1/2" X 3/4"	24V AC	1/4"			SLOW OPEN;0-5 SECS.UNIVERSAL IID,DS,H.S.I.
7000BDER-S7A	3A2-501-733	700-056	350K	3.5 NAT	3/4" X 3/4"	24V AC	1/4"			SLOW OPEN 0 - 5SECS:IID.DSI.H.S.I.
7000BE	302-505-513	700-405	300K	None	3/4" X 3/4"	24VAC 12VDC	1/4"			REWORKED VALVE
7000BE	4E4-505-516	700-401	240K	None	1/2" X 3/4"	24VAC 12VDC	1/4"			
7000BE-120	414-905-516	700-451	240K	None	1/2" X 3/4"	120V AC	1/4"			
7000BE-120	416-905-516	700-453	300K	None	1/2" X 3/4"	120V AC	1/4"			
7000BE-240	437-920-201	700-461	240K	None	1/2" X 3/4"	240V AC	1/4"			
7000BE-240	440-920-201	700-463	300K	None	3/4" X 3/4"	240V AC	1/4"			
7000BER	4E4-501-517	700-402	240K	Uni-Kit	1/2" X 3/4"	24VAC 12VDC	1/4"			
7000BER	4B1-501-517	700-400	240K	Uni-Kit	1/2" X 3/4"	24VAC 12VDC	1/4"			
7000BER	4E6-501-517	700-404	300K	Uni-Kit	1/2" X 3/4"	24VAC 12VDC	1/4"			
7000BER	377-501-503	700-406	300K	Uni-Kit	3/4" X 3/4"	24VAC 12VDC	1/4"			
7000BER-120	416-921-201	700-454	300K	3.5 NAT	3/4" X 3/4"	120V AC	1/4"			
7000BER-120	414-905-516	700-452	240K	3.5 NAT	1/2" X 3/4"	120V AC	1/4"			
7000BER2-3-LP-S7C	REWORK 700-05A	700-445	480K	2.8" to 11" LP	3/4" X 3/4"	24V AC	1/4"			REWORKED VALVE
7000BER2-4	REWORK 700-41C	700-446	300K	1.3" to 3.5" NAT	3/4" X 3/4"	24V AC	1/4"			REWORKED VALVE
7000BER-240	304-921-209	700-462	240K	3.5 NAT	1/2" X 3/4"	240V AC	1/4"			REWORKED VALVE
7000BER-240	302-921-201	700-464	300K	3.5 NAT	3/4" X 3/4"	240V AC	1/4"			REWORKED VALVE
7000BER2-HC-3-LP-S7C	REWORK 700-05A	700-447	960K	2.8" to 11" LP	1" X 1"	24V AC	1/4"			
7000BER2-HC-4	REWORK 700-41C	700-448	720K	1.3" to 3.5" NAT	1" X 1"	24V AC	1/4"			REWORKED VALVE
7000BERC	4E4-503-709	700-412	240K	Convertible	1/2" X 3/4"	24VAC 12VDC	1/4"			REWORKED VALVE
7000BER-LP	302-502-806	700-411	485K	11" LP	3/4" X 3/4"	24VAC 12VDC	1/4"			
7000BER-LP-S7C	4E4-502-581	700-429	390K	11" LP	1/2" X 3/4"	24VAC 12VDC	1/4"			REWORKED VALVE
7000BER-S7A	4B9-501-518	700-426	300K	3.5 NAT	3/4" X 3/4"	24VAC 12VDC	1/4"			
7000BER-S7C	4E4-501-580	700-428	240K	3.5 NAT	1/2" X 3/4"	24VAC 12VDC	1/4"			

Factory Number	Model Number	Uni-Line Number	BTU	Regulator Size	Inlet/Outlet Size	Actuator Type	Pilot Outlet	Temperature Range	Capillary Length	Comments
7000BGOR-S7B	313-541-018	700-804	305K	3.5 NAT	3/4" X 3/4"	Hydraulic	1/4"			
7000BGO-S7B	313-545-024	700-803	305K	3.5 NAT	3/4" X 3/4"	Hydraulic	1/4"			
7000BGVE	307-505-771	700-423	300K	None	3/4" X 3/4"	24VAC 12VDC	1/4"			REWORKED VALVE. HAS NO SAFETY MAG
7000BGVE	327-505-391	700-417	300K	None	3/4" X 3/4"	24VAC 12VDC	1/4"			HAS NO SAFETY MAGNET OR GAS COCK
7000BGVE	329-505-772	700-421	240K	None	1/2" X 3/4"	24VAC 12VDC	1/4"			HAS NO SAFETY MAGNET
7000BGVE-120	327-905-391	700-457	600K	None	1" X 1"	120V AC	1/4"			REWORKED VALVE. HAS NO SAFETY MAG OR GAS COCK
7000BGVER	329-501-756	700-422	240K	3.5 NAT	1/2" X 3/4"	24VAC 12VDC	1/4"			HAS NO SAFETY MAGNET
7000BGVER	307-501-757	700-424	300K	3.5 NAT	3/4" X 3/4"	24VAC 12VDC	1/4"			HAS NO SAFETY MAGNET
7000BGVER	312-501-503	700-420	240K	3.5 NAT	3/4" X 3/4"	24VAC 12VDC	1/4"			HAS NO SAFETY MAGNET
7000BGVER-120	329-901-208	700-450	240K	3.5 NAT	1/2" X 3/4"	120V AC	1/4"			REWORKED VALVE. DIAPHRAGM VALVE HAS NO SAFETY MAG
7000BGVER2-3-LP-S7C	REWORK 700-05A	700-440	480K	2.8" to 11" LP	3/4" X 3/4"	24V AC	1/4"			HAS NO SAFETY MAGNET
7000BGVER2-4	307-509-925	700-413	300K	1.5" to 3.5" NAT	3/4" X 3/4"	24V AC	1/4"			HAS NO SAFETY MAGNET
7000BGVER-S36	310-501-509	700-416	240K	4.0 NAT	1/2" X 1/2"	24VAC 12VDC	1/4"			CARRIER REPLACEMENT HAS NO SAFETY MAGNET
7000BGVMV	307-700-716	700-523	300K	None	3/4" X 3/4"	Millivolt	1/4"			HAS NO SAFETY MAGNET
7000BGVMVR	327-701-389	700-524	300K	3.5 NAT	3/4" X 3/4"	Millivolt	1/4"			REWORKED VALVE. HAS NO SAFETY MAG OR GAS COCK
7000BKER-S7A	3B4-501-905	700-062	350K	3.5 NAT	3/4" X 3/4"	24V AC	1/4"			5- WIRE HOOKUP.
7000BKER-S7A	3B3-501-905	700-066	300K	3.5 NAT	3/4" X 3/4"	24V AC	1/4"			5- WIRE HOOKUP.
7000BKER-S7C	3B3-501-908	700-061	300K	3.5 NAT	3/4" X 3/4"	24V AC	1/4"			5- WIRE HOOKUP.
7000BM	302-000-000	700-105	300K	None	3/4" X 3/4"	Manual	1/4"			REWORKED VALVE. Includes 3/4 X 1/2 bushings (2)
7000BMR	302-001-001	700-106	300K	3.5 NAT	3/4" X 3/4"	Manual	1/4"			REWORKED VALVE. Includes 3/4 X 1/2 bushings (2)
7000BMSE-120-S7C	4B7-905-255	700-471	300K	None	3/4" X 3/4"	120V AC	1/4"			REWORKED VALVE
7000BMSE	337-501-502	700-409	240K	3.5 NAT	1/2" X 1/2"	24VAC 12VDC	1/4"			HAS THERMOPILE SAFETY MAGNET
7000BMSE-120	337-901-212	700-472	240K	5.0 NAT	1/2" X 1/2"	120V AC	1/4"			REWORKED VALVE
7000BMSE-120	338-901-231	700-470	300K	3.5 NAT	3/4" X 3/4"	120V AC	1/4"			REWORKED VALVE. HAS THERMOPILE SAFETY MAGNET
7000BMSE-LP-120	338-902-230	700-469	300K	11" LP	1" X 1"	120V AC	1/4"			
7000BMSGO	334-545-000	700-885	305K	None	3/4" X 3/4"	Millivolt	1/4"			REWORKED VALVE
7000MSGOR	334-541-001	700-886	305K	3.5 NAT	3/4" X 3/4"	Millivolt	1/4"			
7000MSGOR	336-541-151	700-887	240K	4.0 NAT	1/2" X 1/2"	Millivolt	1/4"			
7000BMSM	338-000-000	700-185	300K	None	3/4" X 3/4"	Manual	1/4"			REWORKED VALVE. Includes 3/4 X 1/2 bushings (2)
7000BMV	345-815-400	700-503	240K	None	1/2" X 1/2"	Millivolt	1/4"			
7000BMV	343-705-401	700-505	300K	None	3/4" X 3/4"	Millivolt	1/4"			REWORKED VALVE
7000BMVR	4E7-701-400	700-510	300K	3.5 NAT	3/4" X 3/4"	Millivolt	1/4"			REWORKED VALVE
7000BMVR	345-811-404	700-504	240K	3.5 NAT	1/2" X 3/4"	Millivolt	1/4"			HAS COAXIAL THERMOPILE CONNECTION
7000BMVR	359-701-400	700-508	240K	3.5 NAT	1/2" X 1/2"	Millivolt	1/4"			REWORKED VALVE
7000BMVR	342-811-400	700-506	300K	3.5 NAT	3/4" X 3/4"	Millivolt	1/4"			HAS COAXIAL THERMOPILE CONNECTION

Factory Number	Model Number	Uni-Line Number	BTU	Regulator Size	Inlet/Outlet Size	Actuator Type	Pilot Outlet	Temperature Range	Capillary Length	Comments
7000BMVR-LP	343-812-425	700-515	485K	10.0 LP	3/4" X 3/4"	Millivolt	1/4"			
7000BMVR-S7C	343-811-410	700-511	300K	Uni-Kit	3/4" X 3/4"	Millivolt	1/4"			REPLACEMENT FOR TELEDYNE LARS VALVE
7000BMVR-S7C	343-811-410	700-512	300K	Uni-Kit	3/4" X 3/4"	Millivolt	1/4"			ITT GENERAL B-60 REPLACEMENT
7000BMVR-S7C	342-811-410	700-507	240K	3.5 NAT	1/2" X 3/4"	Millivolt	1/4"			
7000DEHC-S7C	5N6-505-848	700-058	720K	None	1" X 1"	24V AC	1/4"			REWORKED VALVE. IID,DSI,H.S.I.UNIUNIVERSAL
7000DER2-HC-3-LP-S7C	REWORK 700-05A	700-063	960K	2.8" to 11" LP	1" X 1"	24V AC	1/4"			2-STAGE UNIVERSAL
7000DER2-HC-4-S7C	5P1-501-791	700-064	720K	1.3" to 3.5" NAT	1" X 1"	24V AC	1/4"			2-STAGE UNIVERSAL REWORKED VALVE
7000DERHC	5N2-501-531	700-057	720K	4.0 NAT	1" X 1"	24V AC	1/4"			IID,DSI,H.S.I. UNIVERSAL
7000DERHC-S7C	5P1-501-791	700-059	720K	4.0 NAT	1" X 1"	24V AC	1/4"			IID,DSI,H.S.I.UNIUNIVERSAL
7000EHC-120-S7C	451-905-204	700-455	600K	None	1" X 1"	120V AC	1/4"			REWORKED VALVE
7000EHC-240-S7C	450-920-281	700-465	600K	None	1" X 1"	240V AC	1/4"			
7000EHC-S7C	451-505-558	700-441	600K	None	1" X 1"	24VAC 12VDC	1/4"			REWORKED VALVE
7000ELC	736-505-528	710-401	70K	None	1/2" X 1/2"	24V/12V DC	1/4"			
7000ERHC	451-501-557	700-438	720K	3.5 NAT	1" X 1"	24VAC 12VDC	1/4"			REWORKED VALVE
7000ERHC-120	451-901-200	700-468	720K	3.5 NAT	1" X 1"	120V AC	1/4"			
7000ERHC-120-S7C	5C3-901-260	700-456	600K	3.5 NAT	1" X 1"	120V AC	1/4"			
7000ERHC-240-S7C	466-921-201	700-466	720K	3.5 NAT	1" X 1"	240V AC	1/4"			REWORKED VALVE
7000ERHC-S7C	5C3-501-553	700-442	720K	3.5 NAT	1" X 1"	24VAC 12VDC	1/4"			
7000ERLC	739-501-527	710-402		3.5 NAT	1/2" X 1/2"	24V/12V DC	1/4"			
7000ERLC	736-501-527	710-404	70K	3.5 NAT	1/2" X 1/2" INV FLARE	24V/12V DC	1/4"			
7000GOHC-S7B	450-545-024	700-823	100K	None	1" X 1"	Hydraulic	1/4"			
7000GORHC-S7B	450-541-018	700-824	600K	3.5 NAT	1" X 1"	Hydraulic	1/4"			
7000GVEHC-120-S7C	468-905-255	700-459	600K	None	1" X 1"	120V AC	1/4"			HAS NO SAFETY MAGNET
7000GVEHC-S7C	5C3-901-260	700-431	600K	None	1" X 1"	24VAC 12VDC	1/4"			HAS NO SAFETY MAGNET
7000GVERHC-120-S7C	468-901-238	700-458	720K	3.5 NAT	1" X 1"	120V AC	1/4"			REWORKED VALVE. HAS NO SAFETY MAG
7000GVERHC-S7C	468-501-532	700-432	720K	3.5 NAT	1" X 1"	24VAC 12VDC	1/4"			REWORKED VALVE. HAS NO SAFETY MAG
7000GVER-S7A	307-501-572	700-430	240K	3.5 NAT	3/4" X 3/4"	24VAC 12VDC	1/4"			HAS NO SAFETY MAGNET
7000GVMVLC	754-715-448	710-513	70K	None	1/2" X 1/2"	Millivolt	1/4"			no safety magnet
7000MHC-S7C	451-000-024	700-113	600K	None	1" X 1"	Manual	1/4"			
7000MLC	736-000-042	710-101	70K	None	1/2" X 1/2"	Manual	1/4"			
7000MRHC-S7C	451-001-018	700-114	720K	3.5 NAT	1" X 1"	Manual	1/4"			REWORKED VALVE
7000MRLC	701-001-000	710-108	70K	3.5 NAT	3/8" X 3/8"	Manual	1/4"			
7000MRLC	739-001-001	710-102	70K	3.5 NAT	1/2" X 1/2"	Manual	1/4"			REWORKED VALVE
7000MRLC	710-002-046	710-107	70K	10.5 LP	3/8" X 3/8"	Manual	1/4"			REWORKED VALVE 3/8" side outlet right only
7000MVHC-S7C	450-811-393	700-521	600K	None	1" X 1"	Millivolt	1/4"			
7000MVLC	737-835-414	710-501	70K	None	1/2" X 1/2"	Millivolt	1/4"			SPACE HEATING REPLACES GENERAL B-67
7000MVRB-5-LC	759-716-441	710-503	70K	1.7" to 3.5" NAT	1/2" X 3/8"	Millivolt	1/4"			Has a hi/lo adjustable pressure regulator.
7000MVRB-5-LC	759-816-441	710-511	70K	1.7" to 3.5" NAT	1/2" X 3/8"	Millivolt	1/4"			Has a quick drop safety magnet
7000MVRHC-S7C	450-891-393	700-522	720K	3.5 NAT	1" X 1"	Millivolt	1/4"			
7000MVRLC	760-711-454	710-508	70K	3.5 NAT	3/8" X 3/8"	Millivolt	1/4"			Has quick drop safety magnet
7000MVRLC	740-711-415	710-502	70K	3.5 NAT	1/2" X 1/2"	Millivolt	1/4"			SPACE HEATERS REPLACES B-67

Factory Number	Model Number	Uni-Line Number	BTU	Regulator Size	Inlet/Outlet Size	Actuator Type	Pilot Outlet	Temperature Range	Capillary Length	Comments
7000SLC	736-335-063	710-201	70K	None	1/2" X 1/2"	Hydraulic	1/4"	58 - 90 ° F	18"	recreational vehicles
7000SLC	736-350-076	710-218	70K	None	3/8" X 3/8"	Hydraulic	1/4"	100-250 ° F	36"	Catering truck valve replaces itt general
7000SLC	736-355-063	710-203	70K	None	1/2" X 1/2"	Hydraulic	1/4"	58 - 90 ° F	36"	recreational vehicles
7000SRLC	739-351-064	710-205	70K	3.5 NAT	1/2" X 1/2"	Hydraulic	1/4"	58 - 90 ° F	36"	wall furnace replaces TV-27
7000SRLC	739-331-064	710-204	70K	3.5 NAT	1/2" X 1/2"	Hydraulic	1/4"	58 - 90 ° F	18"	
7010BGVER	327-501-399	700-418	300K	3.5 NAT	3/4" X 3/4"	24VAC 12VDC	1/4"			HAS NO SAFETY MAGNET OR GAS COCK
7010BGVMV	327-705-393	700-517	300K	None	3/4" X 3/4"	Millivolt	1/4"			REWORKED VALVE. HAS NO SAFETY MAG OR GAS COCK
7010BGVMV	304-811-393	700-514	240K	None	1/2" X 3/4"	Millivolt	1/4"			REWORKED VALVE. HAS NO SAFETY MAG OR GAS COCK
7010BGVMV	305-705-393	700-513	240K	None	1/2" X 1/2"	Millivolt	1/4"			HAS NO SAFETY MAGNET
7010BGVMV	305-811-393	700-513	240K	None	1/2" X 1/2"	Millivolt	1/4"			NO SAFETY MAGNET OR GAS COCK
7100DER	71B-11A-033	700-077		3.5 NAT	1/2" X 3/4"	24V AC	None			
7100DERB-5-S02	71J-11G-501	700-078		3.5 NAT	1/2" X 3/8"	24V AC	None			
7100DER-LP-S7C	71H-11C-007	700-073		10.0 LP	1/2" X 3/4"	24V AC	None			
7100DER-LP-S7C	71B-11C-007	700-071		10.0 LP	1/2" X 3/4"	24V AC	None			
7100DERN	71G-01E-043	700-074		NEGATIVE PRESS.	1/2" X 3/4"	24V AC	None			NEGATIVE PRESSURE VALVE;-1.0"Wc TO +0.5"Wc
7100DERP	71K-01B-027	700-076		3.5 NAT	1/2" X 1/2"	24V AC	None			
7100DER-S7C	71B-11A-001	700-070		3.5 NAT	1/2" X 3/4"	24V AC	None			
7100DER-S7C	71B-11A-001	700-072		3.5 NAT	1/2" X 3/4"	24V AC	None			
7200DER	7C4-A8B-003	720-051	150K	3.5 NAT	1/2" X 3/4"	24V AC	None			UNI-KIT
7200DERB-5-SO-2	7D6-G1D-056	720-078	125K	3.5 NAT	1/2" X 3/8"	24V AC	1/4"			ADJUSTABLE LOW/HI REGULATOR
7200DERCS-1	7C6-A7B-001	720-055	125K	Convertible	1/2" X 3/8"	24V AC	None			
7200DERN	7E9-F5L-008	720-074	150K	3.5 NAT	1/2" X 3/4"	Millivolt	1/4"			
7200DER-S7C	7C4-C5B-015	720-050	150K	3.5 NAT	1/2" X 3/4"	24V AC	1/4"			UNI-KIT
7200DER-S7C	7C4-A9B-003	720-052	150K	3.5 NAT	1/2" X 1/2"	24V AC	1/4"			UNI-KIT CROSSED TO 720-050
7200DER-SO-3	7C4-B6J-502	720-054	150K		1/2" X 3/4"	24V AC	1/4"			UNI KIT
7200DER-SO-4-120	7A5-A7B-034	720-083	150K	3.5 NAT	1/2" X 1/2"	120V AC	None			UNI-KIT
7200E	7A4-A0A-000	720-401	150K	None	1/2" X 3/4"	24V AC	1/4"			UNI-KIT
7200ER	7A4-A1B-001	720-402	150K	3.5 NAT	1/2" X 3/4"	24V AC	1/4"			
7200ER	7A7-A1B-001	720-400	150K	3.5 NAT	1/2" X 3/4"	24V AC	1/4"			UNI-KIT
7200ER	7A8-A1B-007	720-406	150K	3.5 NAT	3/4" X 3/4"	24V AC	1/4"			UNI-KIT
7200ER	7C8-A1B-001	720-404	150K	3.5 NAT	3/4" X 3/4"	24V AC	1/4"			UNI-KIT
7200ERC	7C9-B2F-005	720-007	150K	Convertible	1/2" X 1/2"	24V AC	1/4"			
7200ERCS-2	7DO-CAF-005	720-472	150K	Convertible	1/2" X 1/2"	24V AC	1/4"			STEP OPEN TO 40% OF FULL FLOW
7200ERCS-2	7C3-CAF-005	720-474	150K	Convertible	1/2" X 1/2"	24V AC	1/4"			STEP OPEN FEATURE TO 25% OF FULL FLOW .30 SECONDS
7200ER-S7C	7A4-A5B-001	720-403	150K	3.5 NAT	1/2" X 3/4"	24V AC	1/4"			UNI-KIT
7200IPER	7E3-D5B-029	720-079	150K	3.5 NAT	1/2" X 3/4"	24V AC	1/4"			UNI-KIT
7200IPER2-4	FA8-F7G-004	720-082	150K	3.5 NAT	3/4" X 3/4"	24V AC	1/4"			UNI-KIT/LO-FIRE 1.3 HIGH FIRE 3.5"W.C./2-STAGE
7200IPER-LP	7E3-E9C-050	720-080	150K	3.5 NAT	1/2" X 3/4"	24V AC	1/4"			UNI-KIT/ REPLACED BY 720-079

Factory Number	Model Number	Uni-Line Number	BTU	Regulator Size	Inlet/Outlet Size	Actuator Type	Pilot Outlet	Temperature Range	Capillary Length	Comments
7200IPER-LP-S7C	7E3-FOC-050	720-073	150K	3.5 NAT	1/2" X 3/4"	24V AC	1/4"			UNI-KIT/REPLACED BY 720-073
7200IPER-LP-S7C	7E2-FOC-050	720-071	150K	3.5 NAT	1/2" X 3/4"	24V AC	1/4"			
7200IPER-S7C	7E3-E7B-029	720-072	150K	3.5 NAT	1/2" X 3/4"	24V AC	1/4"			UNI-KIT
7200IPER-S7C	7E2-E7B-029	720-070	150K	3.5 NAT	1/2" X 3/4"	24V AC	1/4"			UNI-KIT
7200IPER-SO-4	7E2-E5J-528	720-081	150K	3.5 NAT	1/2" X 3/4"	24V AC	1/4"			UNI-KIT
7222DER	609-011-900	722-051	100K	UNI-KIT	1/2" X 1/2"	24V AC	None			
7222DERC	606-013-013	722-053	100K	Convertible	1/2" X 1/2"	24V AC	1/4"			
7222DER-S7A	606-011-000	722-052	100K	UNI-KIT	1/2" X 1/2"	24V AC	1/4"			
7222IPER	675-011-000	722-079	100K	Uni-Kit	1/2" X 1/2"	24V AC	1/4"			90 DEGREE FLANGE FOR SIDE OUTLETS
R103RCTSLP	28-006-001	110-506		11" LP	1/2" X 1/2" RH THREAD	THERMOCOUPLE	1/4"	160 ° F	1-1/4"	IN/OUTLET INV.FLARE:3/8"BUSH:PILOTADJ.LOW CAPACITY
R103RCTSLPPA	29-437-003	110-503		11" LP	1/2" X 3/8" PIPE,RH THREAD	THERMOCOUPLE	1/4"	160 ° F	1-1/4"	3/8" BUSH:
R103RVTSPL	28-537-005	110-507		11" LP	3/8" X 3/8" RH THREAD	THERMOCOUPLE	1/4"	160 ° F	1-3/8"	IN/OUTLET INVERT.FLARE:PILOT ADJ.LOW CAPACITY
R103RVTSPL	28-937-004	110-509		11" LP	3/8" X 3/8" RH THREAD	THERMOCOUPLE	1/4"	160 ° F	1 1/2"	IN/OUTLET INV.FLARE:LOW CLEAR PTR KNOB:LOW CAPACIT
R103RVTSLPP	29-437-003	110-502		11" LP	1/2" X 1/2" RH THREAD	THERMOCOUPLE	1/4"	160 ° F	1-3/8"	INVERTED FLARE OUTLET:3/8" BUSH:LOW CAPACITY.
R103RVTSLPPA	29-636-000	110-505			3/8" X 3/8" RH THREAD	THERMOCOUPLE	1/4"	160 ° F	1-1/4"	INVERTED FLARE INLET:LOW CAPACITY
R103RVTSLPPA	29-639-005	110-501		11" LP	3/8" X 3/8"	THERMOCOUPLE	1/4"	160 ° F	1-5/8"	INVERTED FLARE INLET:
R103RVTSLPPA	29-936-013	110-504		11" LP	3/8" X 3/8" RH THREAD	THERMOCOUPLE	1/4"	160 ° F	1-1/4"	INVERTED FLARE OUTLET:LOW CAPACITY
R103RVTSLPPA	28-838-014	110-508		11" LP	3/8" X 3/8" RH THREAD	THERMOCOUPLE	1/4"	160 ° F	1-1/2"	IN/OUTLET PIPEFIT:LOW CAPACITY
R110RCTS-PC	69-436-406	110-203		Convertible	1/2" X 1/2"	THERMOCOUPLE	1/4"	160 ° F	1-1/4"	INVERTED FLARE OUTLET:3/8" BUSHING:PILOT ADJ.
R110RCTS-PC	69-437-406	110-204		Convertible	1/2" X 1/2"	THERMOCOUPLE	1/4"	180 ° F	1-3/8"	INVERTED FLARE OUTLET:3/8"BUSH:PILOT ADJ.UNIKIT
R110RTS	61-237-065	110-326		3.5 NAT	1/2" X 1/2"	THERMOCOUPLE	1/4"	160 ° F	1-3/8"	INVERTED FLARE OUTLET:3/8"BUSH:PILOT ADJ.UNIKIT
R110RTS8P	66-138-640	110-353		3.5 NAT	1/2" X 1/2" RH THREAD	THERMOCOUPLE	1/4"	180 ° F	1-1/2"	3/8"BUSH:INV.FLARE OUTLET:
R110RTSP	75-614-006	110-206		3.5 NAT	1/2" X 1/2"	THERMOCOUPLE	1/4"	160 ° F	2-3/8"	INVERTED FLARE OUTLET,3/8"REDUCER/UNIKIT/PILOTADJ.
R65RRTSP	7-237-202	110-268	100K	10.0 LP	1/2" X 1/2"	THERMOCOUPLE	1/4"	160 ° F	1-3/8"	1/2" I.F. OUTLET