APPLICATIONS

• Commercial, industrial, and home uses where liquid must be transferred

FEATURES

- Self-priming for instant delivery or dewatering up to 6' (1.8 m)
- Non-submersible stainless steel or plated brass pump body
- Rugged metallic handle or easy portability
- Dual threaded intake and discharge with both 3/4" (19 mm) male garden hose thread and 3/8" FNPT (9.5 mm)
- Model 360K includes pump, hose, strainer, and suction adapter
- Pump only models available with separate kit options
- cULus listing on models 555502, 555103, 555507, and 555122





SERIES SPECIFICATIONS

	Volts	Hz	Amps		Watts	Performance (GPH @ Height in Feet)				Shut-Off	PSI
l			FLA	Start		1'	5'	10'	20'	(ft)	
	115	60	1.6	2.4	91	360	330	300	250	25'	20.9
	12 VDC	-	7	14	84	300	270	240	202	25'	19.9

Item No.	Model	HP	Volts	Material	Operation	Cord	Weight
555502	360	1/10	115	Plated Brass	Self-Priming	6' 1.8 m	3.4 lbs 1.54 Kg
555103	360S	1/10	/10 115 Stainless Steel		Self-Priming	6' 1.8 m	3.4 lbs 1.54 Kg
555507	370	1/10	115	Plated Brass	Self-Priming	6' 1.8 m	4.7 lbs 2.12 Kg
555602	365	1/10	12 VDC	Plated Brass	Self-Priming	12" Leads 30.5 cm	4.7 lbs 2.12 Kg
555203	365S	1/10	12 VDC	Stainless Steel	Self-Priming	12" Leads 30.5 cm	4.7 lbs 2.12 Kg
555122	360K	1/10	115	Plated Brass	Self-Priming	6' 1.8 m	4.7 lbs 2.12 Kg

SERIES SPECIFICATIONS CONT.





Model	A	В	C	D	Е	F	G	Н	J	K	L	M
115 V	3/4" MGHT	3/8" FNPT	6.62"	1.87"	4.5"	3.35"	4"	3"	3.37"	2.14"	1.69"	0.22"
	1.91 cm	9.5 mm	16.81 cm	4.75 cm	11.43 cm	8.51 cm	10.16 cm	7.62 cm	8.56 cm	5.44 cm	4.29 cm	5.6 mm
12 VDC	3/4" MGHT	3/8" FNPT	5.93"	1.87"	4.18"	3.13"	4"	3"	3.37"	1.82"	1.69"	0.22"
	1.91 cm	9.5 mm	15.06 cm	4.75 cm	10.62 cm	7.95 cm	10.16 cm	7.62 cm	8.56 cm	4.62 cm	4.29 cm	5.6 mm

PERFORMANCE DATA

Flow - Liters per Hour 180 360 540 720 900 1080 1260 1440 0 30 9 25 Total Head in Meters Total Head in Feet 20 15 10 5 0 0 50 100 150 200 250 300 350 400 Flow - Gallons per Hour ■ 360/360S/360K/370 ■ 365/365S

REPLACEMENT & BRUSH KITS

Item No.	Model	Includes	Kit Used On
555702	HRK-360S	(2) Each - Buna Impeller with SST Insert, Buna Cover Gaskets (1) Each - SST Cam, SST Cam Screws, SST Volute Cover, Cam Gasket (4) Each - Volute Cover Screws	All Models
555706	IRK-360	(2) Each - Buna Impellers with Brass Insert, Buna Cover Gaskets	555502, 555122, 555602
555710	HW-360 (1) Each - 10' ft Garden Hose, SST Spring Strainer, Suction Adapter		All Models
555713	IRK-360S	(2) Each - Buna Impellers with SST Insert, Buna Cover Gaskets	555103, 555203, 555503
555714	ISRK-360S	(2) Each - Buna Impellers with SST Insert, Buna Cover Gaskets (1) Each - Slinger, Viton U-Cup Seal, Felt Washer, Retainer Ring	All Models
555705	WB-360	Brush Kit: (2) Each - White Caps, Brushes, Covers with Springs	All Models

Spec Sheet 996287