

FUEL UNITS


Suntec

2-Stage Fuel Units

Maximum nozzle capacity 6 gph.

NOTE: Remanufactured units listed below may also be exchanged for old style S2 units and low capacity H2 units.

Rotation and Nozzle Port	Mounting	Mfr#	Reman#
CW-L	Hub	H3BB-200	P4-10R
CW-R	Hub	H3BA-200	P4-11R
CCW-L	Hub	H3BC-200	P4-12R
CCW-R	Hub	H3BD-200	P4-13R
CW-L	Flange	H3BB-100	P4-14R
CW-R	Flange	H3BA-100	P4-15R
CCW-L	Flange	H3BC-100	P4-16R
CCW-R	Flange	H3BD-100	P4-17R
CW-L	Flange	HA2BB-100	P2-32R



Suntec

2-Stage Mini-Pumps

Mount in any position except upside down.

MODEL B2 - FOR 3450 RPM - 7 GPH



Rotation and Nozzle Port	Mounting	Mfr#	Item#	Reman#
CW-R	Flange	B2YA8916	P4-30	P4-30R
MODEL B1 - FOR 1725 RPM - 3 GPH				
CW-R	Flange	B1YA8212	P4-60	P4-60R
MODEL B2 - FOR 3450 RPM - 3 GPH				
CW-R	Flange	B2VA8216	P4-70	P4-70R

NOTE: Remanufactured products available only on exchange for similar defective units. All fuel units, whether new or Sid Harvey Remanufactured, are set for one line operation. The direction of rotation and nozzle port location are determined looking at the shaft end of the unit.