

### Bramec® Silicone Sealant

- Permanently flexible -60°F to 400°F
- 100% RTV silicone
- Insulates thermally
- Insulates electrically
- Waterproof seal
- Weatherproof seal



ITEM NUMBER	DESCRIPTION	STD QTY	PLT QTY	U M
20080	Clear Silicone (10.1 Fl. oz.)	12	600	EA
20081	White Silicone (10.1 Fl. oz.)	12	600	EA
20082	Aluminum Silicone (10.1 Fl. oz.)	12	600	EA

### Bramec® Hi-Temp Silicone Sealant

- Permanently flexible -85°F to 450°F
- Short term exposure to 500°F
- 100% RTV silicone
- Insulates thermally
- Waterproof seal



ITEM NUMBER	DESCRIPTION	STD QTY	U M
18068	Red Hi-Temp Silicone (10.1 Fl. oz.)	12	EA

### 25 Acrylic Latex Caulk

- Environmentally Friendly
- Easy Gunning & Tooling
- Cleans Up with Water
- Paintable

**Caulk Cross Reference Numbers**  
19005      7-4500      93265



ITEM NUMBER	DESCRIPTION	STD QTY	U M
19005	White Latex Caulk (10.1 Fl. oz.)	24	EA

### BOSS® 357 Acrylic Latex Contractor's Caulk

- Non-yellowing
- Paintable sealant
- Interior & exterior uses
- Flexible bond



ITEM NUMBER	DESCRIPTION	STD QTY	U M
19010	White Acrylic Latex Caulk	12	EA

### DAP® BLOCKADE® Fire-Rated Intumescent Acrylic Latex Sealant

- Meets ASTM E-814/UL 1479 specifications
- Intumescent expansion fills void created by combustible materials burned during a fire
- Treats all general firestopping applications for combustible & non-combustible penetrations
- Excellent adhesion to unprimed surfaces
- Red color for easy inspection



ITEM NUMBER	DESCRIPTION	STD QTY	U M
19699	[18858] DAP Blockade Caulk (Red)	12	EA

### 3M™ Fire Barrier Sealant CP 25WB+

- A premium elastomeric latex caulk designed for use as a one-part fire, smoke, noxious gas and water sealant for through-penetrations
- Red color
- No-sag, non-halogen formula
- Fast-drying tack-free in approximately 10-15 minutes
- Paintable
- Up to 4 hours Fire Protection



ITEM NUMBER	DESCRIPTION	STD QTY	U M
5863	[11638] Fire Sealant 10.1 oz. (Red)	12	EA

### BOSS® 125 Multi-Seal Building/Construction Sealant

- VOC compliant in all 50 states
- One-part sealant, no mixing required
- Non-streaking
- Good weatherability
- Paintable with most latex base paints
- Can be used in vertical and horizontal applications



ITEM NUMBER	DESCRIPTION	STD QTY	U M
20419	10.3 oz BOSS Multi-Seal (White)	12	EA
17769	10.3 oz BOSS Multi-Seal (Gray)	12	EA

### Caulking Guns



ITEM NUMBER	DESCRIPTION	STD QTY	U M
14006	1/10 Gallon Standard Duty	10	EA

### 3M™ Fire Barrier Moldable Putty Pads

- Firestop tested up to 4 hours in accordance with ASTM E 814 (UL 1479) & CAN/ULC S115
- Wall opening protective material tested up to 2 hours in accordance with UL 263
- Provides draft and cold smoke seal
- Halogen-free formula
- Pliable and conformable (molds easily into required shapes)
- Self-adhering pads can be joined together for larger firestop applications
- Noncorrosive to metal and compatible with synthetic cable jackets
- Will not dry out or crumble, re-enterable
- Helps reduce noise transfer (STC-Rating of 56 when tested in STC 56-rated wall assembly)



ITEM NUMBER	DESCRIPTION	STD QTY	U M
15061	[051115-16509] 7" X 7" Putty Pads	20	EA