



UTILITY ENTERPRISES, INC.
 700 MAIN STREET
 WESTBURY, NY 11590
 (516) 997-6300 - FAX # (516) 997-6345
www.UtilityChemicals.com

ALUMINUM SAFE POLAR GRADE NO-FREEZ

FOR CHEMICAL EMERGENCY: Spill, Leak, Fire, Exposure, or Accident - Call **INFOTRAC** - Day or Night: **1-800-535-5053**
THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) **IMPORTANT:** Read this MSDS before handling & disposing of this product. Pass this information on to employees, customers and users of this product.

PRODUCT IDENTIFICATION

DOT Shipping name:	PROPYLENE GLYCOL	CAS NO.: MIXTURE
Chemical Family:	GLYCOL	UN/NA #: N/A
DOT Hazard Class:	NONE	DATE OF ISSUE: 07/15

SECTION I - HAZARDOUS INGREDIENTS/EXPOSURE LIMITS

Hazardous Ingredients:	CAS #	TLV/PEL	AGENCY	TYPE	SARA-313(% Range)
NO HAZARDOUS INGREDIENTS					

SECTION II - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Flush eyes with plenty of water.

SKIN CONTACT: Wash off in flowing water or shower.

INHALATION: (breathing) Remove to fresh air if effects occur. Consult a physician.

INGESTION: (swallowing) No adverse effects anticipated by this route of exposure incidental to proper industrial handling.

SECTION III - HEALTH HAZARDS / ROUTES OF ENTRY

EYE CONTACT: May cause slight transient (temporary) eye irritation. Corneal injury is unlikely. Mists may cause eye irritation.

SKIN CONTACT: Prolonged contact is essentially non-irritating to skin. A single prolonged exposure is not likely to result in the material being absorbed through skin in harmful amounts. Repeated exposures may cause flaking and softening of skin.

INHALATION: (breathing) At room temperature, vapors are minimal due to physical properties. Mists may cause irritation of upper respiratory tract.

INGESTION: (swallowing) Single dose oral toxicity is considered to be extremely low. No hazards anticipated from swallowing small amounts incidental to normal handling operations.

SECTION IV - SPECIAL PROTECTION INFORMATION

VENTILATION: Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines.

RESPIRATORY PROTECTION: Atmospheric levels should be maintained below the exposure guideline. When respiratory protection is required for certain operations, use an approved air-purifying respirator. In misty atmospheres, use an approved mist respirator.

SKIN PROTECTION: Use gloves impervious to this material.

EYE PROTECTION: Use safety glasses. Safety glasses should be sufficient for most operations; however, for misty operations wear chemical goggles.

EXPOSURE GUIDELINE(S): Propylene glycol: AIHA WEEL is 10mg/m³ 8-hr. TWA.

SECTION V - REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY: (materials to avoid) This product is incompatible with: *Oxidizing agents*.

HAZARDOUS DECOMPOSITION PRODUCTS: When available oxygen is limited, as in a fire or when heated to very high temperatures by hot wire or plate, carbon monoxide and other hazardous compounds such as aldehydes might be generated.

HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI - SPILL OR LEAK PROCEDURES

PRECAUTIONS IN CASE OF LEAK OR SPILL: Clean up spilled material with absorbent material.

WASTE DISPOSAL METHOD: Do not dump into any sewers, on the ground, or into any body of water. All disposal methods must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.



UTILITY ENTERPRISES, INC.
700 MAIN STREET
WESTBURY, NY 11590
(516) 997-6300 - FAX # (516) 997-6345
www.UtilityChemicals.com

ALUMINUM SAFE POLAR GRADE NO-FREEZ

SECTION VII - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS: Keep containers tightly closed when not in use.

SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

EXTINGUISHING MEDIA: Extinguish with water fog or fine spray, dry chemical, CO₂, or a universal type foam.

FIRE AND EXPLOSION HAZARD: During a fire, smoke may contain the original material in addition to unidentified toxic and/or irritating compounds. Hazardous combustion products may include and are not limited to: aldehydes, carbon monoxide.

FIRE FIGHTING PROCEDURES: Keep people away. Isolate fire area and deny unnecessary entry. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire.

SECTION IX - PHYSICAL DATA

APPROXIMATE BOILING POINT (DEG F):	>500	PER CENT VOLATILE:	0
SPECIFIC GRAVITY (68 F):	1.036	FLASH POINT (TCC, DEG F):	471
RELATIVE EVAPORATION RATE (ESTIMATED):	<1	PER CENT SOLUBILITY IN WATER:	100
VAPOR PRESSURE @20C mmHg (CALCULATED):	<.1		

SECTION X - OTHER REGULATORY DATA

SARA

SECTION 302: NOT LISTED
SECTION 311 & 312: NOT LISTED
SECTION 313: See Section I.I

HMIS

Health: 0
Flammability: 0
Reactivity: 0

TSCA

All components are in full compliance with the TSCA inventory.

CALIFORNIA PROPOSITION 65

NOT LISTED

RCRA

Waste material would be a D001

CERCLA

NOT LISTED

CARCINOGENICITY:

NOT LISTED with NTP or IARC.

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.



UTILITY MANUFACTURING CO., INC.
700 MAIN STREET, WESTBURY, NY 11590
(516) 997-6300 - FAX # (516) 997-6345

MATERIAL SAFETY DATA SHEET

ALUMINUM SAFE POLAR NO-FREEZ

FOR CHEMICAL EMERGENCY: Spill, Leak, Fire, Exposure, or Accident - Call **INFOTRAC** - Day or Night: **1-800-535-5053**

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) **IMPORTANT:** Read this MSDS before handling & disposing of this product. Pass this information on to employees, customers and users of this product.

PRODUCT IDENTIFICATION

DOT Shipping name:	PROPYLENE GLYCOL	CAS NO.: MIXTURE
Chemical Family:	GLYCOL	UN/NA #: N/A
DOT Hazard Class:	NONE	DATE OF ISSUE : 4/08

SECTION I - HAZARDOUS INGREDIENTS/EXPOSURE LIMITS

Hazardous Ingredients:	CAS #	TLV/PEL	AGENCY	TYPE	SARA-313(% Range)
NO HAZARDOUS INGREDIENTS					

SECTION II - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Flush eyes with plenty of water.

SKIN CONTACT: Wash off in flowing water or shower.

INHALATION: (breathing) Remove to fresh air if effects occur. Consult a physician.

INGESTION: (swallowing) No adverse effects anticipated by this route of exposure incidental to proper industrial handling.

SECTION III - HEALTH HAZARDS / ROUTES OF ENTRY

EYE CONTACT: May cause slight transient (temporary) eye irritation. Corneal injury is unlikely. Mists may cause eye irritation.

SKIN CONTACT: Prolonged contact is essentially non-irritating to skin. A single prolonged exposure is not likely to result in the material being absorbed through skin in harmful amounts. Repeated exposures may cause flaking and softening of skin.

INHALATION: (breathing) At room temperature, vapors are minimal due to physical properties. Mists may cause irritation of upper respiratory tract.

INGESTION: (swallowing) Single dose oral toxicity is considered to be extremely low. No hazards anticipated from swallowing small amounts incidental to normal handling operations.

SECTION IV - SPECIAL PROTECTION INFORMATION

VENTILATION: Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines.

RESPIRATORY PROTECTION: Atmospheric levels should be maintained below the exposure guideline. When respiratory protection is required for certain operations, use an approved air-purifying respirator. In misty atmospheres, use an approved mist respirator.

SKIN PROTECTION: Use gloves impervious to this material.

EYE PROTECTION: Use safety glasses. Safety glasses should be sufficient for most operations; however, for misty operations wear chemical goggles.

EXPOSURE GUIDELINE(S): Propylene glycol: AIHA WEEL is 50 ppm total, 10mg/m3 aerosol only.

SECTION V - REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY: (materials to avoid) This product is incompatible with: *Oxidizing agents*.

HAZARDOUS DECOMPOSITION PRODUCTS: When available oxygen is limited, as in a fire or when heated to very high temperatures by hot wire or plate, carbon monoxide and other hazardous compounds such as aldehydes might be generated.

HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI - SPILL OR LEAK PROCEDURES

PRECAUTIONS IN CASE OF LEAK OR SPILL: Clean up spill with absorbent material

WASTE DISPOSAL METHOD: Do not dump into any sewers, on the ground, or into any body of water. All disposal methods must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.



UTILITY MANUFACTURING CO., INC.
700 MAIN STREET, WESTBURY, NY 11590
(516) 997-6300 - FAX # (516) 997-6345

MATERIAL SAFETY DATA SHEET

ALUMINUM SAFE POLAR NO-FREEZ

SECTION VII - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS: Keep containers tightly closed when not in use.

SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

EXTINGUISHING MEDIA: Extinguish with water fog or fine spray, dry chemical, CO₂, or a universal type foam.

FIRE AND EXPLOSION HAZARD: During a fire, smoke may contain the original material in addition to unidentified toxic and/or irritating compounds. Hazardous combustion products may include and are not limited to: aldehydes, carbon monoxide.

FIRE FIGHTING PROCEDURES: Keep people away. Isolate fire area and deny unnecessary entry. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire.

SECTION IX - PHYSICAL DATA

APPROXIMATE BOILING POINT (DEG F):	>500	PER CENT VOLATILE:	0
SPECIFIC GRAVITY (68 F):	1.036	FLASH POINT (TCC, DEG F):	471
RELATIVE EVAPORATION RATE (ESTIMATED):	>1	PER CENT SOLUBILITY IN WATER:	100
VAPOR PRESSURE @20C mmHg (CALCULATED):	<.1		

SECTION X - OTHER REGULATORY DATA

SARA

SECTION 302: NOT LISTED
SECTION 311 & 312: NOT LISTED
SECTION 313: See Section I.I

HMIS

Health: 0
Flammability: 0
Reactivity: 0

TSCA

All components are in full compliance with the TSCA inventory.

CALIFORNIA PROPOSITION 65

NOT LISTED

RCRA

Waste material would be a D001

CERCLA

NOT LISTED

CARCINOGENICITY:

NOT LISTED with NTP or IARC.

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufactures and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.