

### SAFETY DATA SHEET

# NOKORODE® COLD WEATHER

Soldering paste flux SDS# Z0663

## Sid Harvey item #'s 14720 & 14730

## Section 1 - Product and Company Information

Product Name

Nokorode® Cold Weather Paste Flux

**Product Codes** 

14700, 14720, 14730

**Chemical Family** 

Organic/Inorganic

Use

Soldering flux

Manufacturer's Name

The RectorSeal Corporation 2601 Spenwick Drive Houston, Texas 77055 USA

Date of Validation January 23, 2015

Date of Preparation May 2, 2012 **HMIS Codes** 

Health 1

Flammability 1
Reactivity 0

ivity 0 PPI B

Emergency Telephone No. Chemtrec 24 Hours (800)-424-9300 USA (703)-527-3887 International

Technical Service Telephone No. (800)-231-3345 or (713)-263-8001

### Section 2 - Hazards Identification

### **EMERGENCY OVERVIEW**

**OSHA Hazards** 

Irritant

## **GHS CLASSIFICATION**

**Physical Hazards** 

None

#### **Health Hazards**

Acute Toxicity:

Oral: Not Classified Dermal: Not Classified Inhalation: Not Classified

Skin Corrosion/Irritation: Not Classified

Serious Eye Damage/Eye Irritation: Not Classified Respiratory or Skin Sensitization: Not Classified

Germ Cell Mutagenicity: Not Classified

Carcinogenicity: Not Classified

Reproductive Toxicology: Not Classified

Target Organ Systemic Toxicity - Single Exposure: Not Classified Target Organ Systemic Toxicity - Repeated Exposure: Not Classified

Aspiration Toxicity: Not Classified

### **ENVIRONMENTAL HAZARDS**

Hazardous to the Aquatic Environment: Not Classified

Acute aquatic toxicity: Not Classified Chronic aquatic toxicity: Not Classified Bioaccumulation potential: Not Classified Rapid degradability: Not Classified

### GHS Label elements, including precautionary statements



GHS07: Exclamation Mark/Irritant

Signal Word: Warning

#### Hazard Statements:

H302 - Harmful if swallowed.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

### Precautionary Statements:

P102 - Keep out of reach of children.

P262 - Do not get in eyes, on skin, or on clothing.

P264 - Wash hands thoroughly after handling.

P281 Use personal protective equipment as required.

### **Summary Of Acute Hazards**

Irritation to respiratory system from fumes evolved during soldering. Eye contact may cause intense irritation and injury.

### **Route Of Exposure, Signs And Symptoms**

#### **INHALATION**

Irritation to respiratory system from fumes evolved during soldering.

#### **EYE CONTACT**

Contact may cause intense irritation and injury.

#### SKIN CONTACT

May cause skin irritation.

## **INGESTION**

Nausea, vomiting, irritation to digestive system.

#### SUMMARY OF CHRONIC HAZARDS

Short term effects to liver and kidneys can occur. Chemical irritation from continued skin contact can occur. Continuous industrial use in small unventilated areas may result in sufficient inhalation of solder and flux fumes to cause lung damage and irritation of respiratory tract.

#### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver, or kidneys may have increased susceptibility to excessive exposure.

### Section 3 - Composition/Information on Ingredients

Ingredient: Zinc Chloride

Percentage By Weight: 10-25

CAS#: 7646-85-7

EC#: 231-592-0

**Ingredient:** Ammonium Chloride

Percentage By Weight: 10-25

CAS Number: 12125-02-9

EC#: 235-186-4

**Ingredient:** Petrolatum

Percentage By Weight: 70-90

CAS Number: 8009-03-8

EC#: 232-373-2

Ingredient: Petroleum Distillates

Percentage By Weight: < 10

CAS Number: 64742-46-7

EC#: 265-148-2

## Section 4 - First Aid Measures

If inhaled: If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial

respiration as needed. Obtain emergency medical attention. Prompt action is essential.

If on skin: Immediately wash with soap and water. Remove and wash any contaminated clothing.

If in eyes: Immediately flush with large amounts of water for at least 15 minutes. Get prompt medical

attention if irritation persists.

If swallowed: If swallowed, call a physician immediately. Only induce vomiting at the instruction of

a physician. Never give anything by mouth to an unconscious person.

#### Section 5 - Fire Fighting Measures

### **Extinguishing Media**

Foam, dry chemical, carbon dioxide or water fog.

**Special Fire Fighting Procedures:** Wear self-contained full face piece breathing apparatus and other protective clothing. Hazardous decomposition products possible (see Section 10). May release ZnO and HCl fumes.

Unusual Fire And Explosion Hazards: Heat may build up pressure and rupture closed containers.

## Section 6 - Accidental Release Measures

**Steps To Be Taken In Case Material Is Released Or Spilled:** Wipe up spills to prevent footing hazard. Avoid flushing into sewers, drains, waterways and soil. Wear protective clothing during clean up.

## Section 7 - Handling and Storage

**Precautions To Be Taken In Handling And Storing:** Keep container closed and upright when not in use. Store flux at ambient conditions. Wash thoroughly after handling to remove all residue.

**Other Precautions:** Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions. Do not reuse empty containers.

## Section 8 - Exposure Controls/Personal Protection

Ingredient	Units
Zinc Chloride ACGIH TLV: OSHA PEL:	1 mg/m3 1 mg/m3
Ammonium Chloride ACGIH TLV: OSHA PEL:	10 mg/m3 10 mg/m3
Petrolatum ACGIH TLV: OSHA PEL:	N/D N/D
Petroleum Distillates	

**Respiratory Protection (Specify Type):** In confined poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air purifying or supplied air respirators during soldering operations until fumes have dissipated.

N/D

N/D

Ventilation - Local Exhaust: Acceptable

ACGIH TLV:

OSHA PEL:

Special: N/A

Mechanical (General): Acceptable.

Other: N/A

Protective Gloves: Wear rubber gloves.

**Eye Protection:** Safety glasses (ANSI Z-87.1 or equivalent)

Other Protective Clothing Or Equipment: Coveralls recommended.

Work/Hygienic Practices: Where use can result in skin contact, wash exposed areas thoroughly before eating,

drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

### Section 9 - Physical and Chemical Properties

Boiling point: N/A

Specific gravity (H20 = 1): 1.06

Vapor pressure (mmHg): < 0.01 @ 68°F (20°C)

Melting point:  $120^{\circ} - 150^{\circ}F (52^{\circ} - 66^{\circ}C)$ 

Vapor Density (Air = 1): N/A

Evaporation rate (Ethyl Acetate = 1): N/A

Appearance/Odor: Tan/Petroleum odor

Solubility in water: Insoluble

Volatile Organic Compounds (VOC) Content

(theoretical percentage by weight): 0% or (0 g/L)

Flash point: > 400°F (204°C) SETA CC

Lower explosion limit: N/D Upper explosion limit: N/D

### Section 10 - Stability and Reactivity

Stability: Stable

Conditions To Avoid: None

Incompatibility (Materials To Avoid): None known

Hazardous Decomposition Products: Toxic fumes of zinc, chlorine, and HCL may be evolved during soldering.

Hazardous Polymerization: Will not occur.

### Section 11 - Toxicology Information

#### **Chronic Health Hazards**

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

**Toxicology Data** 

Ingredient Name

**Zinc Chloride** 

Oral-Rat LD50: 350 mg/kg

Inhalation-Rat LCLo: 1960 mg/m3/10M

**Ammonium Chloride** 

Oral-Rat LD50: 1650 mg/kg

Inhalation-Rat LC50: N/D

Petrolatum

Oral-Rat LD50: N/D Inhalation-Rat LC50: N/D

**Petroleum Distillates** 

Oral-Rat LD50: N/D Inhalation-Rat LC50: N/D

## Section 12 - Ecological Information

## **Ecological Data**

Ingredient Name: Zinc Chloride

Food Chain Concentration Potential None

Waterfowl Toxicity N/A

BOD None

Aquatic Toxicity 7.2 ppm/96 hr/medium bluegill/TLm

Ingredient Name: Ammonium Chloride

Food Chain Concentration Potential None

Waterfowl Toxicity N/A

BOD N/A

Aquatic Toxicity 6 ppm/96 hr/sunfish/TLm

Ingredient Name: Petrolatum

Food Chain Concentration Potential N/D

Waterfowl Toxicity N/D

BOD N/D

Aquatic Toxicity N/D

Ingredient Name: Petroleum Distillates

Food Chain Concentration Potential N/D

Waterfowl Toxicity N/D

BOD N/D

Aquatic Toxicity N/D

## Section 13 - Disposal Considerations

Waste Classification: Non-regulated solid waste

Disposal Method: Approved landfill

Waste from this product is not considered hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with Federal, State, and Local regulation regarding pollution.

## Section 14 - Transportation Information

DOT: Non-regulated

Ocean (IMDG): Non-regulated

Air (IATA): Non-regulated

WHMIS (Canada): Non-regulated

## Section 15 - Regulatory Information

## **Regulatory Data**

Ingredient Name: Zinc Chloride

SARA 313 No

TSCA Inventory Yes

CERCLA RQ 1000 lb.

RCRA Code N/A

## **Regulatory Data (cont.)**

Ingredient Name: Ammonium Chloride

SARA 313 No

TSCA Inventory Yes

CERCLA RQ N/A

RCRA Code N/A

Ingredient Name: Petrolatum

SARA 313 No

TSCA Inventory Yes

CERCLA RQ N/A

RCRA Code N/A

Ingredient Name: Petroleum Distillates

SARA 313 No

TSCA Inventory Yes

CERCLA RQ N/A

RCRA Code N/A

## Section 16 - Other Information

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made.

Consult RectorSeal for further information: (713) 263-8001

#### SAFETY DATA SHEET

SDS 0497

\_\_\_\_\_\_ Section 1 -- PRODUCT AND COMPANY IDENTIFICATION HMIS CODES PRODUCT NAME Health Flammability Nokorode Cold Weather Paste Flux Reactivity PRODUCT CODES PPI 14700, 14720, 14730 CHEMICAL FAMILY: Organic/Inorganic USE Soldering Flux MANUFACTURER'S NAME EMERGENCY TELEPHONE NO. The RectorSeal Corporation Chemtrec 24 Hours 2601 Spenwick Drive (800)424-9300 USA Houston, Texas 77055 USA (703)527-3887 International DATE OF VALIDATION TECHNICAL SERVICE TELEPHONE NO. January 23, 2015 (800)231-3345 or (713)263-8001 DATE OF PREPARATION May 2, 2012 \_\_\_\_\_\_ Section 2 -- HAZARDS IDENTIFICATION EMERGENCY OVERVIEW OSHA Hazards Irritant GHS CLASSIFICATION PHYSICAL HAZARDS: None HEALTH HAZARDS Acute Toxicity Oral: Not Classified Dermal: Not Classified Inhalation: Not Classified Skin Corrosion/Irritation: Not Classified Serious Eye Damage/Eye Irritation: Not Classified Respiratory or Skin Sensitization: Not Classified Germ Cell Mutagenicity: Not Classified Carcinogenicity: Not Classified Reproductive Toxicology: Not Classified Target Organ Systemic Toxicity - Single Exposure: Not Classified Target Organ Systemic Toxicity - Repeated Exposure: Not Classified Aspiration Toxicity: Not Classified \_\_\_\_\_\_ ENVIRONMENTAL HAZARDS Hazardous to the Aquatic Environment: Not Classified Acute aquatic toxicity: Not Classified Chronic aquatic toxicity: Not Classified Bioaccumulation potential: Not Classified Rapid degradability: Not Classified \_\_\_\_\_\_

GHS Label elements, including precautionary statements

```
Pictogram: Irritant
Signal Word: Warning
Hazard Statements
H302 - Harmful if swallowed.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
Precautionary Statements:
P102 - Keep out of reach of children.
P262 - Do not get in eyes, on skin, or on clothing.
P264 - Wash hands thoroughly after handling.
P281 Use personal protective equipment as required.
______
SUMMARY OF ACUTE HAZARDS
  Irritation to respiratory system from fumes evolved during soldering.
Eye contact may cause intense irritation and injury.
ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS
INHALATION
  Irritation to respiratory system from fumes evolved during soldering.
EYE CONTACT
  Contact may cause intense irritation and injury.
SKIN CONTACT
  May cause skin irritation.
INGESTION
  Nausea, vomiting, irritation to digestive system.
SUMMARY OF CHRONIC HAZARDS
  Short term effects to liver and kidneys can occur. Chemical irritation
from continued skin contact can occur. Continuous industrial use in small
unventilated areas may result in sufficient inhalation of solder and flux
fumes to cause lung damage and irritation of respiratory tract.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
 Individuals with pre-existing or chronic diseases of the eyes, skin,
 respiratory system, cardiovascular system, gastrointestinal system, liver,
 or kidneys may have increased susceptibility to excessive exposure.
______
         Section 3 -- COMPOSITION/INFORMATION ON INGREDIENTS
INGREDIENT: Zinc Chloride
PERCENTAGE BY WEIGHT: 10-25
CAS#: 7646-85-7
EC#: 231-592-0
______
INGREDIENT: Ammonium Chloride
PERCENTAGE BY WEIGHT: 10-25
CAS#: 12125-02-9
EC#: 235-186-4
______
INGREDIENT: Petrolatum
PERCENTAGE BY WEIGHT: 70-90
CAS#: 8009-03-8
EC#: 232-373-2
INGREDIENT: Petroleum Distillates
```

EVAPORATION RATE (ETHYL ACETATE = 1): N/A
APPEARANCE/ODOR: Tan / Petroleum Odor

120-150 F (52-66 C)

PERCENTAGE BY WEIGHT: < 0.01 @ 68 F (20 C)

MELTING POINT:

VAPOR DENSITY (AIR = 1):

SOLUBILITY IN WATER: Insoluble VOLATILE ORGANIC COMPOUNDS(VOC)Content (Theoretical Percentage By Weight): 0% or (0 g/L)Flash POINT >400 F (204 C) SETA CC LOWER EXPLOSION LIMIT N/D UPPER EXPLOSION LIMIT N/D \_\_\_\_\_\_ Section 10 -- STABILITY AND REACTIVITY \_\_\_\_\_ STABILITY: Stable CONDITIONS TO AVOID: None INCOMPATIBILITY (MATERIALS TO AVOID): None known HAZARDOUS DECOMPOSITION PRODUCTS: Toxic fumes of zinc, chlorine, and HCL may be evolved during soldering. HAZARDOUS POLYMERIZATION: Will not occur. \_\_\_\_\_\_ Section 11 -- TOXICOLOGY INFORMATION CHRONIC HEALTH HAZARDS No ingredient in this product is an IARC, NTP or OSHA listed carcinogen. \_\_\_\_\_\_ TOXICOLOGY DATA Ingredient Name Zinc Chloride Oral-Rat LD50:350 mg/kg Inhalation-Rat LCLo:1960 mg/m3/10M Ammonium Chloride Oral-Rat LD50:1650 mg/kg Inhalation-Rat LC50:N/D Petrolatum Oral-Rat LD50:N/D Inhalation-Rat LC50:N/D Petroleum Distillates Oral-Rat LD50:N/D Inhalation-Rat LC50:N/D \_\_\_\_\_\_ Section 12 -- Ecological Information ECOLOGICAL DATA Ingredient Name Zinc Chloride Food Chain Concentration Potential None WATERFOWL TOXICITY N/A AQUATIC TOXICITY: 7.2 ppm/96 hr/medium bluegill/TLm Ammonium Chloride Food Chain Concentration Potential None WATERFOWL TOXICITY N/AAQUATIC TOXICITY: 6 ppm/96 hr/sunfish TLm Petrolatum Food Chain Concentration Potential N/DWATERFOWL TOXICITY N/D

N/D

N/D

BOD

AQUATIC TOXICITY:

```
Petroleum Distillates
```

Food Chain Concentration Potential N/DWATERFOWL TOXICITY N/D BOD N/D AQUATIC TOXICITY: N/D

\_\_\_\_\_\_

Section 13 -- DISPOSAL CONSIDERATIONS

\_\_\_\_\_\_

Waste Classification: Non-regulated solid waste

Disposal Method: Approved landfill

Waste from this product is not considered hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with Federal, State, and Local regulation regarding pollution.

\_\_\_\_\_\_

Section 14 -- TRANSPORTATION INFORMATION

DOT: Non-Regulated OCEAN (IMDG): Non-Regulated AIR (IATA): Non-Regulated WHMIS (CANADA): Non-Regulated

\_\_\_\_\_\_

Section 15 -- REGULATORY INFORMATION

\_\_\_\_\_\_

REGULATORY DATA Ingredient Name

\_\_\_\_\_\_

Zinc Chloride

Yes SARA 313 TSCA Inventory Yes CERCLA RQ 1000 lb.

RCRA Code N/A

Ammonium Chloride

SARA 313 No TSCA Inventory CERCLA RQ N/A RCRA Code N/A

Petrolatum

SARA 313 TSCA Inventory Yes CERCLA RO N/A RCRA Code N/A

Petroleum Distillates

SARA 313 No TSCA Inventory CERCLA RO N/AN/A RCRA Code

\_\_\_\_\_\_

Section 16 -- OTHER INFORMATION

\_\_\_\_\_

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further

information: (713) 263-8001