

The logo for RectorSeal, featuring the brand name in a bold, sans-serif font inside a stylized red and white shield-like border.

SAFETY DATA SHEET

DESOLV™

Mini-split evaporator coil and blower fan cleaner

Sid Harvey item #'s 82560, 82561, 82562 & 82565

SDS# Z0801

SECTION 1 – PRODUCT AND COMPANY INFORMATION

Product Name

Desolv™

Product Codes

82560, 82565

Chemical Family

Organic/Inorganic

Use

Coil cleaner

Manufacturer's Name

The RectorSeal Corporation

2601 Spenwick Drive

Houston, Texas 77055 USA

Date of Validation

April 1, 2015

Date of Preparation

April 1, 2015

HMIS Codes

Health 2

Flammability 0

Reactivity 0

PPI B

Emergency Telephone No.

Chemtrec 24 Hours

(800)-424-9300 USA

(703)-527-3887 International

Technical Service Telephone No.

(800)-231-3345 or (713)-263-8001

SECTION 2 – HAZARDS IDENTIFICATION

GHS CLASSIFICATION**Physical Hazards**

None

Health Hazards

Acute Toxicity

Oral: Not Classified

Dermal: Not Classified

Inhalation: Not Classified

Skin Corrosion/Irritation: Not Classified

Serious Eye Damage/Eye Irritation: Not Classified

Respiratory or Skin Sensitization: Not Classified

Germ Cell Mutagenicity: Not Classified

Carcinogenicity: Not Classified

Reproductive Toxicology: Not Classified


Target Organ Systemic Toxicity - Single Exposure: Not Classified
Target Organ Systemic Toxicity - Repeated Exposure: Not Classified

Aspiration Toxicity: Not Classified

ENVIRONMENTAL HAZARDS

Hazardous to the Aquatic Environment: Not Classified
Acute aquatic toxicity: Not Classified
Chronic aquatic toxicity: Not Classified
Bioaccumulation potential: Not Classified
Rapid degradability: Not Classified

GHS Label elements, including precautionary statements



GHS04: Compressed Gas Cylinder
GHS07: Harmful/Irritant Exclamation Mark
Signal Word: **Warning**

Hazard Statements

H303 - May be harmful if swallowed.
H313 - May be harmful in contact with skin.
H335 + H336 - May cause respiratory irritation, and drowsiness or dizziness.

Precautionary Statements

P102 - Keep out of reach of children.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P262 - Do not get in eyes, on skin, or on clothing.
P264 - Wash hands thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P310 - IF SWALLOWED: Immediately call a **POISON CENTER** or doctor/physician.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P362 - Take off contaminated clothing and wash before reuse.

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU No. 1272/2008

Summary Of Acute Hazards

Irritation to eyes, nose, and throat; drowsiness, narcosis, tremors, and other CNS effects at high concentrations.
Skin irritation, dermatitis, and defatting.

Route Of Exposure, Signs And Symptoms

INHALATION

Nasal and respiratory irritation, dizziness, narcosis, headache, nausea, CNS depression, and unconsciousness.

EYE CONTACT

Watering, blurred vision, inflammation, and irritation which can result in corneal injury.

SKIN CONTACT

Irritation, dermatitis.

INGESTION

Nausea, vomiting; CNS depression; irritation of gastrointestinal tract, liver and peritoneal wall; lung congestion.

SUMMARY OF CHRONIC HAZARDS

Skin irritation, contact dermatitis, and defatting.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver, or kidneys may have increased susceptibility to excessive exposure.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

| | |
|------------------------------|---------------------------------|
| Ingredient: | Di(ethylene glycol) hexyl ether |
| Percentage By Weight: | 1-5 |
| CAS Number: | 112-59-4 |
| EC#: | 203-988-3 |

SECTION 4 – FIRST AID MEASURES

| | |
|----------------------|---|
| If inhaled: | If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential. |
| If on skin: | Immediately wash with soap and water. Remove and wash any contaminated clothing. |
| If in eyes: | Flush with large amounts of water for at least 15 minutes. Get medical attention if irritation persists. |
| If swallowed: | If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person. |

SECTION 5 – FIRE FIGHTING MEASURES**Extinguishing Media**

Non-flammable. Use agents appropriate for surrounding fires.

Special Fire Fighting Procedures: None.

Unusual Fire And Explosion Hazards: None known.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Remove all sources of ignition. Use absorbent materials to prevent footing hazard and to contain. Ventilate area with natural or explosion-proof, forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup.

SECTION 7 – HANDLING AND STORAGE

Precautions To Be Taken In Handling And Storing: Use absorbent materials to prevent footing hazard and to contain.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection (Specify Type): In confined, poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air respirators during soldering operations until fumes have dissipated.

Ventilation – Local Exhaust: Acceptable.

Special: Explosion proof.

Mechanical (General): Acceptable.

Other: N/A

Protective Gloves: Wear rubber gloves.

Eye Protection: Safety glasses (ANSI Z-87.1 or equivalent)

Other Protective Clothing Or Equipment: Chemical resistant coveralls recommended.

Work/Hygienic Practices: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|----------------------------|
| Boiling point: | > 212°F (100°C) @ 760mm Hg |
| Specific gravity (H2O = 1): | 0.99 |
| Vapor pressure (mmHg): | 17 @ 68°F (20°C) |
| Melting point: | N/A |
| Vapor Density (Air = 1): | < 1 |
| Evaporation rate (Ethyl Acetate = 1): | > 1 |
| Appearance/Odor: | Clear liquid/Mild odor |
| Volatile Organic Compounds (VOC) Content (Theoretical Percentage By Weight): | 4% or (40 g/L) |
| Solubility in water: | Soluble |
| Flash point: | None SETA CC |
| Lower explosion limit: | None |
| Upper explosion limit: | None |

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable

Conditions To Avoid: None.

Incompatibility (Materials To Avoid): Heat, sparks and open flames.

Hazardous Decomposition Products: CO, CO₂, and fragmented hydrocarbons.

Hazardous Polymerization: Will not occur.

SECTION 11 – TOXICOLOGY INFORMATION

Chronic Health Hazards

No ingredient in this product is an IARC, NTP or OSHA Lister carcinogen.

Toxicology Data

Ingredient Name

Di(ethylene glycol) hexyl ether

Oral-Rat LD50: 2400 mg/kg

Inhalation-Rat: No Data

SECTION 12 – ECOLOGICAL INFORMATION

Ecological Data

| | |
|------------------------------------|--|
| Ingredient Name: | Di(ethylene glycol) hexyl ether |
| Food Chain Concentration Potential | N/D |
| Waterfowl Toxicity | N/D |
| BOD | N/D |
| Aquatic Toxicity | N/D |

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Classification: Non-regulated liquid waste.

Disposal Method: Dispose of all liquid waste in accordance with local, state and federal regulations.

SECTION 14 – TRANSPORTATION INFORMATION

| | |
|-----------------|---------------|
| DOT: | Non-regulated |
| Ocean (IMDG): | Non-regulated |
| Air (IATA): | Non-regulated |
| WHMIS (Canada): | Non-regulated |

SECTION 15 – REGULATORY INFORMATION

Regulatory Data

| | |
|------------------|--|
| Ingredient Name: | Di(ethylene glycol) hexyl ether |
| SARA 313 | Yes |
| TSCA Inventory | Yes |
| CERCLA RQ | N/A |
| RCRA Code | N/A |

SECTION 16 – OTHER INFORMATION

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200).
The information herein is given in good faith, but no warranty, expressed or implied is made.

Consult RectorSeal for further information: (713) 263-8001