SDS# Pro-Blue Date: October 2015 Total Pages: 6

Sid Harvey item # PRO-BLUE

SDS Z0824

DIVERSITECH

Pro-Blue[™]

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Pro-Blue Catalog Number: Pro-Blue Manufactured by: DiversiTech Corporation 6650 Sugarloaf Parkway Duluth, GA, 30097 Information Phone No.: 1+678.542.3600 EMERGENCY Phone No.: 1 800.255.3924 Chem-Tel (Chemical Emergencies) PREPARED BY: V. Leone

SECTION 2. HAZARDOUS INGREDIENTS INFORMATION

GHS Classification:

Skin Irritation Category 1B Eye Irritation Category 1

Label Elements:



Signal Word Danger!

Hazard Statement(s)

H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage.

Precautionary statement(s)

P102	Keep out of reach of children.
P103	Read label before use.
P260	Do not breathe mist or spray.
P264	Wash thoroughly after handling.
P280	Wear rubber, neoprene or nitrile gloves and protective clothing, and safety goggle or a face shield to protect eyes and face.

Response

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse SKIN with water or shower.			
P363 Wash contaminated clothing before reuse.			
P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			
P310 Immediately call a POISON CENTER or doctor.			
P405 Store locked up			
Dispose of contents and container to appropriate facility in accordance with Federal, State, and local regulations.			

DIVERSITECH

Pro-Blue[™]

SECTION 3. HAZARDOUS INGREDIENTS INFORMATION

INGREDIENT	CAS No.	EINECS No.	% or Range	GHS Classification
Water	7732-18-5	231-791-2	60-80	Not classified
Sodium hydroxide	1310-73-2	215-185-5	15-20	H314: Skin CorrosionCategory 1AH318: Eye DamageCategory 1H402: Aquatic AcuteCategory 3
Sodium Carbonate	497-19-8	207-838-8	1-3	H315: Skin Irritant Category 2 H319: Eye Irritant Category 2A
Sodium Gluconate	527-07-1	208-407-7	1-3	H515: Skin Irritant Category 2 H319: Eye Irritant Category 2B

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician. Ingestion: Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately. Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

Note to Physician: Perform endoscopy in all cases of suspected sodium hydroxide ingestion. In cases of severe esophageal corrosion, consider the use of therapeutic doses of steroids. General supportive measures with continual monitoring of gas exchange, acid-base balance, electrolytes, and fluid intake are also required.

4.2. Signs and Symptoms of Exposure:

Inhalation: Effects from inhalation of mist and spray may cause serious damage of the upper respiratory tract, depending on severity of exposure. Symptoms may vary from mild to severe irritation, sneezing, sore throat or runny nose. Severe pneumonitis may occur.

Ingestion: Symptoms may include burns of mouth, throat, and stomach bleeding, vomiting, diarrhea, fall in blood pressure.

Skin Contact: Contact with skin can cause redness, irritation or severe burns and scarring with greater exposures.

Eye Contact: Contact with mist, spray or liquid causes redness, severe irritation or burning in eyes. Prolonged exposures can cause burns that may result in permanent impairment of vision, even blindness.

Chronic Exposure: Prolonged contact with dilute solutions or mists has a destructive effect upon tissue.

SECTION 5. FIREFIGHTING MEASURES

Suitable and Unsuitable Extinguishing Media:

This product is not flammable. However, sodium hydroxide solutions can react with non-ferrous metals to generate flammable hydrogen gas. Use dry chemical, carbon dioxide, or foam. Use water to cool fire-exposed containers and to protect personnel. Do not direct a solid stream of water or foam into hot, burning pools. This may result in frothing and increase fire intensity.

Special Equipment and Precautions for Fire-Fighters:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face-piece operated in the pressure demand or other positive pressure mode.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Ventilate area of leak or spill. Keep unnecessary and unprotected people away from area of spill. Wear appropriate personal protective equipment and clothing during clean-up.

Methods and Material for Containment and Clean-Up: Contain and recover liquid when possible. Do not flush caustic residues to the sewer. Residues from spills can be diluted with water, then neutralized with dilute acid such as acetic, hydrochloric or sulfuric. Absorb neutralized caustic residue on clay, vermiculite or other inert substance and package in a suitable container for disposal. do not use aluminum tools to collect absorbed material or aluminum containers to store collected waste. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities (700 gallons) of this product. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. Remove contaminated clothing immediately.

Pro-Blue[™]

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling: Keep in a tightly closed container. Protect from physical damage. Keep this and all chemicals out of the reach of children. Avoid contact with eyes and skin. Avoid inhalation of vapors and mists. Wash thoroughly after handling.

Conditions for Safe Storage, Including any Incompatibilities: Store locked up. Protect from freezing. Containers of this material may be hazardous when empty since they retain product residues. Do not store with aluminum or magnesium. Do not mix with acids or organic materials. Observe all warnings and precautions listed for the product.

DIVERSITE

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Airborne Exposure Limits: Sodium Hydroxide: OSHA Permissible Exposure Limit (PEL): 15 mg/m3 Ceiling ACGIH Threshold Limit Value (TLV): 15 mg/m3 Ceiling

Appropriate Engineering Controls:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, <u>Industrial Ventilation, A Manual of Recommended Practices</u>, most recent edition, for details.

Personal Respirators: If the exposure limit is exceeded and engineering controls are not feasible, a half face piece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-face piece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection: Wear rubber, neoprene, nitrile, Saranex® boots, gloves, lab coat, apron or coveralls, as necessary and appropriate, to prevent skin contact.

Eye Protection: Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities or a source of running water in the work area.

Work Hygienic Practices: Use proper industrial hygiene practices to minimize hazardous exposure. Wash hands after handling this material, and before eating, smoking or using the bathroom.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Blue liquid Odor: Odorless Odor Threshold: Not established pH @ 25°C: 14 Melting Point (Pour Point): <25°F Boiling Point: >200°F Flash Point: Not established Evaporation Rate (Water = 1): >1 Flammable Limits: Not established LEL: N/A Vapor pressure (mm Hg): Same as water Vapor Density (Air = 1): Same as water Specific gravity (H2O = 1): 1.190 Solubility in water: Water miscible Octanol/Water Partition Coefficient: Not available Autoignition Temperature: Not available Decomposition Temperature: Not available

Pro-Blue[™]

SECTION 10. STABILITY AND REACTIVITY

Chemical Stability: Stable under ordinary conditions of use and storage.

Possibility of Hazardous Reactions: Will not occur.

Conditions to Avoid: Extreme heat, incompatibles.

Incompatible Materials: Sodium hydroxide in contact with acids and organic halogen compounds, especially trichloroethylene, may cause violent reactions. Contact with nitro methane and other similar nitro compounds causes formation of shock-sensitive salts. Contact with metals such as aluminum, magnesium, tin, and zinc cause formation of flammable hydrogen gas. Sodium hydroxide, even in fairly dilute solution, reacts readily with various sugars to produce carbon monoxide.

Hazardous Decomposition Products: Sodium oxide. Decomposition by reaction with non-ferrous metals releases flammable and explosive hydrogen gas.

DIVERSITECH

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects:

Inhalation: Effects from inhalation of mist and spray may cause serious damage of the upper respiratory tract, depending on severity of exposure. Symptoms may vary from mild to severe irritation, sneezing, sore throat or runny nose. Severe pneumonitis may occur. Ingestion: Symptoms may include burns of mouth, throat, and stomach bleeding, vomiting, diarrhea, fall in blood pressure.

Skin Contact: Contact with skin can cause redness, irritation or severe burns and scarring with greater exposures.

Eye Contact: Contact with mist, spray or liquid causes redness, severe irritation or burning in eyes. Prolonged exposures can cause burns that may result in permanent impairment of vision, even blindness.

Chronic Exposure: Prolonged contact with dilute solutions or mists has a destructive effect upon tissue.

Carcinogenic effects: Not classified

Teratogenicity/Reproductive toxicity: Not classified Mutagenic effects: Not classified

Numerical Measures of Toxicity:

Sodium hydroxide (irritation data): Skin, rabbit: 500 mg/24H severe; Eye rabbit: 50 ug/24H severe.

Sodium Carbonate (acute toxicity): Oral, LD50, rat: >2,000 mg/kg Inhalation, rat: 2.3 mg/l 2h (chronic toxicity): Inhalation, rat, target organ: lungs, 0.07 mg/l, observed effect. No effect on reproduction. Irritation: Rabbit, non-irritant (skin). Rabbit, irritant (eyes).

Sodium Gluconate: ivn-rbt LDLo: 7630 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity: Sodium hydroxide: Fish: Carp: 180ppm (LC100); 24H; Aquatic: This product is toxic to Aquatic Life. Toxicity is primarily associated with pH. Persistence and Degradability: Biodegradable Bioaccumulative Potential: No data available Mobility in Soil: No data available. Can be dangerous if allowed to enter drinking water intakes. Do not contaminate domestic or irrigation water supplies, lakes, streams, ponds, or rivers. Other Adverse Effects: None known Other: For more information, see <u>"HANDBOOK OF ENVIRONMENTAL FATE AND EXPOSURE DATA."</u>

SECTION 13. DISPOSAL CONSIDERATIONS

Dispose of spill clean- up and other wastes in accordance with Federal, State, and local regulations. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Treat empty containers as hazardous. Dispose of container and unused contents in accordance with federal, state and local requirements. **RCRA Hazard Class (if discarded):** CORROSIVE D002.

Pro-Blue[™]

SECTION 14. TRANSPORTATION INFORMATION

US DOT: UN3266, Corrosive liquid, basic, inorganic, N.O.S. (contains sodium hydroxide), 8, PGII DOT Proper Shipping Name: Corrosive liquid, basic inorganic, N.O.S. (contains sodium hydroxide) DOT Hazard Class: 8 UN Number: UN3266 Packing Group: || IMO: UN3266, Corrosive liquid, basic, inorganic, N.O.S. (contains sodium hydroxide), 8, PGII Limited Quantity: No Marine Pollutant: No ADR/RID Class: 8 ADR/RID Packing Group: || IMDG Hazard Class: 8 IMDG Packing Group: || ADNR Class: 8 ADNR Item: UN3266 IATA Hazard Class: 8 IATA Packing Group: || Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15. REGULATORY INFORMATION

US EPA

Comprehensive Environmental Response Compensation and Liability

Act of 1980 (CERCLA) requires notification of the National Response Center of release quantities of Hazardous Substances is not required for this material.

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires emergency planning based on threshold planning quantities and release reporting based on reportable quantities in 40 CFR 355 (used for SARA 302, 304, 311, and 312) is not required for quantities below 250 pounds. Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372 (for SARA 313). This material is not subject to reporting requirements.

Toxic Substances Control Act (TSCA) Status: The ingredients of this product is not listed on the TSCA inventory.

State Right to Know

California Proposition 65: This product does not contain any materials on the Proposition 65 List of Chemicals Known to Cause Cancer or Reproductive Toxicity.

Massachusetts: Hazardous substances and extraordinarily hazardous substances must be identified. Pennsylvania: Hazardous substances must be identified. California SCAQMD Rule 443.1 (VOC's): None

Chemical Inventory Status

Canada

Ingredient Sodium Hydroxide (1310-73-2)	TSCA EC Yes Yes	Japan Yes	Austra Yes		lorea les	DSL Yes	NDSL No	Phil. Yes
Federal, State & International Regulation								
	SARA 302	SARA	313	TSCA	CERC	CLA 26	1.33 8(d)	
Ingredient	RQ TPQ C	hemical	RCRA	List -				
Sodium Hydroxide (1310-73-2)	No No	No	1000	No	No			

Chemical Weapons Convention: No

TSCA 12(b): No CDTA: No

SARA 311/312: Acute: Yes Chronic: Yes Fire: No Pressure: No Reactivity: Yes (Mixture / Liquid) Australian Hazchem Code: 2R Poison Schedule: S6

WHMIS:

This SDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

DIVERSITECH

Pro-Blue[™]

SECTION 16. OTHER INFORMATION:

Revision Summary: All Sections: New GHS Format SDS DATE REVISED: 10/09/2015

RCRA Hazard Class (if discarded): CORROSIVE D002.

HMIS III Ratings HMIS III®

Health	3
Flammability	0
Physical Hazard	1
Personal Protection	1

This information is, to the best of our knowledge and belief, accurate and reliable as of the date completed. However no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the completeness and suitability of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information, nor do we offer any warranty against patent infringement.

DIVERSITECH