Printing date 09.04.2013 Revision: 04.04.2013

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: LEAK LOCK GOLD
- · Article number: 11001,11004,11016,11128,11550
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the preparation Sealant
- · 1.3 Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Highside Chemicals, Inc. 11114 Reichold Road Gulfport, MS 39503 USA Phone: (228) 896-9220

· 1.4 Emergency telephone number:

ChemTel Inc.

(800)255-3924, +1 (813)248-0585

2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



F; Highly flammable

Highly flammable. R11:

Vapours may cause drowsiness and dizziness.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 09.04.2013 Revision: 04.04.2013

Trade name: LEAK LOCK GOLD

· Hazard pictograms







- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour. H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

Keep out of reach of children. P102

P103 Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P210

Wear protective gloves and eye protection. P280

Keep container tightly closed. P233 Avoid breathing mist/vapours/spray. P261

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool. P403+P235

- · Hazard description:
- · WHMIS-symbols:

B2 - Flammable liquid

D2B - Toxic material causing other toxic effects





· NFPA ratings (scale 0 - 4)



Health = 1 Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



1 Health = 1

3 Fire = 3

· HMIS Long Term Health Hazard Substances

64-17-5 ethanol

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 3)

Printing date 09.04.2013 Revision: 04.04.2013

Trade name: LEAK LOCK GOLD

· **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- · 3.2 Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5	ethanol	25-50%
CAS: 14807-96-6 EINECS: 238-877-9	Talc (Mg3H2(SiO3)4)	25-50%
EINECS: 200-661-7 Index number: 603-117-00-0	propan-2-ol	<10%

· Additional information:

For the wording of the listed risk phrases refer to section 16.

Dried product contains substances which are considered nuisance dusts which require a NIOSH Breathing airborne particles or dust from mixing, spraying, sanding, grinding, etc. may cause irritation to respiratory tract.

4 First aid measures

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately rinse with water.

Clean with water and soap.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Dizziness

(Contd. on page 4)

Printing date 09.04.2013 Revision: 04.04.2013

Trade name: LEAK LOCK GOLD

(Contd. of page 3)

Headache

Nausea

Thirst

Disorientation

- · Hazards Condition may deteriorate with alcohol consumption.
- · 4.3 Indication of any immediate medical attention and special treatment needed

Monitor circulation.

If necessary oxygen respiration treatment.

Medical supervision for at least 48 hours.

Contains ethanol and isopropanol.

5 Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · For safety reasons unsuitable extinguishing agents: None.
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Eliminate all ignition sources if safe to do so.

Cool endangered receptacles with water spray.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Protect from heat.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Suppress gases/fumes/haze with water haze or fog.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dilute with plenty of water.

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)

Printing date 09.04.2013 Revision: 04.04.2013

Trade name: LEAK LOCK GOLD

See Section 13 for disposal information.

(Contd. of page 4)

7 Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Keep away from heat and direct sunlight.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Flammable gas-air mixtures may form in empty receptacles.

Fumes can combine with air to form an explosive mixture.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

Do not store together with acids.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:				
64-17-5 ethai	nol			
PEL (USA)	1900 mg/m³, 1000 ppm			
REL (USA)	1900 mg/m³, 1000 ppm			
TLV (USA)	Short-term value: 1880 mg/m³, 1000 ppm			
EL (Canada)	Short-term value: 1000 ppm			
EV (Canada)	1,900 mg/m³, 1,000 ppm			
67-63-0 prop	67-63-0 propan-2-ol			
PEL (USA)	980 mg/m³, 400 ppm			
	(Contd. on page 6)			

(Contd. on page 6)

Printing date 09.04.2013 Revision: 04.04.2013

Trade name: LEAK LOCK GOLD

REL (USA) Short-term value: 1225 mg/m³, 500 ppm
Long-term value: 980 mg/m³, 400 ppm

TLV (USA) Short-term value: 984 mg/m³, 400 ppm
Long-term value: 492 mg/m³, 200 ppm
BEI

EL (Canada) Short-term value: 400 ppm
Long-term value: 200 ppm

EV (Canada) Short-term value: 400 ppm
Long-term value: 200 ppm
Long-term value: 200 ppm

- · **DNELs** No further relevant information available.
- · PNECs No further relevant information available.
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when high concentrations are present.

For spills, respiratory protection may be advisable.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 7)

Printing date 09.04.2013 Revision: 04.04.2013

Trade name: LEAK LOCK GOLD

(Contd. of page 6)

- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

See Section 7 for additional information. No further relevant information available.

9.1 Information on basic physical	and chemical properties
General Information Appearance:	
Form:	Pasty
Colour:	Gold coloured
Odour:	Alcohol-like
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	172 °F / 78 °C
Flash point:	59 °F / 15 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	>500 °F / 260 °C
Decomposition temperature:	Not determined.
Self-igniting:	Product is not self-igniting.
Danger of explosion:	Product is not explosive. However, formation of explosive ai vapour mixtures are possible.
Explosion limits:	
Lower:	3,5 Vol %
Upper:	15,0 Vol %
Vapour pressure at 20 °C:	59 hPa
Density at 20 °C:	1,2 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.

Printing date 09.04.2013 Revision: 04.04.2013

Trade name: LEAK LOCK GOLD

(Contd. of page 7)

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents: Not determined.

VOC (US EPA Method 24) 35 %

9.2 Other informationNo further relevant information available.

10 Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Flammable.

Used empty containers may contain product gases which form explosive mixtures with air.

Can react violently with oxygen rich (oxidizing) material. Danger of Explosion.

Strong exothermic reaction with acids.

Develops readily flammable gases/fumes.

10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

Store away from oxidizing agents.

- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Danger of forming toxic pyrolysis products.

11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Slight irritant effect on skin and mucous membranes.
- on the eye: Slight irritant effect on eyes.
- Sensitization: No sensitizing effects known.
- · Subacute to chronic toxicity: Vapours have narcotic effect.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful Irritant

(Contd. on page 9)

Printing date 09.04.2013 Revision: 04.04.2013

Trade name: LEAK LOCK GOLD

(Contd. of page 8)

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability The product is partially biodegradable. Significant residuals remain.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

This statement was deduced from the properties of the single components.

Due to available data on eliminability/decomposition and bioaccumulation potential a prolonged damage of the environment is unlikely.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with Local Authority requirements.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water only.

14 Transport information

- · 14.1 UN-Number
- · DOT, ADR, IMDG, IATA UN1133
- 14.2 UN proper shipping name
- · DOT, ADR, IMDG, IATA Adhesives

(Contd. on page 10)

Printing date 09.04.2013 Revision: 04.04.2013

Trade name: LEAK LOCK GOLD

	(Contd. of	f page
· 14.3 Transport hazard class(es)		
· DOT		
_		
PLOMBINE JOH D		
Class	3 Flammable liquids.	
· Label 		
· ADR		
₩ Olasa	O (E4) Flammahla Karitta	
· Class · Label	3 (F1) Flammable liquids. 3	
· IMDG, IATA		
· Class	3 Flammable liquids.	
Label	3	
· 14.4 Packing group		
DOT, ADR, IMDG, IATA	II	
· 14.5 Environmental hazards:		
· Marine pollutant:	No	
· 14.6 Special precautions for user	Warning: Flammable liquids.	
· Danger code (Kemler): · EMS Number:	33	
	F-E, <u>S-E</u>	
 14.7 Transport in bulk according to Ann MARPOL73/78 and the IBC Code 		
	Not applicable.	
· Transport/Additional information:		
· ADR		
· Limited quantities (LQ) · Transport category	5L 2	
· Tunnel restriction code	D/E	
· UN "Model Regulation":	UN1133, ADHESIVES, 3, II	

(Contd. on page 11)

Printing date 09.04.2013 Revision: 04.04.2013

Trade name: LEAK LOCK GOLD

(Contd. of page 10)

5 Regulatory information	
· 15.1 Safety, health and environmental regulations/legislation specific for the substa · United States (USA) · SARA	ince or mixture
· Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
67-63-0 propan-2-ol	
TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
· Proposition 65 (California):	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
 Chemicals known to cause developmental toxicity: Ethanol - listing refers specifically to alcoholic beverage consumption and is not applicable 64-17-5 ethanol 	e for product.
· Carcinogenic Categories	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
IARC (International Agency for Research on Cancer)	
64-17-5 ethanol	1
14807-96-6 Talc (Mg3H2(SiO3)4)	2B
TLV (Threshold Limit Value established by ACGIH)	
64-17-5 ethanol	A3
14807-96-6 Talc (Mg3H2(SiO3)4)	A4
67-63-0 propan-2-ol	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)	<u> </u>
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	
· Canada	
· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
	(Contd. on page 12

Printing date 09.04.2013 Revision: 04.04.2013

Trade name: LEAK LOCK GOLD

(Contd. of page 11)

· Canadian Ingredient Disclosure list (limit 0.1%)

64-17-5 ethanol

· Canadian Ingredient Disclosure list (limit 1%)

67-63-0 propan-2-ol

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

R11 Highly flammable.

R36 Irritating to eyes.

R67 Vapours may cause drowsiness and dizziness.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com