

## Freon<sup>™</sup> 407A (R-407A) Refrigerant

Version 8.4	Revision Date: 10/11/2020		DS Number: 336195-00039	Date of last issue: 02/27/2020 Date of first issue: 02/27/2017
SECTIO	N 1. IDENTIFICATION			
Pro	duct name	:	Freon™ 407A (R	-407A) Refrigerant
Pro	duct code	:	D14171414	
SD	S-Identcode	:	130000050502	
Ma	nufacturer or supplier's	det	ails	
Cor	npany name of supplier	:	The Chemours C	ompany FC, LLC
Ado	ress	:	1007 Market Stre Wilmington, DE 1	et 9801 United States of America (USA)
Tel	ephone	:	1-844-773-CHEM (outside the U.S. 1-302-773-1000)	
Em	Emergency telephone :			cy: 1-866-595-1473 (outside the U.S. 1-302- nsport emergency: +1-800-424-9300 (outside 527-3887)
Red	commended use of the	cher	nical and restricti	ons on use
Red	commended use	:	Refrigerant	
Res	trictions on use	:	For professional	users only.

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR
1910.1200)

Gases under pressure	: Liquefied gas
----------------------	-----------------

Simple Asphyxiant

#### **GHS** label elements

Hazard pictograms



Warning :

Hazard Statements


Signal Word

H280 Contains gas under pressure; may explode if heated. : May displace oxygen and cause rapid suffocation.

**Precautionary Statements** 

### Storage: P410 + P403 Protect from sunlight. Store in a well-ventilated place.

:



## Freon™ 407A (R-407A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 02/27/2020
8.4	10/11/2020	1336195-00039	Date of first issue: 02/27/2017

#### Other hazards

Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Pentafluoroethane#	354-33-6	40
1,1,1,2-Tetrafluoroethane#	811-97-2	40
Difluoromethane#	75-10-5	20

# Voluntarily-disclosed non-hazardous substance

### SECTION 4. FIRST AID MEASURES

General advice	:	In the case of accident or if you feel unwell, seek medical ad- vice immediately. When symptoms persist or in all cases of doubt seek medical advice.
lf inhaled	:	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	:	Thaw frosted parts with lukewarm water. Do not rub affected area. Get medical attention immediately.
In case of eye contact	:	Get medical attention immediately.
If swallowed	:	Ingestion is not considered a potential route of exposure.
Most important symptoms and effects, both acute and delayed	:	May cause cardiac arrhythmia. Other symptoms potentially related to misuse or inhalation abuse are Cardiac sensitization Anaesthetic effects Light-headedness Dizziness confusion Lack of coordination Drowsiness Unconsciousness Contact with liquid or refrigerated gas can cause cold burns and frostbite.
Protection of first-aiders	:	No special precautions are necessary for first aid responders.
Notes to physician	:	Because of possible disturbances of cardiac rhythm, ca- techolamine drugs, such as epinephrine, that may be used in



# Freon™ 407A (R-407A) Refrigerant

Vers 8.4	ion	Revision Date: 10/11/2020		0S Number: 36195-00039	Date of last issue: 02/27/2020 Date of first issue: 02/27/2017		
				situations of emer cial caution.	gency life support should be used with spe-		
SEC	SECTION 5. FIRE-FIGHTING MEASURES						
	Suitabl	e extinguishing media	:	Not applicable Will not burn			
	Unsuita media	able extinguishing	:	Not applicable Will not burn			
	Specifi fighting	c hazards during fire I	:		pustion products may be a hazard to health. rises there is danger of the vessels bursting por pressure.		
	Hazard ucts	lous combustion prod-	:	Fluorine compour Carbon oxides Hydrogen fluoride carbonyl fluoride			
	Specifi ods	c extinguishing meth-	:	cumstances and t Fight fire remotely Use water spray t	measures that are appropriate to local cir- he surrounding environment. due to the risk of explosion. o cool unopened containers. ged containers from fire area if it is safe to do		
		l protective equipment fighters	:	necessary.	ed breathing apparatus for firefighting if ective equipment.		

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Evacuate personnel to safe areas. Avoid skin contact with leaking liquid (danger of frostbite). Ventilate the area. Follow safe handling advice (see section 7) and personal pro- tective equipment recommendations (see section 8).
Environmental precautions	:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.
Methods and materials for containment and cleaning up	:	Ventilate the area. Local or national regulations may apply to releases and dispo- sal of this material, as well as those materials and items em- ployed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

ļ

į



## Freon™ 407A (R-407A) Refrigerant

Version 8.4	Revision Date: 10/11/2020	SDS Number: 1336195-00039	Date of last issue: 02/27/2020 Date of first issue: 02/27/2017
Tec	hnical measures		t rated for cylinder pressure. Use a backflow evice in piping. Close valve after each use and
Loca	al/Total ventilation	: Use only with a	adequate ventilation.
Adv	ice on safe handling	practice, based sessment Wear cold insu- Valve protection remain in place piped to use pro- Use a check vi- zardous back fi Drevent backfi Use a pressure to lower pressi Close valve aff or force fit con Prevent the int Never attempt Do not drag, s Use a suitable Keep away fro Take precaution	ordance with good industrial hygiene and safety d on the results of the workplace exposure as- alating gloves/ face shield/ eye protection. On caps and valve outlet threaded plugs must e unless container is secured with valve outlet oint. alve or trap in the discharge line to prevent ha- flow into the cylinder. ow into the gas tank. e reducing regulator when connecting cylinder ure (<3000 psig) piping or systems. ter each use and when empty. Do NOT change
Cor	nditions for safe storage	vent falling or Separate full o Do not store n Avoid area wh Keep in prope Keep in a cool Keep away fro	uld be stored upright and firmly secured to pre- being knocked over. containers from empty containers. ear combustible materials. ere salt or other corrosive materials are present. rly labeled containers. I, well-ventilated place. om direct sunlight. dance with the particular national regulations.
Mat	erials to avoid	Self-reactive s Organic perox Oxidizing ager Flammable liq Flammable so Pyrophoric liq Pyrophoric so Self-heating s Substances at flammable gas Explosives Acutely toxic s	nts uids lids uids lids ubstances and mixtures nd mixtures which in contact with water emit

4/19



## Freon™ 407A (R-407A) Refrigerant

Ver: 8.4		evision Date: 0/11/2020		0S Number: 36195-00039	Date of last issue: 02/27/2020 Date of first issue: 02/27/2017
	Recomme perature	ended storage tem-	:	< 126 °F / < 52 °C	;
	Storage p	eriod	:	> 10 y	
	Further in age stabil	formation on stor- ity	:	The product has a	an indefinite shelf life when stored properly.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Pentafluoroethane	354-33-6	TWA	1,000 ppm	US WEEL
1,1,1,2-Tetrafluoroethane	811-97-2	TWA	1,000 ppm	US WEEL
Difluoromethane	75-10-5	TWA	1,000 ppm	US WEEL

### Ingredients with workplace control parameters

#### Engineering measures


: Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

### Personal protective equipment

Respiratory protection	:	General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazar- dous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.
Hand protection Material	:	Low temperature resistant gloves
Remarks	:	Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to che- micals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the pro- duct. Change gloves often!
Eye protection	:	Wear the following personal protective equipment: Chemical resistant goggles must be worn. Face-shield
Skin and body protection	:	Skin should be washed after contact.



Versic 8.4	on Revision Date: 10/11/2020		S Number: 6195-00039	Date of last issue: 02/27/2020 Date of first issue: 02/27/2017
F	Protective measures	:	Wear cold insula	ting gloves/ face shield/ eye protection.
ŀ	łygiene measures		eye flushing syst king place. When using do n	emical is likely during typical use, provide ems and safety showers close to the wor- ot eat, drink or smoke. ted clothing before re-use.
SECT	ION 9. PHYSICAL AND CHE	MIC	AL PROPERTIE	S
A	Appearance	:	Liquefied gas	
C	Color	:	colorless	
C	Ddor	:	slight, ether-like	
C	Ddor Threshold	:	No data availab	le
p	ьН	:	No data availab	le
N	Melting point/freezing point	:	No data availab	le
	nitial boiling point and boiling ange	:	-49 °F / -45 °C	
			1	
F	Flash point	:	Not applicable	
E	Evaporation rate	:	Not applicable	
F	Flammability (solid, gas)	:	Will not burn	
	Jpper explosion limit / Upper lammability limit	:	Upper flammab Method: ASTM None.	ility limit E681
	Lower explosion limit / Lower lammability limit	:	Lower flammab Method: ASTM None.	
١	/apor pressure	:	12,531 hPa (77	°F / 25 °C)
F	Relative vapor density	:	3.2	
F	Relative density	:	1.15 (77 °F / 25	°C)
Ş	Solubility(ies) Water solubility	:	No data availab	le
F	Partition coefficient: n-	:	Not applicable	



Versior 8.4	Revision Date: 10/11/2020		S Number: 6195-00039	Date of last issue: 02/27/2020 Date of first issue: 02/27/2017
oc	tanol/water			
Au	toignition temperature	:	No data available	9
De	composition temperature	:	No data available	9
Vi	scosity Viscosity, kinematic	:	Not applicable	
Ex	Explosive properties		Not explosive	
O	Oxidizing properties		: The substance or mixture is not classified as oxidi:	
Pa	rticle size	:	Not applicable	
SECTIO	ON 10. STABILITY AND RI	EAC	τινιτγ	
Re	eactivity	:	Not classified as	a reactivity hazard.
Cł	nemical stability	:		directed. Follow precautionary advice and le materials and conditions.
Pc tio	ossibility of hazardous reac- ns	:	Can react with st	rong oxidizing agents.
Co	onditions to avoid	:	100 °C (212 °F) of this substance pressure and/or presence of an ig come combustib gen concentratio containing this su gen enriched atm the inter-relation and 3) the propo substance should mospheric press enriched environ	s not flammable in air at temperatures up to at atmospheric pressure. However, mixtures with high concentrations of air at elevated temperature can become combustible in the gnition source. This substance can also be- le in an oxygen enriched environment (oxy- ns greater than that in air). Whether a mixture ubstance and air, or this substance in an oxy- nosphere become combustible depends on ship of 1) the temperature 2) the pressure, rtion of oxygen in the mixture. In general, this d not be allowed to exist with air above at- ure or at high temperatures; or in an oxygen ment. For example this substance should ith air under pressure for leak testing or other I sparks.
In	compatible materials	:	Oxidizing agents	
	azardous decomposition oducts	:	No hazardous de	ecomposition products are known.




# Freon™ 407A (R-407A) Refrigerant

Versio 8.4	on Revision Date: 10/11/2020		9S Number: 36195-00039	Date of last issue: 02/27/2020 Date of first issue: 02/27/2017
SECT	ION 11. TOXICOLOGICAL	INFO	ORMATION	······································
lr S	nformation on likely routes nhalation Skin contact Sye contact	ofe	əxposure	
	cute toxicity lot classified based on availa	able	information.	
<u>C</u>	Components:			
=	Pentafluoroethane: Acute inhalation toxicity	:	LC50 (Rat): > 800 Exposure time: 4 Test atmosphere: Method: OECD T	h gas
			No observed adv Remarks: Cardia	erse effect concentration (Dog): 75000 ppm c sensitization
			Cardiac sensitisa Remarks: Cardia	tion threshold limit (Dog): 368.159 mg/m³ c sensitization
1	,1,1,2-Tetrafluoroethane:			
Д	Acute oral toxicity	:	Assessment: The icity	substance or mixture has no acute oral tox-
Δ	Acute inhalation toxicity	:	LC50 (Rat): > 56 Exposure time: 4 Test atmosphere Method: OECD T	h
			No observed adv Test atmosphere Remarks: Cardia	
			ppm Test atmosphere	adverse effect concentration (Dog): 80000 ; gas cause cardiac arrhythmia.
			Test atmosphere	tion threshold limit (Dog): 334,000 mg/m³ : gas cause cardiac arrhythmia.
A	Acute dermal toxicity	:	Assessment: The toxicity	substance or mixture has no acute dermal
	Difluoromethane: Acute oral toxicity	;	Assessment: The icity	e substance or mixture has no acute oral tox-

i

8/19



sion	Revision Date: 10/11/2020	SDS Number: 1336195-00039	Date of last issue: 02/27/2020 Date of first issue: 02/27/2017
Acute	inhalation toxicity	: LC50 (Rat): > 5 Exposure time: Test atmospher Method: OECD	4 h
		Test atmospher	lverse effect concentration (Dog): 350000 pp re: gas iac sensitization
		350000 ppm Test atmospher	ed adverse effect concentration (Dog): > re: gas iac sensitization
		Test atmospher	sation threshold limit (Dog): > 735,000 mg/m³ re: gas iac sensitization
Acute	e dermal toxicity	: Assessment: Ti toxicity	ne substance or mixture has no acute dermal
Skin corrosion/irritation Not classified based on availa <u>Components:</u>		ailable information.	
1,1,1 Resu	,2-Tetrafluoroethane It	: No skin irritatio	1.
<b>Diflu</b> Resເ	oromethane: It	No skin irritatio	1 · · · · · · · · · · · · · · · · · · ·
Serious eye damage/eye in Not classified based on avail <u>Components:</u>			
1,1,1 Resi	,2-Tetrafluoroethane	: : No eye irritation	1
Diflu Resu	oromethane: It	: No eye irritation	ı <sup>.</sup>
Resp	biratory or skin sensi	tization	
	sensitization	ailable information.	



sion	Revision Date: 10/11/2020		S Number: 36195-00039	Date of last issue: 02/27/2020 Date of first issue: 02/27/2017
Comp	onents:			
1,1,1,	2-Tetrafluoroethane	:		
	s of exposure	:	Skin contact	
Resul		:	negative	
	s of exposure	:	Inhalation	
Speci		:	Rat	
Resul	L	•	negative	
	s of exposure	:	Inhalation	
Speci Resul		:	Humans negative	
Nesu	L	•	negative	
Difluc	promethane:			
	s of exposure	:	Skin contact	
Resul	t	:	negative	
Germ	cell mutagenicity			
	assified based on av	ailable	information.	
Comp	oonents:			
Penta	fluoroethane:			
Geno	toxicity in vitro	:		terial reverse mutation assay (AMES)
			Method: OECE Result: negativ	) Test Guideline 471 e
			_	
			Test Type: In v Result: negativ	itro mammalian cell gene mutation test
				e ed on data from similar materials
				omosome aberration test in vitro ) Test Guideline 473
			Result: negativ	
Geno	toxicity in vivo		Test Type: Mai	nmalian erythrocyte micronucleus test (in viv
00.10			cytogenetic as	
			Species: Mous	
				ute: inhalation (gas) ) Test Guideline 474
			Result: negativ	
	0 7-4			•
	2-Tetrafluoroethane toxicity in vitro		Test Type: Rad	terial reverse mutation assay (AMES)
Genu				) Test Guideline 471
			Result: negativ	
			Test Type: Chi	omosome aberration test in vitro
			Method: OECE	) Test Guideline 473
			Result: negativ	e
Geno	toxicity in vivo	:	Test Type: Ma	mmalian erythrocyte micronucleus test (in vi
				·



sion	Revision Date: 10/11/2020	SDS Number:         Date of last issue: 02/27/2020           1336195-00039         Date of first issue: 02/27/2017
		cytogenetic assay) Species: Mouse Application Route: inhalation (gas) Method: OECD Test Guideline 474 Result: negative
		Test Type: Unscheduled DNA synthesis (UDS) test with mammalian liver cells in vivo Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 486 Result: negative
	n cell mutagenicity - ssment	: Weight of evidence does not support classification as a gen cell mutagen.
Diflu	oromethane:	
	toxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
		Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
Geno	toxicity in vivo	<ul> <li>Test Type: Mammalian erythrocyte micronucleus test (in viv cytogenetic assay)</li> <li>Species: Mouse</li> <li>Application Route: inhalation (gas)</li> <li>Method: OECD Test Guideline 474</li> <li>Result: negative</li> </ul>
	n cell mutagenicity - ssment	: Weight of evidence does not support classification as a ger cell mutagen.
	inogenicity lassified based on ava	ailable information.
Com	ponents:	
Spec Appli	cation Route sure time od	Rat inhalation (gas) 2 Years OECD Test Guideline 453 negative
Carci ment	inogenicity - Assess-	<ul> <li>Weight of evidence does not support classification as a car cinogen</li> </ul>
IARC		ent of this product present at levels greater than or equal to 0.1% is s probable, possible or confirmed human carcinogen by IARC.
	A No compo	

-



sion	Revision Date: 10/11/2020	SDS Number: 1336195-00039	Date of last issue: 02/27/2020 Date of first issue: 02/27/2017					
	on OSHA's	list of regulated carcin	ogens.					
NTP			of this product present at levels greater than or equal to 0.1% is known or anticipated carcinogen by NTP.					
•	oductive toxicity assified based on avai	lable information.						
<u>Comp</u>	onents:							
Penta	fluoroethane:							
Effect	s on fertility	Species: Rat Application Rou Result: negativ	e-generation reproduction toxicity study ute: inhalation (vapor) e ed on data from similar materials					
Effect	s on fetal developmen	Species: Rat Application Rot	oryo-fetal development ute: inhalation (gas) r Test Guideline 414 e					
1,1,1,	2-Tetrafluoroethane:							
Effect	s on fertility	: Species: Mous Application Ro Result: negativ	ute: Inhalation					
Effect	s on fetal developmen	reproduction/de Species: Rabb Application Ro	ute: inhalation (gas) 9 Test Guideline 414					
Repro sessn	oductive toxicity - As- nent	: Weight of evide ductive toxicity	ence does not support classification for repro					
Difluc	promethane:							
Effect	s on fertility	: Species: Mous Application Ro Result: negativ Remarks: Base	ute: Inhalation					
Effect	s on fetal developmer	reproduction/d Species: Rat Application Ro	nbined repeated dose toxicity study with the evelopmental toxicity screening test ute: inhalation (gas) ) Test Guideline 414 e					
			nbined repeated dose toxicity study with the evelopmental toxicity screening test					



sion	Revision Date: 10/11/2020		Number: 195-00039	Date of last issue: 02/27/2020 Date of first issue: 02/27/2017
		A N		e: inhalation (gas) Test Guideline 414
Repro sessn	eductive toxicity - As- nent		leight of evider uctive toxicity	nce does not support classification for repro
sтот	-single exposure			
Not cl	assified based on ava	lable inf	ormation.	
Comp	onents:			
1,1,1,	2-Tetrafluoroethane:			
Route	es of exposure ssment	: N		ealth effects observed in animals at concent pmV/4h or less
Difluc	promethane:			
	es of exposure ssment	: N		ealth effects observed in animals at concent pmV/4h or less
	-repeated exposure assified based on ava	ilable int	ormation	
	oonents:			
	 2-Tetrafluoroethane:			
Route	s of exposure	: N		ealth effects observed in animals at concent NV/6h/d or less.
Difluc	promethane:			
Route	<b>promethane:</b> es of exposure esment	: N	halation (gas) lo significant he ons of 250 ppn	ealth effects observed in animals at concen nV/6h/d or less.
Route Asses	es of exposure	: N	lo significant he	alth effects observed in animals at concen vV/6h/d or less.
Route Asses Repe	es of exposure ssment	: N	lo significant he	alth effects observed in animals at concen ìV/6h/d or less.
Route Asses Repe	es of exposure ssment ated dose toxicity	: N	lo significant he	alth effects observed in animals at concen vV/6h/d or less.
Route Asses Repe	ated dose toxicity	: N ti : F	lo significant he ons of 250 ppn	alth effects observed in animals at concen ìV/6h/d or less. ∖
Route Asses Repe Comp Penta Speci NOAE	es of exposure esement ated dose toxicity ponents: afluoroethane: es	: N ti : F : >	lo significant he ons of 250 ppn at = 50000 ppm	ealth effects observed in animals at concen iV/6h/d or less.
Route Asses Repe Comp Penta Speci NOAE Applic	ated dose toxicity ponents: afluoroethane: es EL cation Route	: N ti : F : > : ir	lo significant he ons of 250 ppn at = 50000 ppm shalation (gas)	ealth effects observed in animals at concen iV/6h/d or less.
Route Asses Repe Comp Penta Speci NOAE Applic	ated dose toxicity ponents: afluoroethane: es EL cation Route sure time	: N ti : F : > : ir : 1	lo significant he ons of 250 ppn at = 50000 ppm	ıV/6h/d or less. `
Route Asses Reper Comm Penta Speci NOAE Applic Expos Metho	ated dose toxicity ponents: afluoroethane: es EL cation Route sure time od	: N ti : F : > : ir : 1 : C	lo significant he ons of 250 ppn at = 50000 ppm shalation (gas) 3 Weeks	νV/6h/d or less.
Route Asses Reper Comm Penta Speci NOAE Applic Expos Metho	es of exposure assment ated dose toxicity <u>ponents:</u> afluoroethane: es EL cation Route sure time od 2-Tetrafluoroethane:	: N ti : F : > : ir : 1 : C	lo significant he ons of 250 ppn at = 50000 ppm shalation (gas) 3 Weeks	deline 413




## Freon™ 407A (R-407A) Refrigerant

Version 8.4	Revision Date: 10/11/2020		3 Number: 6195-00039	Date of last issue: 02/27/2020 Date of first issue: 02/27/2017					
Appl Expo	LOAEL Application Route Exposure time Method		: >50000 ppm : inhalation (gas) : 2 y : OECD Test Guideline 453						
Spec NOA LOA Appl	AEL EL lication Route osure time		Rat, male and fen 49100 ppm > 49100 ppm inhalation (gas) 13 Weeks OECD Test Guide						
-	iration toxicity classified based on availa	ıble ir	nformation.						
Con	<u>iponents:</u>								
	1,2-Tetrafluoroethane: aspiration toxicity classific	ation							
No a	uoromethane: aspiration toxicity classific 12. ECOLOGICAL INF( toxicity		ATION						
<u>Con</u>	<u>nponents:</u>								
Pen	tafluoroethane:								
Тохі	city to fish		Exposure time: 96	hus mykiss (rainbow trout)): > 100 mg/l 3 h on data from similar materials					
	icity to daphnia and other atic invertebrates		Exposure time: 48	nagna (Water flea)): > 100 mg/l 3 h on data from similar materials					
Toxi plan	icity to algae/aquatic ts		mg/l Exposure time: 7: Method: OECD T Remarks: Based	est Guideline 201 on data from similar materials rchneriella subcapitata (green algae)): > 1 2 h					
				on data from similar materials					

#### 1,1,1,2-Tetrafluoroethane:

14/19



Version 8.4	Revision Date: 10/11/2020		S Number: 36195-00039	Date of last issue: 02/27/2020 Date of first issue: 02/27/2017
Toxicit	y to fish	:	Exposure time: 96	hus mykiss (rainbow trout)): 450 mg/l 5 h on (EC) No. 440/2008, Annex, C.1
	y to daphnia and other c invertebrates	:	Exposure time: 48	agna (Water flea)): 980 mg/l 3 h on (EC) No. 440/2008, Annex, C.2
Toxicil plants	y to algae/aquatic	:	ErC50 (green alga Exposure time: 96 Remarks: Based o	
Difluo	romethane:			
	ly to fish	:	LC50 (Fish): 1,50 Exposure time: 96 Method: ECOSAF ships)	
	ty to daphnia and other c invertebrates	:	Exposure time: 48	
Toxici plants	ty to algae/aquatic	:	EC50 (green alga Exposure time: 96 Method: ECOSAF ships)	
Persis	stence and degradabil	ity	1.10	
Comp	onents:			
	fluoroethane: gradability	:	Result: Not readil Biodegradation: 4 Exposure time: 28 Method: OECD T	5 %
	<b>2-Tetrafluoroethane:</b> gradability	:		y biodegradable. est Guideline 301D
	promethane: gradability	:	Result: Not readil Method: OECD T	y biodegradable. est Guideline 301D
Bioac	cumulative potential			
Comp	oonents:			
	fluoroethane: on coefficient: n-	:	Pow: 1.48	



## Freon™ 407A (R-407A) Refrigerant


Versi 8.4	on Revision Date: 10/11/2020	SDS Number: 1336195-00039	Date of last issue: 02/27/2020 Date of first issue: 02/27/2017
c	octanol/water	Method: OEC	D Test Guideline 107
	1,1,1,2-Tetrafluoroethane: Bioaccumulation	: Remarks: Bio	accumulation is unlikely.
	Partition coefficient: n- octanol/water	: log Pow: 1.06	
ł	<b>Difluoromethane:</b> Partition coefficient: n- octanol/water	: log Pow: 0.71	4
	<b>Mobility in soil</b> No data available		
	Other adverse effects No data available		
SECT	FION 13. DISPOSAL CONSI	IDERATIONS	
I	Disposal methods		

Waste from residues	:	Dispose of in accordance with local regulations.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty pressure vessels should be returned to the supplier. If not otherwise specified: Dispose of as unused product.

### SECTION 14. TRANSPORT INFORMATION

### International Regulations

UNRTDG		
UN number	:	UN 3338
Proper shipping name	:	REFRIGERANT GAS R 407A
Class	:	2.2
Packing group	:	Not assigned by regulation
Labels	:	2.2
IATA-DGR		
UN/ID No.	:	UN 3338
Proper shipping name	:	Refrigerant gas R 407A
Class	:	2.2
Packing group	;	Not assigned by regulation
Labels	:	Non-flammable, non-toxic Gas
Packing instruction (cargo aircraft)	:	200
Packing instruction (passen- ger aircraft)	:	200
IMDG-Code		
UN number	:	UN 3338



### Freon<sup>™</sup> 407A (R-407A) Refrigerant

Version 8.4	Revision Date: 10/11/2020	SDS Number: 1336195-00039	Date of last issue: 02/27/2020 Date of first issue: 02/27/2017
Prope	er shipping name	: REFRIGERA	NT GAS R 407A
Labe EmS	ing group	: 2.2 : Not assigned : 2.2 : F-C, S-V : no	by regulation
	sport in bulk accordi upplicable for product a	-	ARPOL 73/78 and the IBC Code
Dom	estic regulation		
	FR D/NA number er shipping name	: UN 3338 : Refrigerant g	as R 407A
Labe ERG	ing group	: 2.2 : Not assigned : NON-FLAMM : 126 : no	by regulation IABLE GAS
The t base Shee	d upon the properties	(s) provided herein a of the unpackaged n ifications may vary l	re for informational purposes only, and solely naterial as it is described within this Safety Data by mode of transportation, package sizes, and

variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity


This material does not contain any components with a section 302 EHS TPQ.


SARA 311/312 Hazards	:	Gases under pressure Simple Asphyxiant
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
US State Regulations		

Pennsylvania Right To Know	
Pentafluoroethane	354-33-6
1,1,1,2-Tetrafluoroethane	811-97-2
Difluoromethane	75-10-5
California List of Hazardous Substances	
Difluoromethane	75-10-5



### Freon<sup>™</sup> 407A (R-407A) Refrigerant





Freon<sup>™</sup> and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours<sup>™</sup> and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

#### Full text of other abbreviations

US WEEL	:	USA. Workplace Environmental Exposure Levels (WEEL)
US WEEL / TWA	:	8-hr TWA

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EMS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% response; EMS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime



### Freon<sup>™</sup> 407A (R-407A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 02/27/2020
8.4	10/11/2020	1336195-00039	Date of first issue: 02/27/2017

Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory: LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships: MSHA - Mine Safety and Health Administration: n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG -United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to	:	Internal technical data, data from raw material SDSs, OECD
compile the Material Safety Data Sheet		eChem Portal search results and European Chemicals Agen- cy, http://echa.europa.eu/
Data Offeet		cy, http://cond.col/opa.col/

**Revision** Date

10/11/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8

.