

ZR16K5E-PFV

HCFC, R-22, 60 Hz, 1 - Phase, 208/230 V

## Air Conditioning

**Production Status:** Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Performance			Mechanical	
Evaporator Temp. (°F)	45.00	45	Displacement (in^3/Rev):	1.31
Condensing Temp. (°F)	130.00	100	Displacement (ft^3/Hr):	
Return Gas Temp. (°F)	65.00	65	Overall Length (in):	9.69
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.69
Capacity (BTU/hr)	15500	18400	Overall Height (in):	15.25
Power (W):	1485	1010	Mounting Length (in):	7.50
Current (Amps):	6.3	4.5	Mounting Width (in):	7.50
EER(BTU/Wh):	10.45	18.2	Mounting Height (in):	16.00
Mass Flow (lbs/hr):	227	237	Suction Size (in),Type:	3 / 4 Stub
Sound Data @			Discharge Size (in),Type:	1 / 2 Stub
Sound Power (dBA):	68 Avg	73 Max	Initial Oil Charge (oz):	25
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	Oil Recharge (oz):	19
Record Date:	2025-04-11		Oil Type:	3MA
			Net Weight (lbs):	47.7
			Internal Free Volume (in^3):	128.0
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors					
LRA High* (Amps):	40.3	Type	Part No	Low MFD	High MFD	Volt s	User Description
LRA Low*(Amps):		Run Capacitor	014-0064-06	30.0	0.0	370	
LRA Half Winding (Amps):							
MCC (Amps):	13	Start Capacitor	014-0061-27	88.0	106.0	330	
Max Operating Current (Amps):	9.00						
RLA, MCC/1.4(use for contactor selection)(Amps):	9.3						
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	8.3						
RPM:	3500						
Box IP :	21						
UL File No:							
UL File Date:							

\*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

## Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
-------------	---------	-------	-----------	-------------

