

ZR19M3E-TWC

HFC, R-407C, 60 Hz, 3 - Phase, 208/230 V , [Also Available with Variable Frequency Drives](#)

Air Conditioning

Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Copeland Wholesaler. Please check with your local Copeland Representative for international availability.

Performance			Mechanical	
Evaporator Temp. (°F)	45.00	45	Displacement (in^3/Rev):	15.00
Condensing Temp. (°F)	130.00	100	Displacement (ft^3/Hr):	
Return Gas Temp. (°F)	65.00	65	Overall Length (in):	12.60
Liquid Temp. (°F)	115.00	85	Overall Width (in):	13.80
Capacity (BTU/hr)	185000	222000	Overall Height (in):	23.30
Power (W):	16700	11400	Mounting Length (in):	8.70
Current (Amps):	48.3	36	Mounting Width (in):	8.70
EER(BTU/Wh):	11.1	19.5	Mounting Height (in):	23.50
Mass Flow (lbs/hr):	2690	2760	Suction Size (in),Type:	2 1 / 4
Sound Data @			Discharge Size (in),Type:	1 3 / 4
Sound Power (dBA):	83 Avg	88 Max	Initial Oil Charge (oz):	140
Vibration mils(peak-peak):	2.5 Avg	3.5 Max	Oil Recharge (oz):	137
Record Date:	2007-12-04		Oil Type:	3MA
			Net Weight (lbs):	236.0
			Internal Free Volume (in^3):	1120.0
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors				
LRA High* (Amps):	425	Type	Part No	Low MFD	High MFD	Volts User Description
LRA Low*(Amps):		No data available in table				
LRA Half Winding (Amps):						
MCC (Amps):	77					
Max Operating Current (Amps):	69.00					
RLA, MCC/1.4(use for contactor selection)(Amps):	55.0					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	49.4					
RPM:	3500					
Box IP :	54					
UL File No:	SA-9747					
UL File Date:	1994-07-12					

European Pressure Equipment Directive (PED):

Fluid Group**:	FG 2
PS Low / High Side (BAR):	22.6 / 32.0
TS Min (°C):	-35 / -35
TS Max (°C):	50 / 150
Volume (L) :	3.1 / 15.5

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications				
Refrigerant	Voltage	Phase	Frequency	Application
R-134a HFC	200	3	50	Air Conditioning
R-134a HFC	208/230	3	60	Air Conditioning
R-407C HFC	200	3	50	Air Conditioning