

ZR44K5E-PFV

HFC, R-407C, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Performance			Mechanical	
Evaporator Temp. (°F)	45.00	50	Displacement (in^3/Rev):	3.56
Condensing Temp. (°F)	130.00	100	Displacement (ft^3/Hr):	
Return Gas Temp. (°F)	65.00	70	Overall Length (in):	9.70
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.70
Capacity (BTU/hr)	42200	56500	Overall Height (in):	16.40
Power (W):	4000	2640	Mounting Length (in):	7.50
Current (Amps):	17.8	12.5	Mounting Width (in):	7.50
EER(BTU/Wh):	10.55	21.4	Mounting Height (in):	17.20
Mass Flow (lbs/hr):	614	696	Suction Size (in),Type:	7 / 8 Stub
Sound Data @ 45 / 130			Discharge Size (in),Type:	1 / 2 Stub
Sound Power (dBA):	70 Avg	75 Max	Initial Oil Charge (oz):	42
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	Oil Recharge (oz):	34
Record Date:	2015-10-13		Oil Type:	3MA
			Net Weight (lbs):	68.1
			Internal Free Volume (in^3):	191.1
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors				
LRA High* (Amps):	137	Type	Part No	Low MFD	High MFD	Volt s User Description
LRA Low*(Amps):		Run Capacitor	014-0064-26	60.0	0.0	370
LRA Half Winding (Amps):		Start Capacitor	014-0061-27	88.0	106.0	330
MCC (Amps):	31.5					
Max Operating Current (Amps):	29.00					
RLA, MCC/1.4(use for contactor selection)(Amps):	22.5					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	20.2					
RPM:	3500					
Box IP :	21					
UL File No:	SA2337-20031217					
UL File Date:	2003-12-17					

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
-------------	---------	-------	-----------	-------------