Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Copeland Wholesaler. Please check with your local Copeland Representative for international availability.

| Performance | | | Mechanical | | |
|---|------------|---------------------|--|-------------------|--|
| Evaporator Temp. (°F) | 45.00 | 45 | Displacement (in^3/Rev): | 4.71 | |
| Condensing Temp. (°F) | 130.00 | 100 | Displacement (ft^3/Hr): | | |
| Return Gas Temp. (°F) | 65.00 | 65 | Overall Length (in): | 9.70 | |
| Liquid Temp. (°F) | 115.00 | 85 | Overall Width (in): | 9.80 | |
| Capacity (BTU/hr) | 58500 | 68500 | Overall Height (in): | 17.20 | |
| Power (W): | 4980 | 3430 | Mounting Length (in): | 7.50 | |
| Current (Amps): | 14.5 | 11.1 | Mounting Width (in): | 7.50 | |
| EER(BTU/Wh): | 11.7 | 20 | Mounting Height (in): | 18.00 | |
| Mass Flow (lbs/hr): | 860 | 880 | Suction Size (in),Type: | 7 / 8 Stub | |
| Sound Data @ | | | Discharge Size (in),Type: | 1 / 2 Stub | |
| Sound Power (dBA): | 74 Avg | 79 Max | Initial Oil Charge (oz): | 66 | |
| Vibration mils(peak-peak): | 2.0 Avg | 3.0 Max | Oil Recharge (oz): | 62 | |
| Record Date: | 2014-03-06 | | Oil Type: | ЗМА | |
| | | | Net Weight (lbs): | 85.0 | |
| | | | Internal Free Volume (in^3): | 257.0 | |
| | | | *Overall compressor height on Copeland Brand Promounting grommets. | oduct's specified | |
| Electrical | | | Capacitors | | |
| LRA High* (Amps): | | 123 | Type Part No Low MFD High MFD Volts Us | ser Description | |
| LRA Low*(Amps): | | | No data available in table | | |
| LRA Half Winding (Amps): | | | | | |
| MCC (Amps): | | 27 | | | |
| Max Operating Current (Amps): | | 18.00 | | | |
| RLA, MCC/1.4(use for contactor selection)(Amps): | | 19.3 | | | |
| RLA, MCC/1.56(use for breaker & Dreaker & State Selection)(Amps): | | 17.3 | | | |
| RPM: | | 3500 | | | |
| Box IP : | | 21 | | | |
| UL File No: | | SA2337- 19930726 | | | |
| UL File Date: | | 1993-07- 26 | | | |
| *Low and High refer to the low and high nominal voltage ranges for which the motor is approved. | | | | | |

Alternate Applications

| Refrigerant | Voltage | Phase | Frequency | Application |
|-------------|---------|-------|-----------|------------------|
| R-22 HCFC | 200/220 | 3 | 50 | Air Conditioning |
| R-407C HFC | 200/220 | 3 | 50 | Air Conditioning |
| R-407C HFC | 200/230 | 3 | 60 | Air Conditioning |