

ZR61KCE-TF5

HFC, R-407C, 60 Hz, 3 -Phase, 200/230 V
Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45	45
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	115	85
Capacity (Btu/hr)	60000	71700
Power (W):	5460	3850
Current (Amps):	16.55	13.20
EER (Btu/Wh):	11.00	18.65
Mass Flow (lbs/hr):	867	886
<u>Sound Data @</u>		
Sound Power (dBA):	74 Avg	79 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2015-12-16	

Mechanical

Displacment(in ³ /Rev):	5.04
Displacment(ft ³ /hr):	612.50
Overall Length (in):	9.69
Overall Width (in):	9.69
Overall Height (in):	17.75
Mounting Length (in):	7.50
Mounting Width (in):	7.50
Mounting Height (in):	18.00 *
Suction Size (in),Type:	7/8 Stub
Discharge Size (in),Type:	1/2 Stub
Initial Oil Charge (oz):	66
Oil Recharge (oz):	62
Net Weight (lbs):	78.0
Internal Free Volume (in ³):	272.0
Horse Power:	5.00

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*(Amp):	128.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	29.0
Max Operating Current(Amp):	25.0
RLA, MCC/1.4;use for contactor selection (Amp):	20.7
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	18.6
RPM:	3500
UL File No:	SA-2337
UL File Date:	1993-07-26

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-134a HFC	200/220	3	50	Air Conditioning
R-134a HFC	200/230	3	60	Air Conditioning
R-407C HFC	200/220	3	50	Air Conditioning