

ZR68KCE-PFV

HFC, R-407C, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Performance			Mechanical	
Evaporator Temp. (°F)	45.00	45	Displacement (in^3/Rev):	5.68
Condensing Temp. (°F)	130.00	100	Displacement (ft^3/Hr):	
Return Gas Temp. (°F)	65.00	65	Overall Length (in):	9.70
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.80
Capacity (BTU/hr)	65800	79100	Overall Height (in):	17.20
Power (W):	6220	4420	Mounting Length (in):	7.50
Current (Amps):	28.7	21	Mounting Width (in):	7.50
EER(BTU/Wh):	10.6	17.9	Mounting Height (in):	18.00
Mass Flow (lbs/hr):	951	977	Suction Size (in),Type:	7 / 8 Stub
Sound Data @			Discharge Size (in),Type:	1 / 2 Stub
Sound Power (dBA):	75 Avg	80 Max	Initial Oil Charge (oz):	60
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	Oil Recharge (oz):	56
Record Date:	2014-08-05		Oil Type:	3MA
			Net Weight (lbs):	89.0
			Internal Free Volume (in^3):	234.0
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors				
LRA High* (Amps):	176	Type	Part No	Low MFD	High MFD	Volt s User Description
LRA Low*(Amps):		Run Capacitor	014-0064-35	80.0	0.0	440
LRA Half Winding (Amps):						
MCC (Amps):	45					
Max Operating Current (Amps):	36.00					
RLA, MCC/1.4(use for contactor selection)(Amps):	32.1					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	28.8					
RPM:	3500					
Box IP :	21					
UL File No:	SA2337-19930726					
UL File Date:	1993-07-26					

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications				
Refrigerant	Voltage	Phase	Frequency	Application
R-134a HFC	208/230	1	60	Air Conditioning