

# NYLOG

**It's a Sealant:** Nylog is a viscoelastic fluid made from refrigeration grade compressor oil. Gaskets coated with Nylog will never dry or become heat fixed to the surface. Threaded connections coated with Nylog will prevent high pressure leaks by forming a hydraulic seal. The compound always remains temperature and vibration resilient.

**It's a Lubricant:** Nylog can be used as a high tack assembly lube when installing shaft seals, o-rings, schrader valves, ball valves, unloaders or other system components. Nylog is fully miscible and 100% compatible with the refrigerant and base compressor oils.

**NYLOG RED** Is based on Mineral Oil and used on Ammonia, Propane, CFC or HCFC systems.

**NYLOG BLUE** is synthetic ester oils fully compatible with all systems including those based on PVE oil, HFO refrigerants and CO2.

Will Never Harden or Dry

Will Not Clog or Contaminate Systems

Fully Compatible and Miscible

Used and Recommended by OEM's



NYLOG RED	
Base	Mineral Oil
Application	CFC or HCFC Systems
Temp Range	-30 to 350 F
Size	30ml

NYLOG BLUE	
Base	Synthetic Ester Oils
Application	HFC Systems
Temp Range	-35 to 425 F
Size	30ml



Registered for use in all food processing areas.